

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- . Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41
- . 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- . Application of the substance / the mixture Adhesive
- . 1.3 Details of the supplier of the safety data sheet
- Manufacturer(1)/Supplier(2):

1

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- . Further information obtainable from: Bison QESH
- . **1.4 Emergency telephone number:** +31 88 3235700

SECTION 2: Hazards identification

- . 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- . 2.2 Label elements
- . Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

. Hazard pictograms



GHS07

- . Signal word Warning
- Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
- . Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

EU-EN

www.griffon.eu 1/8



Safety data sheet according to 1907/2006/EC, Article 31

Version number 96 Revision: 11.09.2018 Printing date 09.10.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 1)

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children. Avoid breathing vapours. P261

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

. ==>> Labelling of packages where the contents do not exceed 125 ml

. Hazard pictograms



. Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

. Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

. Results of PBT and vPvB assessment

. **PBT:** Not applicable.

. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

. 3.2 Mixtures

. **Description:** Adhesive

. Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5

(number average molecular weight ≤ 700) Aquatic Chronic 2, H411; 🐧 Skin Irrit. 2, H315; Eye Irrit. Reg.nr.: 01-2119456619-26 2, H319; Skin Sens. 1, H317

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin

(Contd. on page 3)

2/8 www.griffon.eu



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 2)

CAS: 90-72-2

2,4,6-tris(dimethylaminomethyl)phenol

1-2.5%

EINECS: 202-013-9 Reg.nr.: 01-2119560597-27 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319

. Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- . 4.1 Description of first aid measures
- . General information: No special measures required.
- . After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- . After swallowing: Do not induce vomiting; call for medical help immediately.
- . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- . 5.3 Advice for firefighters
- . Protective equipment: No special measures required.

SECTION 6: Accidental release measures

. 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

. 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

- EU-EN -

www.griffon.eu 3/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- . Information about fire and explosion protection: No special measures required.
- . 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- . Requirements to be met by storerooms and receptacles: No special requirements.
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.
- . 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- . Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- . Additional information: The lists valid during the making were used as basis.
- . 8.2 Exposure controls
- . Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- . Respiratory protection: Not required.
- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

Recommended thickness of the material: > 0,12 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

(Contd. on page 5)

EU-EN

www.griffon.eu 4/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 4)

. Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye protection:



Tightly sealed goggles

. Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

. 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.pH-value: Not determined.

. Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

. Flash point: 201 °C

. Flammability (solid, gas): Not applicable.. Decomposition temperature: Not determined.

. Auto-ignition temperature: Product is not selfigniting.

. **Explosive properties:** Product does not present an explosion hazard.

. Explosion limits:

Lower:Not determined.Upper:Not determined.

. Vapour pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

Evaporation rate Not determined.

Not determined.

. Solubility in / Miscibility with

water: Not miscible or difficult to mix.

. Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)

EU-EN

www.griffon.eu 5/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 5)

. Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- . Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- . 10.3 Possibility of hazardous reactions Reacts with amines.
- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity Based on available data, the classification criteria are not met.
- . Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

. Serious eye damage/irritation

Causes serious eye irritation.

. Respiratory or skin sensitisation

May cause an allergic skin reaction.

- . CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity Based on available data, the classification criteria are not met.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . STOT-single exposure Based on available data, the classification criteria are not met.
- . STOT-repeated exposure Based on available data, the classification criteria are not met.
- . Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- . Ecotoxical effects:
- . Remark: Harmful to fish

(Contd. on page 7)

EU-EN

www.griffon.eu 6/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 6)

(Contd. on page 8)

. Additional ecological information:

. General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- . 12.5 Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- . 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number ADR/ADN, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Another Marpol and the IBC Code	nex II Not applicable.
Transport/Additional information:	
IMDG	
Remarks:	Under certain conditions substances in Class (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

www.griffon.eu 7/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2018 Version number 96 Revision: 11.09.2018

Trade name: GRIFFON EPOXY REPAIR STICK 114G*12 L41

(Contd. of page 7)

. UN "Model Regulation":

SECTION 15: Regulatory information

. 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Void

- . Directive 2012/18/EU
- . Named dangerous substances ANNEX I None of the ingredients is listed.
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- . **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

. Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- . Department issuing SDS: Bison QESH
- . Contact: Reach coördinator

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

EU-EN

www.griffon.eu 8/8