

6180006 - BK SUPERCH FBX 125G*24 IT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: BK SUPERCH FBX 125G*24 IT

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive

• 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

	of the substance or mixture cording to Regulation (EC) No 1272/2008
Flam. Liq. 2	H225 Highly flammable liquid and vapour.
GHS07	
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
 · 2.2 Label element · Labelling accord	ts ing to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

(Contd. of page 1)

Trade name: BK SUPERCH FBX 125G*24 IT

· Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: methylcyclohexane
- butanone
- ethyl acetate
- acetone
- **Hazard statements**
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fireextinguishing powder, Carbon dioxide.
- P501 Dispose of contents/container in accordance with national regulations.
- · Additional information:
- EUH208 Contains Rosin. May produce an allergic reaction.
- · Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



· Signal word Danger

- **Hazard-determining components of labelling:** methylcyclohexane butanone ethyl acetate
- acetone
- · Hazard statements
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

(Contd. on page 3)

EU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

(Contd. of page 2)

List II

Trade name: BK SUPERCH FBX 125G*24 IT

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 butanone

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

methylcyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Achi Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
butanone Flam. Liq. 2, H225;	10-25%
ethyl acetate Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
acetone Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
Butylphenolformaldehyde resin Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%
Rosin Skin Sens. 1, H317	≥0.1-<1%
zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
-	 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Butylphenolformaldehyde resin Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Rosin Skin Sens. 1, H317 zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1,

(Contd. on page 4)



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Water haze
- Alcohol resistant foam
- Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 5)

FU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

(Contd. of page 4)

Trade name: BK SUPERCH FBX 125G*24 IT

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

78-93-3 b	utanone		
	V Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm		
	ethyl acetate		
IOELV Short-term value: 1468 mg/m ³ , 400 ppm			
Long-term value: 734 mg/m³, 200 ppm			
67-64-1 a	cetone		
IOELV La	ng-term value: 1210 mg/m³, 500 ppm		
DNELs			
78-93-3 bi	utanone		
Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day	
Inhalative	Consumer, inhalative, longterm exposition	106 mg/m³	
141-78-6 (ethyl acetate		
Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition	37 mg/kg bw/day	
Inhalative	Consumer DNEL, acute inhalation	734 mg/m³	
	Consumer, inhalative, longterm exposition	367 mg/m³	



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

Oral	tone			
- ·	Consumer, oral, longterm exposition 62 mg/kg bw/day			
Dermal Consumer, dermal, longterm exposition 62 mg/kg bw/day				
Inhalative Consumer, inhalative, longterm exposition 200 mg/m ³				
PNECs				
78-93-3 butanone				
Fresh wate				
Marine wa	r 55.8 mg/l			
Soil	22.5 mg/kg			
141-78-6 ethyl acetate				
Fresh wate	5			
Marine wa	r 0.026 mg/l			
Soil	0.22 mg/kg			
67-64-1 ac				
Fresh wate				
Marine wa	r 1.06 mg/l			
Soil	29.5 mg/kg			
Keep away	recautionary measures are to be adhered to when handling chemicals. from foodstuffs, beverages and feed.			
Immediate Wash ham Do not inh Avoid cont Respirato Use suitab Recomme Filter AX Filter A Hand prot	from foodstuffs, beverages and feed. remove all soiled and contaminated clothing before breaks and at the end of work. e gases / fumes / aerosols. ct with the eyes and skin. / protection: e respiratory protective device in case of insufficient ventilation. ded filter device for short term use:			
Immediate Wash ham Do not inh Avoid cont Respirato Use suitab Recomme Filter AX Filter A Hand prot Solvent res Control The glove preparation	from foodstuffs, beverages and feed. remove all soiled and contaminated clothing s before breaks and at the end of work. e gases / fumes / aerosols. ct with the eyes and skin. / protection: a respiratory protective device in case of insufficient ventilation. ded filter device for short term use: ction stant gloves rotective gloves material has to be impermeable and resistant to the product/ the substance the glove material on consideration of the penetration times, rates of diffusion and			

(Contd. on page 7)

⁻ EU -



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

(Contd. of page 6)

Trade name: BK SUPERCH FBX 125G*24 IT

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

- · Penetration time of glove material
- For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling **Body protection:** Use protective suit. Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties		
General Information		
· Physical state	Fluid	
· Colour:	Yellow	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
Boiling point or initial boiling point and		
boiling range	55.8-56.6 °C	
· Flammability	Highly flammable.	
· Lower and upper explosion limit	<u> </u>	
· Lower:	1.8 Vol %	
· Upper:	11.5 Vol %	
Flash point:	-4 °C	
Auto-ignition temperature:	260 °C	
Decomposition temperature:	Not determined.	
· pH	Not determined.	
· Viscosity:		
· Kinematic viscosity	Not determined.	
· Dynamic at 20 °C:	2500 mPas	
Solubility		
· water:	Not miscible or difficult to mix.	
 Partition coefficient n-octanol/water (log 		
value)	Not determined.	
Vapour pressure at 20 °C:	105 hPa	
Vapour pressure at 50 °C:	360 hPa	
Density and/or relative density		
· Density at 20 °C:	0.933-~0.933 g/cm³	
Relative density	Not determined.	
		(Contd. on page 8)
		EU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

	(Contd. of page
· Vapour density	Not determined.
• 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are no measurable or not relevant for the characterization of the mixture.
· Appearance:	
· Form:	Fluid
Important information on protection of heat	
and environment, and on safety. · Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	· · · ·
· Organic solvents:	77.5 %
· Water:	0.2 %
· VOC (EC)	77.45 %
· Solids content:	22.4 %
Change in condition	
· Evaporation rate	Not determined.
 Information with regard to physical haza classes 	ard
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
Self-reactive substances and mixtures	N (- 1 - 1
Sell-reactive substances and mixtures	Void
	Void Void
• Pyrophoric liquids • Pyrophoric solids	
· Pyrophoric liquids	Void
 Pyrophoric liquids Pyrophoric solids 	Void Void
 Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water 	Void Void Void Void
 Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids 	Void Void Void Void Void
 Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids 	Void Void Void Void Void Void
 Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides 	Void Void Void Void Void Void Void
 Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids 	Void Void Void Void Void Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 9)

- EU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

(Contd. of page 8)

• **10.5 Incompatible materials:** No further relevant information available. • **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

Acute tox	i city Base	n hazard classes as defined in Regulation (EC) No 1272/2008 ed on available data, the classification criteria are not met. evant for classification:
108-87-2 ו	nethylcyc	lohexane
Oral	LD50	2250 mg/kg (mouse)
78-93-3 b		·
Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
141-78-6	•	
Oral	LD50	5620 mg/kg (rabbit)
Inhalative		1600 mg/l (rat)
67-64-1 a	cetone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
1314-13-2	zinc oxid	
Oral	LD50	>5000 mg/kg (rat)
Serious e Causes se Respirato Germ cell Not applic Based on Carcinoge	erious eye ory or skin mutagen able. available c enicity Bas	e/irritation irritation. • sensitisation Based on available data, the classification criteria are not me
STOT-sin STOT-rep Aspiration Additiona	gle expos eated exp n hazard E Il toxicolo ects (acuto tion Not ap	ure May cause drowsiness or dizziness. osure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. gical information: e toxicity, irritation and corrosivity) Not applicable.
Sensitisat Repeated		n other hazards
Sensitisa Repeated 11.2 Infor	mation on	

(Contd. on page 10)



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

(Contd. of page 9)

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number		
ADR/ADN, IMDG, IATA	UN1133	
14.2 UN proper shipping name		
ADR/ADN	1133 ADHESIVES	
IMDG, IATA	ADHESIVES	



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

	(Contd. of page
• 14.3 Transport hazard class(es)	
· ADR/ADN	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
	3 Flammable liquids.
	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
 14.5 Environmental hazards: Marine pollutant: 	No
14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code): EMS Number: 	- F-E,S-D
· Stowage Category	A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN	
 Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1
LAUSPIEU quantities (LQ)	Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100
· Transport category	ml 3
· Tunnel restriction code	Ē
·IMDG	
· Limited quantities (LQ)	5L October 51
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100
· Remarks:	ml Under certain conditions substances in Class
· Remarks:	(flammable liquids) can be classified packinggroup III.
	(Contd. on page

EU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

(Contd. of page 11)

3

3

3

3

UN "Model Regulation":

UN 1133 ADHESIVES, 3, III

See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

- None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- · Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

67-64-1 acetone

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

67-64-1 acetone

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 13)

EU



Printing date 25.01.2024

Version number 35 (replaces version 34)

Revision: 25.01.2024

Trade name: BK SUPERCH FBX 125G*24 IT

according to Regulation (EC) No 1272/2008. Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
 Department issuing SDS: Bison QESH Contact: Reach coordinator Date of previous version: 19.09.2022 Version number of previous version: 34 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchar the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and La EINECS: European Inventory of Existing Commercial Chem ELINGS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Irrit. 2: Skin sensitisation – Category 1 	nical Substances