

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer(1)/Supplier(2):

1

Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

Further information obtainable from: Bison QESH

1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

EU-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 1)

Lact. H362 May cause harm to breast-fed children.
Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues
butane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P263 Avoid contact during pregnancy/while nursing.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

EU-EN

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Sealant**Dangerous components:**

CAS: 9016-87-9 EINECS: 202-966-0 Reg.nr.: 01-2119457024-46	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 85535-85-9 EINECS: 287-477-0	alkanes, C14-17, chloro ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	2.5-10%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	2.5-10%
CAS: 106-97-8 EINECS: 203-448-7	butane ⚠ Flam. Gas 1, H220; ⚠ Acute Tox. 3, H331; Press. Gas C, H280	2.5-10%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ⚠ Press. Gas L, H280	2.5-10%

Additional information:

Propellant: CO2

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

EU-EN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 3)

- . **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- . **5.1 Extinguishing media**
. **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- . **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- . **5.3 Advice for firefighters**
. **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- . **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- . **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- . **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- . **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- . **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
. **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- . **7.2 Conditions for safe storage, including any incompatibilities**
. **Storage:**
. **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
. **Information about storage in one common storage facility:** Not required.
. **Further information about storage conditions:** Keep receptacle tightly sealed.
- . **7.3 Specific end use(s)** No further relevant information available.

EU-EN

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

. **Additional information about design of technical facilities:** No further data; see item 7.

. 8.1 Control parameters

. **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

124-38-9 carbon dioxide

IOELV Long-term value: 9000 mg/m³, 5000 ppm

. **Additional information:** The lists valid during the making were used as basis.

. 8.2 Exposure controls

. **Personal protective equipment:**

. **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

. **Respiratory protection:** Not required.

. **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. **Material of gloves**

Recommended thickness of the material: > 0,12 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

. **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

. **Eye protection:**

Safety glasses



Tightly sealed goggles

(Contd. on page 6)

EU-EN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 5)

. **Body protection:** Use protective suit.

SECTION 9: Physical and chemical properties

. 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

. pH-value: Not determined.

. Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44 °C

. Flash point: -97 °C

. Flammability (solid, gas): Not applicable.

. Ignition temperature: 235 °C

. Decomposition temperature: Not determined.

. Auto-ignition temperature: Product is not selfigniting.

. Explosive properties: Not determined.

. Explosion limits:

Lower:	1.8 Vol %
Upper:	8.5 Vol %

. Vapour pressure at 20 °C: 0.1 hPa

. Density at 20 °C: 0.98 g/cm³

. Relative density: Not determined.

. Vapour density: Not determined.

. Evaporation rate: Not applicable.

. Solubility in / Miscibility with water:

Not miscible or difficult to mix.

. Partition coefficient: n-octanol/water: Not determined.

. Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

Organic solvents: 20.4 %

. 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

EU-EN

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 6)

SECTION 10: Stability and reactivity

- . **10.1 Reactivity** No further relevant information available.
- . **10.2 Chemical stability**
- . **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- . **10.3 Possibility of hazardous reactions**
Reacts with alcohols.
Reacts with water.
Reacts with alkali, amines and strong acids.
- . **10.4 Conditions to avoid** No further relevant information available.
- . **10.5 Incompatible materials:** No further relevant information available.
- . **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . **11.1 Information on toxicological effects**
- . **Acute toxicity**
Harmful if inhaled.
- . **LD/LC50 values relevant for classification:**

115-10-6 dimethyl ether		
Inhalative	LC50/4 h	308 mg/l (rat)
106-97-8 butane		
Inhalative	LC50/4 h	658 mg/l (rat)
- . **Primary irritant effect:**
- . **Skin corrosion/irritation**
Causes skin irritation.
- . **Serious eye damage/irritation**
Causes serious eye irritation.
- . **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- . **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- . **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- . **Carcinogenicity**
Suspected of causing cancer.
- . **Reproductive toxicity**
May cause harm to breast-fed children.
- . **STOT-single exposure**
May cause respiratory irritation.
- . **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- . **Aspiration hazard** Based on available data, the classification criteria are not met.

EU-EN

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 7)

SECTION 12: Ecological information

- . **12.1 Toxicity**
- . **Aquatic toxicity:** No further relevant information available.
- . **12.2 Persistence and degradability** No further relevant information available.
- . **12.3 Bioaccumulative potential** No further relevant information available.
- . **12.4 Mobility in soil** No further relevant information available.
- . **Additional ecological information:**
- . **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- . **12.5 Results of PBT and vPvB assessment**
- . **PBT:** Not applicable.
- . **vPvB:** Not applicable.
- . **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- . **13.1 Waste treatment methods**
- . **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- . **Uncleaned packaging:**
- . **Recommendation:**
Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- . **14.1 UN-Number**
- . **ADR/ADN, IMDG, IATA** UN1950
- . **14.2 UN proper shipping name**
- . **ADR/ADN** 1950 AEROSOLS
- . **IMDG** AEROSOLS
- . **IATA** AEROSOLS, flammable

- . **14.3 Transport hazard class(es)**

- . **ADR/ADN**



- . **Class** 2 5F Gases.

(Contd. on page 9)

EU-EN

Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 8)

. Label	2.1
. IMDG, IATA	
	
. Class	2.1
. Label	2.1
. 14.4 Packing group	
. ADR/ADN, IMDG, IATA	Void
. 14.5 Environmental hazards:	
. Marine pollutant:	No
. 14.6 Special precautions for user	
. Danger code (Kemler):	Warning: Gases.
. EMS Number:	-
. Stowage Code	F-D,S-U
. Segregation Code	
SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.	
. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
. Transport/Additional information:	
. ADR/ADN	
. Limited quantities (LQ)	1L
. Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
. Transport category	2
. Tunnel restriction code	D
. IMDG	
. Limited quantities (LQ)	1L
. Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
. Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

(Contd. on page 10)

EU-EN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 9)

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- . **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- . **Directive 2012/18/EU**
- . **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- . **Seveso category P3a** FLAMMABLE AEROSOLS
- . **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- . **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- . **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- . **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . **Relevant phrases**
 - H220 Extremely flammable gas.
 - H280 Contains gas under pressure; may explode if heated.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - H335 May cause respiratory irritation.
 - H351 Suspected of causing cancer.
 - H362 May cause harm to breast-fed children.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
- . **Department issuing SDS:** Bison QESH
- . **Contact:**
 - Marketing UHU BOSTIK
 - Reach coördinator
- . **Abbreviations and acronyms:**
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

EU-EN



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.10.2018

Version number 17

Revision: 10.02.2018

Trade name: BOSTIK PU UNIVERSALE GUN B3 750ML*12 IT

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Press. Gas L: Gases under pressure – Liquefied gas
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
*** Data compared to the previous version altered.**

EU-EN