

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** GRF UNI-100 XT FB 125ML\*30 L1
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Bison International  
Dr.A.F.Philipsstraat 9  
NL-4462 EW Goes  
PO Box 160  
NL-4460 AD Goes  
tel. +31 88 3235700  
fax. +31 88 3235800  
e mail: sds@boltonadhesives.com
- **Further information obtainable from:** Bison QESH
- **1.4 Emergency telephone number:** +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
butanone
- **Hazard statements**  
H225 Highly flammable liquid and vapour.

(Contd. on page 2)

EU-EN

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P261 Avoid breathing vapours.

P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butanone

· **Hazard statements**

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

\* **SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

· **Description:** Adhesive

(Contd. on page 3)

EU-EN

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 2)

**· Dangerous components:**

CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46 01-2119555270-46	Butylated hydroxytoluene ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

**· Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.  
No special measures required.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Alcohol resistant foam  
Fire-extinguishing powder  
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

EU-EN

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 3)

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**Storage class:** 3**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**8.1 Control parameters****Additional information about design of technical facilities:** No further data; see item 7.**Ingredients with limit values that require monitoring at the workplace:****78-93-3 butanone**IOELV Short-term value: 900 mg/m<sup>3</sup>, 300 ppmLong-term value: 600 mg/m<sup>3</sup>, 200 ppm**DNELs****78-93-3 butanone**

Oral Consumer, oral, longterm exposition 31 mg/kg bw/day

Dermal Consumer, dermal, longterm exposition 412 mg/kg bw/day

(Contd. on page 5)

EU-EN

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 4)

Inhalative	Consumer, inhalation, longterm exposition	106 mg/m <sup>3</sup>
<b>· PNECs</b>		
<b>78-93-3 butanone</b>		
Fresh water	55.8 mg/l	
Marine water	55.8 mg/l	
Soil	22.5 mg/kg	

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

· **Recommended filter device for short term use:** Filter A

· **Protection of hands:**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: > 0,7 mm

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· **Eye protection:**



Tightly sealed goggles

Goggles recommended during refilling

· **Body protection:** Solvent resistant protective clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Fluid

(Contd. on page 6)

EU-EN

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 5)

<b>Colour:</b>	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	79-80.5 °C
· <b>Flash point:</b>	-9 °C
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	514 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.8 Vol %
<b>Upper:</b>	11.5 Vol %
· <b>Vapour pressure at 20 °C:</b>	105 hPa
· <b>Density at 20 °C:</b>	0.96-0.962 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	1450 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	77.2 %
<b>Water:</b>	0.0 %
<b>Solids content:</b>	22.7 %
· <b>9.2 Other information</b>	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

EU-EN

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
  - **Acute toxicity** Based on available data, the classification criteria are not met.
- | LD/LC50 values relevant for classification: |      |                     |
|---|------|---------------------|
| <b>78-93-3 butanone</b>                     |      |                     |
| Oral  | LD50 | 3300 mg/kg (rat)    |
| Dermal                                      | LD50 | 5000 mg/kg (rabbit) |
| <b>128-37-0 Butylated hydroxytoluene</b>    |      |                     |
| Oral  | LD50 | 890 mg/kg (rat)     |
- **Primary irritant effect:**
  - **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
  - **Serious eye damage/irritation**  
Causes serious eye irritation.
  - **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
  - **Additional toxicological information:**
  - **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
  - **Sensitisation** Not applicable.
  - **Repeated dose toxicity** Not applicable.
  - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
  - **Germ cell mutagenicity** Not applicable.
  - **Carcinogenicity** Based on available data, the classification criteria are not met.
  - **Reproductive toxicity** Based on available data, the classification criteria are not met.
  - **STOT-single exposure**  
May cause drowsiness or dizziness.
  - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
  - **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 8)

EU-EN

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1



(Contd. of page 7)

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b>	
· <b>ADR/ADN, IMDG, IATA</b>	UN1133
· <b>14.2 UN proper shipping name</b>	
· <b>ADR/ADN</b>	1133 ADHESIVES
· <b>IMDG, IATA</b>	ADHESIVES
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR/ADN</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids.
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>14.4 Packing group</b>	
· <b>ADR/ADN, IMDG, IATA</b>	III

(Contd. on page 9)

EU-EN



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 8)

· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> Warning: Flammable liquids.	
· <b>Hazard identification number (Kemler code):</b> -	
· <b>EMS Number:</b>	F-E,S-D
· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> Not applicable.	
· <b>Transport/Additional information:</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>ADR/ADN</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Remarks:</b>	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, 3, III

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 10)

EU-EN

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.06.2021

Version number 28

Revision: 19.06.2021

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 9)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Serious eye damage/eye irritation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Bison QESH

- **Contact:** Reach coordinator

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

- **\* Data compared to the previous version altered.**

EU-EN