

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** BTK 5242/C TI 400ML*12 IT
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com
- **Further information obtainable from:** Bison QESH
- **1.4 Emergency telephone number:** +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 1)

Hazard pictograms

GHS02 GHS07 GHS09

Signal word Danger**Hazard-determining components of labelling:**methylcyclohexane
acetone
ethyl acetate
butanone**Hazard statements**H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.**Precautionary statements**P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 Avoid breathing vapours.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with national regulations.**Additional information:**

EUH208 Contains Rosin. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.
vPvB: Not applicable.**Determination of endocrine-disrupting properties**

78-93-3 | butanone

List II

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Adhesive

(Contd. on page 3)

EU-EN

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 2)

· Dangerous components:		
CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18	methylcyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-XXXX	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32	Rosin ⚠ Skin Sens. 1, H317	≥0.1-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
CAS: 68610-51-5 EINECS: 271-867-2 Reg.nr.: 01-2119496062-39-0000	phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene ⚠ Repr. 2, H361d; Aquatic Chronic 4, H413	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** No special measures required.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

EU-EN

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - Water haze
 - Alcohol resistant foam
 - Fire-extinguishing powder
 - Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Send for recovery or disposal in suitable receptacles.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep container tightly sealed.

(Contd. on page 5)

EU-EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 4)

Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****67-64-1 acetone**IOELV Long-term value: 1210 mg/m³, 500 ppm**141-78-6 ethyl acetate**IOELV Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm**78-93-3 butanone**IOELV Short-term value: 900 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm· **DNELs****67-64-1 acetone**

Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	62 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	200 mg/m ³

141-78-6 ethyl acetate

Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	37 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	734 mg/m ³
	Consumer, inhalation, longterm exposition	367 mg/m ³

78-93-3 butanone

Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	106 mg/m ³

· **PNECs****67-64-1 acetone**

Fresh water	10.6 mg/l
Marine water	1.06 mg/l
Soil	29.5 mg/kg

141-78-6 ethyl acetate

Fresh water	0.26 mg/l
Marine water	0.026 mg/l
Soil	0.22 mg/kg

78-93-3 butanone

Fresh water	55.8 mg/l
Marine water	55.8 mg/l

(Contd. on page 6)

EU-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 5)

Soil	22.5 mg/kg
------	------------

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see item 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

- **Recommended filter device for short term use:**

Filter AX

Filter A

- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

- **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

- **Body protection:**

Use protective suit.

Solvent resistant protective clothing

EU-EN

(Contd. on page 7)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 6)

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information**

· Physical state	Fluid
· Colour:	Dark orange colour
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	55.8-56.6 °C
· Flammability	Highly flammable.
· Lower and upper explosion limit	
· Lower:	2.1 Vol %
· Upper:	13 Vol %
· Flash point:	-19 °C
· Ignition temperature:	260 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	5000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	233 hPa
· Density and/or relative density	
· Density at 20 °C:	0.923 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	77.6 %
· Water:	0.2 %
· Solids content:	22.3 %
· Change in condition	
· Evaporation rate	Not determined.

(Contd. on page 8)

EU-EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 7)

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**108-87-2 methylcyclohexane**

Oral	LD50	2250 mg/kg (mouse)
------	------	--------------------

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

(Contd. on page 9)

EU-EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 8)

78-93-3 butanone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

1314-13-2 zinc oxide

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**
Not applicable.
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

(Contd. on page 10)

EU-EN

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

Toxic for aquatic organisms

(Contd. of page 9)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packaging:**

· **Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR/ADN, IMDG, IATA**

UN1133

· **14.2 UN proper shipping name**

· **ADR/ADN**

1133 ADHESIVES

· **IMDG**

ADHESIVES, MARINE POLLUTANT

· **IATA**

ADHESIVES

· **14.3 Transport hazard class(es)**

· **ADR/ADN**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

(Contd. on page 11)

EU-EN



6305253 - BTK 5242/C TI 400ML*12 IT

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 10)

· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/ADN):	Product contains environmentally hazardous substances: methylcyclohexane Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Category	Warning: Flammable liquids. - F-E,S-D A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	U N 1 1 3 3 A D H E S I V E S , 3 , I I I , E N V I R O N M E N T A L L Y H A Z A R D O U S

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS

(Contd. on page 12)

EU-EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 11)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Regulation (EC) No 273/2004 on drug precursors**

67-64-1	acetone	3
78-93-3	butanone	3

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

67-64-1	acetone	3
78-93-3	butanone	3

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Bison QESH
- **Contact:** Reach coordinator
- **Date of previous version:** 18.01.2022
- **Version number of previous version:** 10
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 13)

EU-EN



6305253 - BTK 5242/C TI 400ML*12 IT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 11 (replaces version 10)

Revision: 03.02.2023

Trade name: BTK 5242/C TI 400ML*12 IT

(Contd. of page 12)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· * **Data compared to the previous version altered.**

EU-EN