

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK EPOXY METAL BS 56G*12 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

mercaptan polymer

bis-[4-(2,3-epoxipropoxi)phenyl]propane

(Contd. on page 2)

ΕU

www.bostik.it 1/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:		
CAS: 72244-98-5 EC number: 615-735-8 Reg.nr.: 01-2120118957-46- XXXX	mercaptan polymer Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%
CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26- XXXX	bis-[4-(2,3-epoxipropoxi)phenyl]propane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 %	≥10-<25%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-2.5%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

EU

www.bostik.it 2/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

-..

(Contd. on page 4)

www.bostik.it 3/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs	· DNELs				
1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane					
Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)			
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)			
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)			
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m³ (rat)			
	Consumer, inhalative, longterm exposition	0.87 mg/m³ (rat)			
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol					
Oral	Consumer, oral, longterm exposition	0.075 mg/kg bw/day			
Dermal	Worker, dermal, shortterm exposition	0.6 mg/kg bw/day			
	Worker, dermal, longterm exposition	0.15 mg/kg bw/day			
	Consumer, dermal, shortterm exposition	0.075 mg/kg bw/day			
	Consumer, dermal, longterm exposition	0.075 mg/kg bw/day			
Inhalative	Worker, inhalative, shortterm exposition	2.1 mg/m³			
	Worker, inhalative, longterm exposition	0.53 mg/m³			
	Consumer DNEL, acute inhalation	0.13 mg/m³			
	Consumer, inhalative, longterm exposition	0.13 mg/m³			

· PNECs

1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane

Oral	Secondary Poisoning	11 mg/kg (rat)
	Fresh water	0.006 mg/l (rat)
	Fresh water sediment	0.341 mg/kg dry weight (rat)
	Marine water	0.001 mg/l (rat)
	Marine sediment	0.034 mg/kg dry weight (rat)
	Soil	0.065 mg/kg (rat)
	Sewage treatment plant	10 mg/l (rat)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

1	rz-z z,4,6-tris(dimetriyiaminometriyi)pnenoi		
	Fresh water	0.046 mg/l	
	Fresh water sediment	0.262 mg/kg dry weight	
	Marine water	0.005 mg/l	
	Marine sediment	0.026 mg/kg dry weight	
	Soil	0.025 mg/kg	
	Sewage treatment plant	0.2 mg/l	

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Ēυ

www.bostik.it 4/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 4)

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range Undetermined. Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >100 °C

Decomposition temperature: Not determined.

(Contd. on page 6)

ΕU

www.bostik.it 5/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 5) · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined. · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined. Density and/or relative density Density at 20 °C: 1.9 g/cm³ Relative density Not determined. · Vapour density Not determined. · 9.2 Other information All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. · Appearance: · Form: Solid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. **Explosive properties:** Product does not present an explosion hazard. · Solvent content: · Solids content: 70.8 % · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

(Contd. on page 7)

www.bostik.it 6/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 6)

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane

Oral LD50 >2000 mg/kg (rat)
Dermal LD50 >2000 mg/kg (rat)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral LD50 500 mg/kg (rat)

Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

EU

www.bostik.it 7/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 7)

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number	
· ADR/ADN, IMDG, IATA	not regulated
· ADN	not regulated
 14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA 	not regulated
· 14.3 Transport hazard class(es)	
· ADR/ADN, ADN, IMDG, IATA	
Class	not regulated
· 14.4 Packing group	
· ADR/ADN, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk according IMO instruments 	to Not applicable.

(Contd. on page 9)

EU

www.bostik.it 8/10



Safety data sheet

Version number 13 (replaces version 12)

according to Regulation (EC) No 1907/2006, Article 31

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 8)

Revision: 01.08.2024

· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU

Printing date 01.08.2024

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

(Contd. on page 10)

- EL

www.bostik.it 9/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: BTK EPOXY METAL BS 56G*12 IT

(Contd. of page 9)

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/irritation

Skin sensitisation

Hazardous to the aquatic environment - long-

term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 04.07.2023
Version number of previous version: 12

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- EU