

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** UHU POWER CONTACT FB 50ML\*10 L037**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Adhesive**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

UHU GmbH &amp; Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

**Further information obtainable from:** PSRA**1.4 Emergency telephone number:**

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2      H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

STOT SE 3      H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02



GHS07



GHS09

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 1)

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Ethyl acetate

??

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Rosin. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-XXXX	Ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 26022-00-4 EC number: 607-846-5	Phenolic resin ⚠ Skin Sens. 1, H317	2.5-10%

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 2)

CAS: 25085-50-1 EC number: 607-533-3	p-tert-butylphenol formaldehyde resin ⚠ Skin Sens. 1, H317	2.5-10%
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0 Reg.nr.: Exempt	Magnesium oxide substance with a Community workplace exposure limit	1-2.5%
CAS: 8052-10-6 EINECS: 232-484-6 Index number: 650-015-00-7	colophony ⚠ Skin Sens. 1, H317	≥0.1-<1%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41-XXXX	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-<1%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32-XXXX	Rosin ⚠ Skin Sens. 1, H317	≥0.1-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** No special measures required.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

(Contd. on page 4)

IE

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Send for recovery or disposal in suitable receptacles.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 141-78-6 Ethyl acetate

OEL (Ireland)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm
	Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
	IOELV

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 4)

IOELV (EU)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm	
<b>1309-48-4 Magnesium oxide</b>		
OEL (Ireland)	Short-term value: 10** mg/m <sup>3</sup> Long-term value: 4* 5** 10*** mg/m <sup>3</sup> *respirable dust **fume ***total inhalable dust	
<b>110-82-7 cyclohexane</b>		
OEL (Ireland)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm IOELV	
IOELV (EU)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm	

**· DNELs**

**141-78-6 Ethyl acetate**

Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	63 mg/kg bw/day
	Consumer, dermal, longterm exposition	37 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	1468 mg/m <sup>3</sup>
	Worker, inhalative, longterm exposition	734 mg/m <sup>3</sup>
	Consumer DNEL, acute inhalation	734 mg/m <sup>3</sup>
	Consumer, inhalative, longterm exposition	367 mg/m <sup>3</sup>

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics**

Oral	Consumer, oral, longterm exposition	149 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	300 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	149 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	2085 mg/m <sup>3</sup> (rat)
	Consumer, inhalative, longterm exposition	477 mg/m <sup>3</sup> (rat)

**110-82-7 cyclohexane**

Oral	Consumer, oral, longterm exposition	59.4 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	2016 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	1186 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, shortterm exposition	700 mg/m <sup>3</sup> (rat)
	Worker, inhalative, longterm exposition	700 mg/m <sup>3</sup> (rat)
	Consumer DNEL, acute inhalation	412 mg/m <sup>3</sup> (rat)
	Consumer, inhalative, longterm exposition	206 mg/m <sup>3</sup> (rat)

**· PNECs**

**141-78-6 Ethyl acetate**

Fresh water	0.24 mg/l
Fresh water sediment	1.15 mg/kg dry weight
Marine water	0.024 mg/l
Marine sediment	0.115 mg/kg dry weight
Soil	0.148 mg/kg
Sewage treatment plant	650 mg/l

(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 5)

### 110-82-7 cyclohexane

Fresh water	0.207 mg/l (rat)
Fresh water sediment	3.627 mg/kg dry weight (rat)
Marine water	0.207 mg/l (rat)
Marine sediment	3.627 mg/kg dry weight (rat)
Soil	2.99 mg/kg (rat)
Sewage treatment plant	3.24 mg/l (rat)
Sporadic release	0.207 mg/l

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 6)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	77-78 °C
· Flammability	Highly flammable.
· Lower and upper explosion limit	
· Lower:	2.1 Vol %
· Upper:	11.5 Vol %
· Flash point:	-4 °C
· Auto-ignition temperature:	460 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	3750 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	97 hPa
· Vapour pressure at 50 °C:	360 hPa
· Density and/or relative density	
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.

#### · 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

##### · Appearance:

· Form: Fluid

##### · Important information on protection of health and environment, and on safety.

##### · Ignition temperature:

Product is not selfigniting.

##### · Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Solvent content:

##### · Organic solvents:

73.9 %

##### · Water:

0.1 %

##### · VOC (EC)

73.86 %

##### · Solids content:

26.0 %

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 7)

· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Highly flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

#### 141-78-6 Ethyl acetate

Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.3 mg/l (rat)
<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</b>		
Oral	LD50	>5840 mg/kg (rat)

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 8)

Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)
<b>25085-50-1 p-tert-butylphenol formaldehyde resin</b>		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
<b>1309-48-4 Magnesium oxide</b>		
Oral	LD50	3870 mg/kg
Dermal	LD50	>2000 mg/kg (rabbit)
<b>110-82-7 cyclohexane</b>		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	32.88 mg/l (rat)
<b>8050-09-7 Rosin</b>		
Oral	LD50	2800 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**  
Not applicable.  
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

98-54-4 4-tert-butylphenol

List I; II

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037



(Contd. of page 9)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |  |   |
|--|---|
| · <b>14.1 UN number or ID number</b>     |   |
| · <b>ADR/ADN, IMDG, IATA</b>             | UN1133  |
| · <b>14.2 UN proper shipping name</b>    |   |
| · <b>ADR/ADN</b>                         | 1133 ADHESIVES  |
| · <b>IMDG</b>                            | ADHESIVES, MARINE POLLUTANT   |
| · <b>IATA</b>                            | ADHESIVES   |
| · <b>14.3 Transport hazard class(es)</b> |   |
| · <b>ADR/ADN</b>                         |   |
|  |   |
| · <b>Class</b>                           | 3 (F1) Flammable liquids.   |
| · <b>Label</b>                           | 3   |

(Contd. on page 11)

IE

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 10)

· **IMDG**



· **Class** 3 Flammable liquids.  
 · **Label** 3

· **IATA**



· **Class** 3 Flammable liquids.  
 · **Label** 3

· **14.4 Packing group**  
 · **ADR/ADN, IMDG, IATA** III

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances:  
 · **Marine pollutant:** Symbol (fish and tree)  
 · **Special marking (ADR/ADN):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Flammable liquids.  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-E,S-D  
 · **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**  
 · **Quantity limitations** On passenger aircraft/rail: 60 L  
 On cargo aircraft only: 220 L

· **ADR/ADN**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml  
 · **Transport category** 3  
 · **Tunnel restriction code** E

· **IMDG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

· **Remarks:** For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 11)

- with requirements (flow time  $t > 100s$ ).
- **UN "Model Regulation":** UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.

(Contd. on page 13)

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 22.03.2025

Version number 19 (replaces version 18)

Revision: 22.03.2025

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 12)

- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** PSRA
- **Contact:** PSRA
- **Date of previous version:** 28.10.2022
- **Version number of previous version:** 18
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

IE