

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Bison International  
Dr.A.F.Philipsstraat 9  
NL-4462 EW Goes  
PO Box 160  
NL-4460 AD Goes  
tel. +31 88 3235700  
fax. +31 88 3235800  
e mail: sds@boltonadhesives.com
- **Further information obtainable from:** PSRA
- **1.4 Emergency telephone number:**  
National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)  
Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1            H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

STOT RE 1            H372            Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

STOT SE 3            H336            May cause drowsiness or dizziness.

Aquatic Chronic 3 H412            Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Naphtha (petroleum), hydrodesulfurized heavy

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

EUH208 Contains Terpeneol. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Lubricant

· **Dangerous components:**

CAS: 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	50-100%
EC number: 919-857-5		
Reg.nr.: 01-2119463258-33-XXXX	 Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  STOT SE 3, H336, EUH066	

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 2)

CAS: 64742-82-1 EC number: 927-344-2 Index number: 649-330-00-2 Reg.nr.: 01-2119463586-28	Naphtha (petroleum), hydrodesulfurized heavy ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	≥10-<25%
CAS: 72623-86-0 EINECS: 276-737-9 Index number: 649-482-00-X Reg.nr.: 01-2119474878-16	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (Nota L, -R45, <3% dimethyl sulfoxide) ⚠ Asp. Tox. 1, H304	10-25%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide substance with a Community workplace exposure limit	1-2.5%
CAS: 8000-41-7 EINECS: 232-268-1	Terpineol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ Skin Sens. 1, H317	≥0.25-<1%

**Additional information:**

Propellant: CO2

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

**General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

No special measures required.

**After skin contact:** Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing agents:**

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

**5.3 Advice for firefighters**

**Protective equipment:** Mouth respiratory protective device.

(Contd. on page 4)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 3)

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**Storage class:** 2 B**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****124-38-9 carbon dioxide**OEL (Ireland) Long-term value: 9000 mg/m<sup>3</sup>, 5000 ppm  
IOELVIOELV (EU) Long-term value: 9000 mg/m<sup>3</sup>, 5000 ppm**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

- **Respiratory protection:** Not required.

- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- **Eye/face protection**

Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Aerosol

- **Colour:**

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

<35 °C

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

0.6 Vol %

- **Upper:**

7 Vol %

- **Flash point:**

61 °C

- **Auto-ignition temperature:**

240 °C

- **Decomposition temperature:**

Not determined.

(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· pH</li> <li>· <b>Viscosity:</b></li> <li>· <b>Kinematic viscosity</b></li> <li>· <b>Dynamic:</b></li> <li>· <b>Solubility</b></li> <li>· <b>water:</b></li> <li>· <b>Partition coefficient n-octanol/water (log value)</b></li> <li>· <b>Vapour pressure at 20 °C:</b></li> <li>· <b>Density and/or relative density</b></li> <li>· <b>Density at 20 °C:</b></li> <li>· <b>Relative density</b></li> <li>· <b>Vapour density</b></li> </ul>	<p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not miscible or difficult to mix.</p> <p>Not determined.</p> <p>1 hPa</p> <p>0.79 g/cm<sup>3</sup></p> <p>Not determined.</p> <p>Not determined.</p>
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b></li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b></li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b></li> <li>· <b>Explosive properties:</b></li> <li>· <b>Solvent content:</b></li> <li>· <b>Organic solvents:</b></li> <li>· <b>Solids content:</b></li> <li>· <b>Change in condition</b></li> <li>· <b>Evaporation rate</b></li> </ul>	<p>All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.</p> <p>Fluid</p> <p>Product is not selfigniting.</p> <p>Not determined.</p> <p>53.3 %</p> <p>0.0 %</p> <p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b></li> <li>· <b>Flammable gases</b></li> <li>· <b>Aerosols</b></li> <li>· <b>Oxidising gases</b></li> <li>· <b>Gases under pressure</b></li> <li>· <b>Flammable liquids</b></li> <li>· <b>Flammable solids</b></li> <li>· <b>Self-reactive substances and mixtures</b></li> <li>· <b>Pyrophoric liquids</b></li> <li>· <b>Pyrophoric solids</b></li> <li>· <b>Self-heating substances and mixtures</b></li> <li>· <b>Substances and mixtures, which emit flammable gases in contact with water</b></li> <li>· <b>Oxidising liquids</b></li> <li>· <b>Oxidising solids</b></li> <li>· <b>Organic peroxides</b></li> <li>· <b>Corrosive to metals</b></li> </ul>	<p>Void</p> <p>Void</p> <p>Extremely flammable aerosol. Pressurised container: May burst if heated.</p> <p>Void</p>

(Contd. on page 7)

IE

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 6)

· **Desensitised explosives** Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**  
Not applicable.  
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 7)

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- |                                       |                     |
|---------------------------------------|---------------------|
| · <b>14.1 UN number or ID number</b>  |                     |
| · <b>ADR/ADN, IMDG, IATA</b>          | UN1950              |
| · <b>14.2 UN proper shipping name</b> |                     |
| · <b>ADR/ADN</b>                      | 1950 AEROSOLS       |
| · <b>IMDG</b>                         | AEROSOLS            |
| · <b>IATA</b>                         | AEROSOLS, flammable |

(Contd. on page 9)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 8)

· **14.3 Transport hazard class(es)**

· **ADR/ADN**



· **Class** 2.5F Gases.  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases.  
 · **Label** 2.1

· **14.4 Packing group**

· **ADR/ADN, IMDG, IATA** not regulated

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Gases.  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-D,S-U  
 · **Stowage Code** SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
 · **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
 For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS:  
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **Quantity limitations** On passenger aircraft/rail: 75 kg  
 On cargo aircraft only: 150 kg

· **ADR/ADN**

· **Limited quantities (LQ)** 1L

(Contd. on page 10)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 9)

· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3b FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.

(Contd. on page 11)

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 29.07.2024

Version number 34 (replaces version 33)

Revision: 29.07.2024

**Trade name:** GRF WOOD LUBRICANT AE 500ML\*12 NLFR

(Contd. of page 10)

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

Aerosols, Section 2.3.1	Bridging principles
Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** PSRA
- **Contact:** PSRA
- **Date of previous version:** 21.01.2022
- **Version number of previous version:** 33
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Aerosol 1: Aerosols – Category 1  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

IE