

Printing date 31.07.2024 Version number 27 (replaces version 26) Re

Revision: 31.07.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9

NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

| Skin Irrit. 2H315Causes skin irritation.STOT SE 3H336May cause drowsiness or dizziness.Asp. Tox. 1H304May be fatal if swallowed and enters airways.Aquatic Chronic 3H412Harmful to aquatic life with long lasting effects. | Aerosol 1 | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
|--|--|-----------|--|
| STOT SE 3H336May cause drowsiness or dizziness.Asp. Tox. 1H304May be fatal if swallowed and enters airways. | GHS07 | | |
| Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. | Skin Irrit. 2 | H315 | Causes skin irritation. |
| | STOT SE 2 | H336 | May cause drowsiness or dizziness. |
| Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. | 3101 3E 3 | | |
| | | H304 | May be fatal if swallowed and enters airways. |
| | Asp. Tox. 1 Aquatic Chronic 3 2.2 Label elemer | 3 H412 | · · · · · · |

(Contd. on page 2)



Printing date 31.07.2024 Version number 27 (replaces version 26) Revision: 31.07.2024 Trade name: GRF LUBRIT-ALL AE 300ML*12 L221 (Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: Naphtha (petroleum), hydrotreated heavy Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (Nota L, -R45, <3% dimethyl sulfoxide) Hydrocarbons, C6, isoalkanes, <5% n-hexane Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics **Hazard statements** H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P273 Avoid release to the environment. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with national regulations. P501 · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Lubricant

| · Dangerous components: | | |
|--|--|-----------------|
| CAS: 64742-48-9 EC number: 927-241-2 Index number: 649-328-00-1 Reg.nr.: 01-2119471843-32 | Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412 | 25-50% |
| | (C | ontd. on page 3 |

FU



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

| CAS: 72623-86-0 | Lubricating oils (petroleum), C15-30, hydrotreated | Contd. of page 2 10-25% |
|---|---|----------------------------|
| EINECS: 276-737-9 Index number: 649-482-00-X Reg.nr.: 01-2119474878-16 | neutral oil-based (Nota L, -R45, <3% dimethyl sulfoxide) | 10-2376 |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21- XXXX | propane | 10-25% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32- XXXX | n-Butan | 10-25% |
| CAS: 64742-49-0 EC number: 931-254-9 Index number: 649-328-00-1 Reg.nr.: 01-2119484651-34- XXXX | Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; N Skin Irrit. 2, H315; STOT SE 3, H336 | ≥2.5-<10% |
| EC number: 927-510-4 Reg.nr.: 01-2119475515-33- XXXX | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | ≥2.5-<10% |
| CAS: 64742-49-0 EC number: 926-605-8 Index number: 649-328-00-1 Reg.nr.: 01-2119486291-36- XXXX | Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; O Skin Irrit. 2, H315; STOT SE 3, H336, EUH066 | ≥1-<2.5% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane | 1-2.5% |
| CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0 Reg.nr.: 01-2119480412-44 | n-hexane | ≥0.25-<1% |
| CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41- XXXX | cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336 | ≥0.25-<1% |

(Contd. on page 4)



Printing date 31.07.2024 Version number 27 (replaces version 26) Revision

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. • Information about fire - and explosion protection:
- Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.

(Contd. on page 5)

FU



Printing date 31.07.2024 Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

(Contd. of page 4) Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

9 1 Control .

| Ingredien | ts with limit values that require monitoring | ng at the workplace: | |
|------------|--|--------------------------|--|
| 110-54-3 ı | | | |
| IOELV Lo | ng-term value: 72 mg/m³, 20 ppm | | |
| 110-82-7 (| cyclohexane | | |
| IOELV Lo | ng-term value: 700 mg/m³, 200 ppm | | |
| DNELs | | | |
| 64742-49- | 0 Hydrocarbons, C6, isoalkanes, <5% n-l | nexane | |
| Oral | Consumer, oral, longterm exposition | 1301 mg/kg bw/day (rat) | |
| Dermal | Worker, dermal, longterm exposition | 13964 mg/kg bw/day (rat) | |
| | Consumer, dermal, longterm exposition | 1377 mg/kg bw/day (rat) | |
| Inhalative | Worker, inhalative, longterm exposition | 5306 mg/m³ (rat) | |
| | Consumer, inhalative, longterm exposition | 1131 mg/m³ (rat) | |
| Hydrocar | bons, C7, n-alkanes, isoalkanes, cyclics | | |
| Oral | Consumer, oral, longterm exposition | 149 mg/kg bw/day (rat) | |
| Dermal | Worker, dermal, longterm exposition | 300 mg/kg bw/day (rat) | |
| | Consumer, dermal, longterm exposition | 149 mg/kg bw/day (rat) | |
| Inhalative | Worker, inhalative, longterm exposition | 2085 mg/m³ (rat) | |
| | Consumer, inhalative, longterm exposition | 477 mg/m³ (rat) | |
| 64742-49- | 0 Naphtha (petroleum), hydrotreated ligh | ht | |
| Oral | Consumer, oral, longterm exposition | 1301 mg/kg bw/day (rat) | |
| Dermal | Worker, dermal, longterm exposition | 13964 mg/kg bw/day (rat) | |
| | Consumer, dermal, longterm exposition | 1377 mg/kg bw/day (rat) | |
| Inhalative | Worker, inhalative, longterm exposition | 5306 mg/m³ (rat) | |
| | Consumer, inhalative, longterm exposition | 1131 mg/m³ (rat) | |
| 110-82-7 (| cyclohexane | | |
| Oral | Consumer, oral, longterm exposition | 59.4 mg/kg bw/day (rat) | |
| Dermal | Worker, dermal, longterm exposition | 2016 mg/kg bw/day (rat) | |
| | Consumer, dermal, longterm exposition | 1186 mg/kg bw/day (rat) | |



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

| Inhalative | Worker, inhal | ative, shortterm exposition | (Contd. of page 5 700 mg/m³ (rat) | |
|--|---|---|---------------------------------------|--|
| | | ative, longterm exposition | 700 mg/m ³ (rat) | |
| | | NEL, acute inhalation | 412 mg/m ³ (rat) | |
| | | halative, longterm exposition | 3 | |
| ·PNECs | 1 | | | |
| 110-82-7 | cyclohexane | | | |
| Fresh wat | er | 0.207 mg/l (rat) | | |
| Fresh wat | er sediment | 3.627 mg/kg dry weight (rat) | | |
| Marine wa | ater | 0.207 mg/l (rat) | | |
| Marine se | diment | 3.627 mg/kg dry weight (rat) | | |
| Soil | | 2.99 mg/kg (rat) | | |
| Sewage ti | reatment plant | 3.24 mg/l (rat) | | |
| · Additiona | al information | The lists valid during the ma | aking were used as basis. | |
| Keep awa Immediate Wash har Do not inh Avoid con Avoid con | y from foodstu ely remove all s ds before brea hale gases / fur tact with the sk tact with the ey ory protection tection | ffs, beverages and feed. soiled and contaminated cloth aks and at the end of work. mes / aerosols. kin. yes and skin. : Not required. | l to when handling chemicals. ning | |
| Curls- | The glove material has to be impermeable and resistant to the product/ the substance/ the | | | |
| preparatic Selection degradatio Material o Recomme Nitrile rub Penetrati For the m (Permeati • Eye/face | The glove material has to be impermeable and resistant to the product/ the substance/ transport to preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and transport to the gloves Material of gloves Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR Penetration time of glove material For the mixture of chemicals mentioned below the penetration time has to be at least 10 minut (Permeation according to EN 374 Part 3: Level 1). Eye/face protection Not required. Body protection: Use protective suit. | | | |

(Contd. on page 7)



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

(Contd. of page 6)

| 9.1 Information on basic physical and ch | emical properties |
|--|--|
| • General Information | ennear properties |
| Physical state | Aerosol |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| Boiling point or initial boiling point and | |
| boiling range | -44.5 °C |
| Flammability | Not applicable. |
| Lower and upper explosion limit | |
| · Lower: | 0.6 Vol % |
| Upper: | 10.9 Vol % |
| Flash point: | -97 °C |
| Auto-ignition temperature: | 240 °C |
| Decomposition temperature: | Not determined. |
| рН | Not determined. |
| Viscosity: | |
| Kinematic viscosity | Not determined. |
| Dynamic: | Not determined. |
| Solubility | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient n-octanol/water (log | |
| value) | Not determined. |
| Vapour pressure at 20 °C: | 8300 hPa |
| Density and/or relative density | 0.000 |
| Density at 20 °C: | 0.693 g/cm ³ |
| Relative density | Not determined. |
| · Vapour density | Not determined. |
| 9.2 Other information | All relevant physical data were determined for the |
| | mixture. All non-determined data are n |
| | measurable or not relevant for th |
| | characterization of the mixture. |
| Appearance: | Assessed |
| Form: | Aerosol |
| Important information on protection of he | eaith |
| and environment, and on safety. | Droduct is not colfigniting |
| Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation explosive air/vapour mixtures are possible. |
| Solvent content: | explosive all/vapour mixtures are possible. |
| Organic solvents: | 47.8 % |
| Solids content: | 47.8 % 0.1 % |
| Change in condition | 0.1 /0 |
| Evaporation rate | Not applicable. |



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

| | | (Contd. of page 7 |
|---|---------------------------------|-------------------|
| · Information with regard to physical haz | ard | |
| classes | | |
| · Explosives | Void | |
| [.] Flammable gases | Void | |
| · Aerosols | Extremely flammable aerosol. | Pressurised |
| Ovidiaina assos | container: May burst if heated. | |
| Oxidising gases | Void | |
| · Gases under pressure | Void | |
| · Flammable liquids | Void | |
| Flammable solids | Void | |
| Self-reactive substances and mixtures | Void | |
| · Pyrophoric liquids | Void | |
| · Pyrophoric solids | Void | |
| • Self-heating substances and mixtures | Void | |
| · Substances and mixtures, which emit | | |
| flammable gases in contact with water | Void | |
| • Oxidising liquids | Void | |
| Oxidising solids | Void | |
| · Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

| | | n hazard classes as defined in Regulation (EC) No 1272/2008 ed on available data, the classification criteria are not met. |
|------------|------------|---|
| LD/LC50 | values re | levant for classification: |
| 64742-48 | 3-9 Naphth | na (petroleum), hydrotreated heavy |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >3000 mg/kg (rab) |
| 106-97-8 | n-Butan | |
| Inhalative | e LC50/4 h | n mg/l (rat) |
| 64742-49 | -0 Hydroc | arbons, C6, isoalkanes, <5% n-hexane |
| Oral | LD50 | >5000 mg/kg (rat) |



Printing date 31.07.2024 Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

| | | (Contd. of pag |
|--|--|--|
| Dermal | LD50 | >3000 mg/kg (rabbit) |
| | | >20 mg/l (rat) |
| Hydrocar | | n-alkanes, isoalkanes, cyclics |
| Oral | LD50 | >5840 mg/kg (rat) |
| Dermal | LD50 | >2920 mg/kg (rat) |
| | | >23.3 mg/l (rat) |
| 64742-49 | - | a (petroleum), hydrotreated light |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >3000 mg/kg (rabbit) |
| | | >20 mg/l (rat) |
| 110-82-7 | cyclohexa | ne |
| Oral | LD50 | |
| · Serious e · Respirate | osion/irrita kin irritatior eye damag ory or skin | n. e/irritation Based on available data, the classification criteria are not met. sensitisation Based on available data, the classification criteria are not me |
| Causes s Serious e Respirato Germ cel Not applio Based on Carcinog Reproduc STOT-sin STOT-rep Aspiratio Additiona Acute eff Sensitisa Repeated | osion/irrita kin irritatior eye damag ory or skin I mutagen cable. available of enicity Ba ctive toxic gle expos peated exp n hazard M al toxicolo ects (acuta tion Not ap I dose toxi | ation a. e/irritation Based on available data, the classification criteria are not met. sensitisation Based on available data, the classification criteria are not met icity data, the classification criteria are not met. sed on available data, the classification criteria are not met. ity Based on available data, the classification criteria are not met. ure May cause drowsiness or dizziness. osure Based on available data, the classification criteria are not met. May be fatal if swallowed and enters airways. gical information: e toxicity, irritation and corrosivity) Not applicable. oplicable. icity Not applicable. |
| Causes s Serious e Respirato Germ cel Not applic Based on Carcinog Reproduc STOT-sin STOT-rep Aspiratio Additiona Acute eff Sensitisa Repeated 11.2 Infor | osion/irrita kin irritation eye damag ory or skin I mutagen able. available o enicity Ba ctive toxic ogle expos beated exp n hazard M al toxicolo ects (acut tion Not ap I dose toxi mation on | ation a. e/irritation Based on available data, the classification criteria are not met. sensitisation Based on available data, the classification criteria are not met icity data, the classification criteria are not met. sed on available data, the classification criteria are not met. ity Based on available data, the classification criteria are not met. ure May cause drowsiness or dizziness. osure Based on available data, the classification criteria are not met. May be fatal if swallowed and enters airways. gical information: e toxicity, irritation and corrosivity) Not applicable. opplicable. |

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Harmful to fish

(Contd. on page 10)

⁻ EU



Printing date 31.07.2024 Version number 27 (replaces version 26) Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| 14.1 UN number or ID number ADR/ADN, IMDG, IATA | UN1950 |
|---|--|
| 14.2 UN proper shipping name ADR/ADN IMDG IATA | 1950 AEROSOLS AEROSOLS AEROSOLS, flammable |
| • 14.3 Transport hazard class(es) • ADR/ADN | |
| Class Label | 2 5F Gases. 2.1 |
| · IMDG, IATA | |
| · Class · Label | 2.1 Gases. 2.1 |
| · 14.4 Packing group · ADR/ADN, IMDG, IATA | not regulated |

(Contd. of page 9)



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

| | (Contd. of page 1 |
|--|---|
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user Hazard identification number (Kemler cod EMS Number: Stowage Code | Warning: Gases. ie): - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |
| · Segregation Code | SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| 14.7 Maritime transport in bulk according IMO instruments | to Not applicable. |
| Transport/Additional information: Quantity limitations | On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg |
| ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| Transport category Tunnel restriction code | 2 D |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 12)

- EU -



Printing date 31.07.2024 Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

(Contd. of page 11)

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 57

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

| Aerosols, Section 2.3.1 | Bridging principles |
|-------------------------|--|
| | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |
| Aspiration hazard | Expert judgement |

· Department issuing SDS: PSRA

· Contact: PSRA

• Date of previous version: 22.01.2022

Version number of previous version: 26

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

(Contd. on page 13)

FU



Printing date 31.07.2024

Version number 27 (replaces version 26)

Revision: 31.07.2024

Trade name: GRF LUBRIT-ALL AE 300ML*12 L221

(Contd. of page 12) GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 EU