

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF WDF-05 BO 500ML*12 L81
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

- EU

www.griffon.eu 1/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 1)

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Tetrahydrofuran

Butanone

· Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Tetrahydrofuran

Butanone

· Hazard statements

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with national regulations.

(Contd. on page 3)

ΕU

www.griffon.eu 2/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

Dood iption / tancon o		
Dangerous components:		
CAS: 109-99-9 EINECS: 203-726-8 Index number: 603-025-00-0 Reg.nr.: 01-2119444314-46- XXXX	Tetrahydrofuran	50-100%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone	25-50%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

(Contd. on page 4)

- EU

www.griffon.eu 3/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 3)

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

EU -

(Contd. on page 5)

www.griffon.eu 4/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 4)

Ingredients with limit values that require monitoring at the workplace: 109-99-9 Tetrahydrofuran IOELV Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Skin	8.1 Con	trol parameters			
IOELV Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Skin	Ingredie	ents with limit values	that require monitori	ng at the workplace:	
Long-term value: 150 mg/m³, 50 ppm Skin	109-99-9	Tetrahydrofuran			
IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm	l.	ong-term value: 150			
Long-term value: 600 mg/m³, 200 ppm	78-93-3	Butanone			
Oral Consumer, oral, longterm exposition Vorker, dermal, longterm exposition Consumer, dermal, longterm exposition Consumer, dermal, longterm exposition Hohalative Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, dermal, longterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Vorker, dermal, longterm exposition Vorker, dermal, longterm exposition Consumer, dermal, longterm exposition Consumer, dermal, longterm exposition Consumer, dermal, longterm exposition Vorker, inhalative, shortterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Vorker, inhalative, longterm exposition Vorker, inhalative, longterm exposition Consumer, inhalative, longterm exposition Vorker, inhalative, longterm exposition Vo					
Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Hinhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer, oral, longterm exposition Worker, dermal, longterm exposition Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Consumer, dermal, longterm exposition Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Rays and Consumer, inhalative, longterm exposition Rays and Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer Rays and Consume	DNELs				
Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Hinhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer, oral, longterm exposition Worker, dermal, longterm exposition Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Consumer, dermal, longterm exposition Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Rays and Consumer, inhalative, longterm exposition Rays and Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Rays and Consumer Rays and Consume	109-99-9	Tetrahydrofuran			
Consumer, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition T8-93-3 Butanone Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Inhalative Worker, dermal, longterm exposition Under Worker, inhalative, shortterm exposition Inhalative Worker, inhalative, shortterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer inhalative, longterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Vorker, dermal, longterm exposition Vorker, der			ngterm exposition	1.5 mg/kg bw/day	
Consumer, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition T8-93-3 Butanone Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Inhalative Worker, dermal, longterm exposition Under Worker, inhalative, shortterm exposition Inhalative Worker, inhalative, shortterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer inhalative, longterm exposition Vorker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Vorker, dermal, longterm exposition Vorker, der	Dermal		•	12.6 mg/kg bw/day	
Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation 52 mg/m³ 78-93-3 Butanone Oral Consumer, oral, longterm exposition Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Highlight Processing Substance Oral Consumer, oral, longterm exposition Worker, dermal, longterm exposition Highlight Processing Substance Substanc			•		
Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition 78-93-3 Butanone Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer DNEL, acute inhalation Consumer PNECs 750 mg/m³ 450 mg/m³	Inhalativ	e Worker, inhalative,	shortterm exposition	96 mg/m³	
Consumer, inhalative, longterm exposition 78-93-3 Butanone Oral Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Toral Secondary Poisoning Fresh water Fresh water Marine water Marine sediment Soil Sewage treatment plant Vorlat Inhalative, longterm exposition All Secondary Poisoning All Seconda		Worker, inhalative,	longterm exposition	72.4 mg/m³	
Oral Consumer, oral, longterm exposition Uvorker, dermal, longterm exposition Highlight (Consumer, oral, longterm exposition) Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Holative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Holative, longterm exposition Consumer, inhalative, longterm exposition Holative, longterm exposition H		Consumer DNEL, a	acute inhalation	52 mg/m³	
Oral Dermal Worker, dermal, longterm exposition Under the proof of the		Consumer, inhalati	ve, longterm exposition	13 mg/m³	
Dermal Worker, dermal, longterm exposition Consumer, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Torious Secondary Poisoning Fresh water Fresh water Fresh water sediment Marine water Marine sediment Soil Sewage treatment plant 1161 mg/kg bw/day 412 mg/kg bw/day 412 mg/kg bw/day 412 mg/kg bw/day 900 mg/m³ 600 mg/m³ 106 mg/m³ 450 mg/m³ 250 mg/m³ 250 mg/kg 450 mg/m³ 250 mg/kg 450 mg/m³ 250	78-93-3	Butanone			
Consumer, dermal, longterm exposition Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning Fresh water	Oral	Consumer, oral, lor	ngterm exposition	31 mg/kg bw/day	
Inhalative Worker, inhalative, shortterm exposition Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition 106 mg/m³ PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning Fresh water 4.32 mg/l Fresh water sediment Marine water Marine sediment Soil Sewage treatment plant 2.13 mg/kg Sewage treatment plant 4.6 mg/l	Dermal	Worker, dermal, lor	ngterm exposition	1161 mg/kg bw/day	
Worker, inhalative, longterm exposition Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition Consumer, inhalative, longterm exposition PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning 67 mg/kg Fresh water 4.32 mg/l Fresh water sediment 23.3 mg/kg dry weight Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l		Consumer, dermal,	longterm exposition	412 mg/kg bw/day	
Consumer DNEL, acute inhalation Consumer, inhalative, longterm exposition PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning Fresh water Fresh water 4.32 mg/l Fresh water sediment Marine water Marine sediment Soil Sewage treatment plant Consumer DNEL, acute inhalation 450 mg/m³ 106 mg/m³ 107 108 109-99-9 109-99-9 Tetrahydrofuran 4.32 mg/kg 4.32 mg/l 4.32 mg/l 4.32 mg/l 4.33 mg/kg dry weight 501 2.13 mg/kg 5ewage treatment plant 450 mg/m³ 108 109-99-9 109	Inhalativ	e Worker, inhalative,	shortterm exposition	900 mg/m³	
PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning Fresh water 4.32 mg/l Fresh water sediment Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l		Worker, inhalative,	longterm exposition	600 mg/m³	
PNECs 109-99-9 Tetrahydrofuran Oral Secondary Poisoning 67 mg/kg Fresh water 4.32 mg/l Fresh water sediment 23.3 mg/kg dry weight Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l		Consumer DNEL, a	acute inhalation	450 mg/m³	
Oral Secondary Poisoning 67 mg/kg Fresh water 4.32 mg/l Fresh water sediment 23.3 mg/kg dry weight Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l		Consumer, inhalati	ve, longterm exposition	106 mg/m³	
Oral Secondary Poisoning Fresh water 4.32 mg/l Fresh water sediment 23.3 mg/kg dry weight Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l	PNECs				
Fresh water Fresh water sediment Marine water Marine sediment Soil Sewage treatment plant 4.32 mg/l 23.3 mg/kg dry weight 2.33 mg/kg dry weight 2.33 mg/kg dry weight 2.13 mg/kg 4.6 mg/l	109-99-9	Tetrahydrofuran			
Fresh water sediment Marine water 0.432 mg/k Marine sediment Soil Sewage treatment plant 23.3 mg/kg dry weight 2.33 mg/kg dry weight 2.13 mg/kg 4.6 mg/l	Oral Se	condary Poisoning	67 mg/kg		
Marine water 0.432 mg/l Marine sediment 2.33 mg/kg dry weight Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l	Fre	esh water	4.32 mg/l		
Marine sediment Soil Sewage treatment plant 2.33 mg/kg dry weight 2.13 mg/kg 4.6 mg/l			-		
Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l	Marine water				
Soil 2.13 mg/kg Sewage treatment plant 4.6 mg/l	Marine sediment		_		
	Soil				
Sporadic release 21.6 mg/l	Sewage treatment plant 4.6		4.6 mg/l		
	Sp	Sporadic release 21.6 mg/l			
78-93-3 Butanone	78-93-3	Butanone			
Oral Secondary Poisoning 1000 mg/kg	Oral Se	condary Poisoning	1000 mg/kg		

www.griffon.eu 5/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 5)

	(Conta. or page 5)
Fresh water sediment	284.7 mg/kg dry weight	1
Marine water	55.8 mg/l	
Marine sediment	284.7 mg/kg dry weight	
Soil	22.5 mg/kg	
Sewage treatment plant	709 mg/l	
Sporadic release	55.8 mg/l	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter A
- · Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

(Contd. on page 7)

ÉU

www.griffon.eu 6/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

· Eye/face protection

(Contd. of page 6)



Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range $65.5 \,^{\circ}\text{C}$

• Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.5 Vol %
Upper: 12 Vol %
Flash point: -21 °C
Auto-ignition temperature: 230 °C

Decomposition temperature: Not determined.

pH Not determined. Viscosity:

• Kinematic viscosity
Not determined.

• Dynamic at 20 °C: 675 mPas
• Solubility

• water: Not miscible or difficult to mix. • Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C:
Vapour pressure at 50 °C:
550 hPa

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

Appearance:

· Form: Fluid

(Contd. on page 8)

EU

www.griffon.eu 7/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 7)

Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 82.9 %
 Water: 0.0 %
 VOC (EC) 82.92 %
 Solids content: 16.9 %

· Change in condition

• Evaporation rate Not determined.

 $\cdot \ \, \text{Information with regard to physical hazard} \\$

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

(Contd. on page 9)

www.griffon.eu 8/12

=11.



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 8)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 ·	· LD/LC50 values relevant for classification:			
109-99-9	109-99-9 Tetrahydrofuran			
Oral	LD50	500 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
Inhalative	LC50/4 h	>5000 mg/l (rat)		
78-93-3 B	78-93-3 Butanone			
Oral	LD50	>2193 mg/kg (rat)		
Dermal	LD50	>8050 mg/kg (rat)		

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Suspected of causing cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrin	e disrupting properties	
78-93-3	Butanone	List II
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 10)

FU.

www.griffon.eu 9/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

(Contd. of page 9)

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION	14:	Transpo	rt info	rmation
---------	-----	---------	---------	---------

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR/ADN



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

· 14.5 Environmental hazards:

Marine pollutant: No

(Contd. on page 11)

ΕU

www.griffon.eu 10/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

	(Contd. of page 10
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids.
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
Remarks:	For substances with class 3 according to IMDG
	Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance.
	with requirements (flow time t > 100s).
IIN "Model Population":	UN 1133 ADHESIVES, 3, III
UN "Model Regulation":	UN 1133 ADDESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 12)

EU

www.griffon.eu 11/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 500ML*12 L81

· REGULATION (EU) 2019/1148

(Contd. of page 11)

Regulation (EC) No 273/2004 on drug precursors

78-93-3 Butanone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 Butanone

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 12.02.2023
 Version number of previous version: 34

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- El

www.griffon.eu 12/12