

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains trimethoxyvinylsilane. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

- · 2.3 Other hazards During curing methanol (CAS 67-56-1) is produced.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Adhesive

(Contd. on page 2)

ΕU

www.griffon.eu 1/10



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

	(Con	td. of page 1)
· Dangerous components:		
CAS: 2768-02-7 EINECS: 220-449-8 Index number: 014-049-00-0 Reg.nr.: 01-2119513215-52- XXXX	trimethoxyvinylsilane  Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Sens. 1B, H317	2.5-10%
CAS: 13822-56-5 EINECS: 237-511-5 Reg.nr.: 01-2119510159-45- XXXX	3-(trimethoxysilyl)propylamine   → Eye Dam. 1, H318; → Skin Irrit. 2, H315	1-2.5%
CAS: 52829-07-9 EINECS: 258-207-9 Reg.nr.: 01-2119537297-32- XXXX	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate  Repr. 2, H361f; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411	<0.25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

FII

www.griffon.eu 2/10



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 2)

#### · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

	trimethoxyvinylsilane	
Oral	Consumer, oral, longterm exposition	0.3 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	3.9 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	7.8 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	27.6 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	6.7 mg/m³ (rat)
		18.9 mg/m³ (rabbit)
13822-56-	5 3-(trimethoxysilyl)propylamine	
Dermal	Worker, dermal, longterm exposition	1 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.5 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	7.1 mg/m³
	Consumer, inhalative, longterm exposition	1.7 mg/m³
52829-07-	9 bis(2,2,6,6-tetramethyl-4-piperidyl) seb	acate
Oral	Consumer, oral, longterm exposition	0.18 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	1.8 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.9 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	1.27 mg/m³
	Consumer, inhalative, longterm exposition	0.31 mg/m³

www.griffon.eu 3/10



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

	(Contd. of page
PNECs	
2768-02-7 trimethoxyvi	
Fresh water	0.4 mg/l
Fresh water sediment	1.5 mg/kg dry weight
Marine water	0.04 mg/l
Marine sediment	0.15 mg/kg dry weight
Soil	0.06 mg/kg
Sewage treatment plant	6.6 mg/l
Sporadic release	2.4 mg/l
13822-56-5 3-(trimetho	xysilyl)propylamine
Fresh water	0.5 mg/l
Fresh water sediment	1.8 mg/kg dry weight
Marine water	0.05 mg/l
Marine sediment	0.18 mg/kg dry weight
Soil	0.069 mg/kg
Sewage treatment plant	0.81 mg/l
52829-07-9 bis(2,2,6,6-6	tetramethyl-4-piperidyl) sebacate
Fresh water	0.018 mg/l
Fresh water sediment	29 mg/kg dry weight
Marine water	0.0018 mg/l
Marine sediment	2.9 mg/kg dry weight
Soil	5.9 mg/kg
Sewage treatment plant	1 mg/l
Sporadic release	0.007 mg/l

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)



# Safety data sheet

# according to Regulation (EC) No 1907/2006, Article 31

Version number 36 (replaces version 35) Revision: 21.03.2025 Printing date 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 4)

· Eye/face protection Goggles recommended during refilling

# **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

**Melting point/freezing point:** Undetermined.

· Boiling point or initial boiling point and

boiling range Undetermined. · Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. · Decomposition temperature: Not determined.

· pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

Solubility

Not miscible or difficult to mix. · water:

Partition coefficient n-octanol/water (log

value)

Not determined. Vapour pressure: Not determined.

Density and/or relative density

Not determined. · Density: · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Organic solvents: 0.0 % · Solids content: 74.5 %

· Change in condition

**Evaporation rate** Not determined.

(Contd. on page 6)



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 5)

<ul> <li>Information with regard to physical haz classes</li> </ul>	ard	
· Explosives	Void	
Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
· Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
<ul> <li>Self-heating substances and mixtures</li> </ul>	Void	
<ul> <li>Substances and mixtures, which emit</li> </ul>		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Danger of forming toxic pyrolysis products.

Possible in traces.

· Additional information: During curing methanol (CAS 67-56-1) is produced.

# **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification:		
ſ	2768-02-7 trimethoxyvinylsilane		
ſ	Oral	LD50	6899 mg/kg (rat)
١	Dermal	LD50	3158 mg/kg (rabbit)
١	Inhalative	LC50/4 h	16.8 mg/l (rat)

(Contd. on page 7)



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 6)

13822-56-5 3-(trimethoxysilyl)propylamine		
Oral	LD50	3030 mg/kg (rat)
Dermal	LD50	10000 mg/kg (rabbit)
52829-07-9 bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate		
Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	>3170 mg/kg (rat)
Inhalative	LC50/4 h	7.7 mg/l (rat)

## · Primary irritant effect:

· Skin corrosion/irritation

Component CAS No. Method Species Conclusion
Vinyltrimethoxysilane 2768-02-7 OECD No. 429 mouse, dermal no sensitisation

Serious eye damage/irritation

Component CAS No. Method Species Conclusion

3-Aminopropyl 13822-56-5 BCOP OECD 437 cattle, eye no ocular irritation

trimethoxysilane

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 8)

ÉU

www.griffon.eu 7/10



# Safety data sheet

# according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 7)

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	not regulated
ADR/ADN, IMDG, IATA	-
ADN	not regulated
14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR/ADN, ADN, IMDG, IATA Class	not regulated
14.4 Packing group ADR/ADN, IMDG, IATA	not regulated
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	not regulated

EU

(Contd. on page 9)

www.griffon.eu 8/10



# Safety data sheet

# according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 36 (replaces version 35) Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 8)

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- Department issuing SDS: PSRA
- · Contact: PSRA
- Date of previous version: 25.07.2024Version number of previous version: 35
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

- EU

www.griffon.eu 9/10



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 36 (replaces version 35) Printing date 21.03.2025 Revision: 21.03.2025

Trade name: GRF PM FIX&SEAL EXP BK CQ 425G\*12 L221

(Contd. of page 9)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 2: Reproductive toxicity – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2