

Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: BK SUPERCH FBX 50G*24 IT

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

| | on of the substance or mixture ccording to Regulation (EC) No 1272/2008 2 flame |
|--|---|
| Flam. Liq. 2 | H225 Highly flammable liquid and vapour. |
| GHS07 | , |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Irrit. 2 | H319 Causes serious eye irritation. |
| STOT SE 3 | H336 May cause drowsiness or dizziness. |
| Aquatic Chronic | 3 H412 Harmful to aquatic life with long lasting effects. |
| 2.2 Label eleme Labelling accor | nts ding to Regulation (EC) No 1272/2008 |

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:
- Methylcyclohexane
- Butanone
- Ethyl acetate
- Acetone
- Hazard statements
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fireextinguishing powder, Carbon dioxide.
- P501 Dispose of contents/container in accordance with national regulations.
- · Additional information:
- EUH208 Contains Rosin. May produce an allergic reaction.
- · Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: Methylcyclohexane
- Butanone Ethyl acetate
- Einyi acel
- Acetone
- Hazard statements
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

(Contd. on page 3)

(Contd. of page 1)

EU •



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

P261 Avoid breathing vapours.

(Contd. of page 2)

List II

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 Butanone

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Г

· Description: Adhesive

| | | - | | |
|---|-------|-------|-------|--------|
| • | Dange | erous | compo | nents: |

| Dangerous components: | | |
|---|--|-----------------|
| CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18- XXXX | Methylcyclohexane Flam. Liq. 2, H225; S Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | ≥10-<25% |
| CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX | Butanone | 10-25% |
| CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX | Ethyl acetate Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 10-25% |
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX | Acetone Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | ≥2.5-<10% |
| CAS: 25085-50-1 EC number: 607-533-3 | p-tert-butylphenol formaldehyde resin Skin Sens. 1, H317 | 2.5-10% |
| CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32- XXXX | Rosin Skin Sens. 1, H317 | ≥0.1-<1% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32- XXXX | Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | ≥0.025-<0.25% |
| | | (Contd. on page |



Printing date 21.03.2025 Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

(Contd. of page 3)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents:** Water haze Alcohol resistant foam Fire-extinguishing powder
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

⁻ EU -



Printing date 21.03.2025 Version number 38 (replaces version 37) Revisio

Revision: 11.03.2025

(Contd. of page 4)

Trade name: BK SUPERCH FBX 50G*24 IT

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 • Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

| 78-93-3 B | | |
|------------|---|------------------------|
| IOELV Sł | nort-term value: 900 mg/m³, 300 ppm | |
| Lo | ong-term value: 600 mg/m³, 200 ppm | |
| 141-78-6 | Ethyl acetate | |
| IOELV Sł | nort-term value: 1468 mg/m³, 400 ppm | |
| Lo | ong-term value: 734 mg/m³, 200 ppm | |
| 67-64-1 A | cetone | |
| IOELV La | ong-term value: 1210 mg/m³, 500 ppm | |
| DNELs | | |
| 108-87-2 | Methylcyclohexane | |
| Oral | Consumer, oral, longterm exposition | 0.4 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 1.7 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 0.8 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 1354.6 mg/m³ |
| | Worker, inhalative, longterm exposition | 64.3 mg/m ³ |
| | Consumer DNEL, acute inhalation | 1016 mg/m ³ |
| | Consumer, inhalative, longterm exposition | - |
| 78-93-3 B | utanone | I |
| Oral | Consumer, oral, longterm exposition | 31 mg/kg bw/day |

ΕU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

| Dermal | Worker, dermal, lo | naterm exposition | 1161 mg/kg bw/day | (Contd. of pag |
|--|--------------------------------|---------------------------|------------------------|----------------|
| Donna | | , longterm exposition | 412 mg/kg bw/day | |
| Inhalative | | shortterm exposition | 900 mg/m ³ | |
| milalative | | longterm exposition | 600 mg/m ³ | |
| | Consumer DNEL, a | • | 450 mg/m ³ | |
| | | ve, longterm exposition | - | |
| 141-78-6 | Ethyl acetate | ve, iongterni exposition | 100 mg/m | |
| Oral | Consumer, oral, lo | naterm exposition | 4.5 mg/kg bw/day | |
| Dermal | Worker, dermal, lo | • | 63 mg/kg bw/day | |
| Dermai | | , longterm exposition | 37 mg/kg bw/day | |
| Inhalative | | shortterm exposition | 1468 mg/m ³ | |
| minalative | | longterm exposition | 734 mg/m ³ | |
| | Consumer DNEL, a | • | 734 mg/m ³ | |
| | | ve, longterm exposition | | |
| 67-64-1 A | | | cor ng/n | |
| Oral | Consumer, oral, lo | naterm exposition | 62 mg/kg bw/day | |
| Dermal | Worker, dermal, lo | • | 186 mg/kg bw/day | |
| Dermar | | , longterm exposition | 62 mg/kg bw/day | |
| Inhalative | | shortterm exposition | 2420 mg/m ³ | |
| minalative | | longterm exposition | 1210 mg/m ³ | |
| | | ve, longterm exposition | 200 mg/m ³ | |
| PNECs | | ro, iongtoini oxpoolitori | 200 | |
| | Methylcyclohexane | <u> </u> | | |
| | h water | • 0.00134 mg/l | | |
| | h water sediment | 0.0362 mg/kg dry weig | ht | |
| | ne water | 0.000134 mg/l | | |
| | ne sediment | 0.00362 mg/kg dry wei | abt | |
| Soil | | 0.0097 mg/kg | | |
| | age treatment plant | | | |
| 78-93-3 B | • | 0.275 mg/i | | |
| | ondary Poisoning | 1000 mg/kg | | |
| | h water | 55.8 mg/l | | |
| | h water sediment | 284.7 mg/kg dry weigh | t | |
| | ne water | 55.8 mg/l | | |
| | ne sediment | 284.7 mg/kg dry weigh | t | |
| Soil | | 22.5 mg/kg | | |
| | | | | |
| | ane treatment nlant | | | |
| Sew | age treatment plant | - | | |
| Sew Spor | radic release | 55.8 mg/l | | |
| Sew Spor 141-78-6 | radic release Ethyl acetate | 55.8 mg/l | | |
| Sew Spor 141-78-6 Fres | radic release | - | | |



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

| | (Contd. of page 6) |
|--|--|
| Marine water | 0.024 mg/l |
| Marine sediment | 0.115 mg/kg dry weight |
| Soil | 0.148 mg/kg |
| Sewage treatment plant | 650 mg/l |
| 67-64-1 Acetone | |
| Fresh water | 10.6 mg/l |
| Fresh water sediment | 30.4 mg/kg dry weight |
| Marine water | 1.06 mg/l |
| Marine sediment | 3.04 mg/kg dry weight |
| Soil | 29.5 mg/kg |
| Sewage treatment plant | 100 mg/l |
| Sporadic release | 21 mg/l |
| 1314-13-2 Zinc oxide | |
| Fresh water | 0.0144 mg/l |
| Fresh water sediment | 146.9 mg/kg dry weight |
| Marine water | 0.0072 mg/l |
| Marine sediment | 162.2 mg/kg dry weight |
| Soil | 83.1 mg/kg |
| Sewage treatment plant | 0.1 ma/l |
| • General protective and hygi The usual precautionary meas Keep away from foodstuffs, be Immediately remove all soiled Wash hands before breaks an Do not inhale gases / fumes / Avoid contact with the eyes ar • Respiratory protection: | sures are to be adhered to when handling chemicals. everages and feed. and contaminated clothing id at the end of work. aerosols. nd skin. ctive device in case of insufficient ventilation. |
| preparation. Selection of the glove materia | be impermeable and resistant to the product/ the substance/ the al on consideration of the penetration times, rates of diffusion and the |
| degradation | (Contd. on page 8) |



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 7)

Trade name: BK SUPERCH FBX 50G*24 IT

Material of gloves

Recommended thickness of the material: > 0,12 mm Butyl rubber, BR Nitrile rubber, NBR Recommended thickness of the material: > 0,7 mm **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).
- · Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling **Body protection:** Use protective suit. Solvent resistant protective clothing

| SECTION 9: Physical and chemical | properties | |
|---|-----------------------------------|-------------------|
| · 9.1 Information on basic physical and che | mical properties | |
| General Information | | |
| · Physical state | Fluid | |
| · Colour: | Yellow | |
| · Odour: | Characteristic | |
| · Odour threshold: | Not determined. | |
| Melting point/freezing point: | Undetermined. | |
| · Boiling point or initial boiling point and | | |
| boiling range | 55.8-56.6 °C | |
| · Flammability | Highly flammable. | |
| • Lower and upper explosion limit | | |
| · Lower: | 1.8 Vol % | |
| · Upper: | 11.5 Vol % | |
| Flash point: | -4 °C | |
| · Auto-ignition temperature: | 260 °C | |
| Decomposition temperature: | Not determined. | |
| · pH | Not determined. | |
| · Viscosity: | | |
| · Kinematic viscosity | Not determined. | |
| · Dynamic at 20 °C: | 2500 mPas | |
| [·] Solubility | | |
| water: | Not miscible or difficult to mix. | |
| · Partition coefficient n-octanol/water (log | | |
| value) | Not determined. | |
| Vapour pressure at 20 °C: | 105 hPa | |
| · Vapour pressure at 50 °C: | 360 hPa | |
| | | (Contd. on page s |

EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

| | (Contd. of page |
|--|---|
| Density and/or relative density | |
| Density at 20 °C: | 0.933-~0.933 g/cm ³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | All relevant physical data were determined for th mixture. All non-determined data are no measurable or not relevant for th characterization of the mixture. |
| Appearance: | |
| Form: | Fluid |
| Important information on protection of hea and environment, and on safety. | llth |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Solvent content: | |
| Organic solvents: | 77.5 % |
| Water: | 0.2 % |
| VOC (EC) | 77.45 % |
| Solids content: | 22.4 % |
| Change in condition | |
| Evaporation rate | Not determined. |
| Information with regard to physical haza | ard |
| classes | |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Highly flammable liquid and vapour. |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| | N / 1 / |
| Self-heating substances and mixtures | Void |
| | Void |
| Self-heating substances and mixtures | Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids | |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water | Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides | Void Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids | Void Void Void |

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

(Contd. on page 10) EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 9)

Trade name: BK SUPERCH FBX 50G*24 IT

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

| Oral Dermal | Methylcyc | |
|---|-------------|-------------------------------|
| Dermal | LD50 | |
| | | 4000-4500 mg/kg (rabbit) |
| | LD50 | >2000 mg/kg (rabbit) |
| 78-93-3 E | Butanone | |
| Oral | LD50 | >2193 mg/kg (rat) |
| Dermal | LD50 | >8050 mg/kg (rat) |
| 141-78-6 | Ethyl acet | ate |
| Oral | LD50 | 4934 mg/kg (rabbit) |
| Dermal | LD50 | >20000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 29.3 mg/l (rat) |
| 67-64-1 A | cetone | |
| Oral | LD50 | 5800 mg/kg (rat) |
| Dermal | LD50 | >15800 mg/kg (rat) |
| Inhalative | LC50/4 h | 76 mg/l (rat) |
| 25085-50 | -1 p-tert-b | utylphenol formaldehyde resin |
| Oral | LD50 | >2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| 8050-09- | 7 Rosin | |
| Oral | LD50 | 2800 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| 1314-13- | 2 Zinc oxic | le |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| Skin cor Causes s Serious Causes s | erious eye | ation n. e/irritation |

(Contd. on page 11)



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

(Contd. of page 10)

List II

List I: II

Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· Acute effects (acute toxicity, irritation and corrosivity) Not applicable.

- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Butanone

98-54-4 4-tert-butylphenol

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 12)

FU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

(Contd. of page 11)

· Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| 14.1 UN number or ID number ADR/ADN, IMDG, IATA | UN1133 |
|--|--|
| 14.2 UN proper shipping name ADR/ADN IMDG, IATA | 1133 ADHESIVES ADHESIVES |
| 14.3 Transport hazard class(es) | |
| ADR/ADN | |
| | |
| Class Label | 3 (F1) Flammable liquids. 3 |
| IMDG, IATA | |
| | |
| Class Label | 3 Flammable liquids. 3 |
| 14.4 Packing group ADR/ADN, IMDG, IATA | III |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): EMS Number: | - F-E,S-D |
| Stowage Category | A |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| Transport/Additional information: Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| ADR/ADN | |
| Limited quantities (LQ) | 5L Cada: E1 |
| Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 1000 |
| | (Contd. on page 1 |



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK SUPERCH FBX 50G*24 IT

| | (Contd. of page 12 |
|---------------------------|---|
| | ml |
| · Transport category | 3 |
| Tunnel restriction code | E |
| ·IMDG | |
| · Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 100 |
| | ml |
| · Remarks: | For substances with class 3 according to IMDG |
| | Code chapter 2.3.2.2 packing group is classifie |
| | in packing group III, as viscosity is in accordance |
| | with requirements (flow time $t > 100s$). |
| UN "Model Regulation": | UN 1133 ADHESIVES, 3, III |
| | ,, |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors
- 78-93-3 Butanone
- 67-64-1 Acetone
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
- 78-93-3 Butanone

67-64-1 Acetone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 14)

3

3

3

3

EU



Printing date 21.03.2025

H304

H315

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 13)

Trade name: BK SUPERCH FBX 50G*24 IT

Causes skin irritation.

May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. Causes serious eye irritation. H319 H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Flammable liquids Bridging principles The classification of the mixture is generally Skin corrosion/irritation Serious eye damage/irritation based on the calculation method using Specific target organ toxicity (single exposure) substance data according to Regulation (EC) No Hazardous to the aquatic environment - long-1272/2008. term (chronic) aquatic hazard · Department issuing SDS: PSRA Contact: PSRA Date of previous version: 24.07.2024 · Version number of previous version: 37 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 FII