

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK SUPERCHIARO FB 50G*12 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU

www.bostik.it 1/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 1)

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Methylcyclohexane

Butanone

Ethyl acetate

Acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-

extinguishing powder, Carbon dioxide.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH208 Contains Rosin. May produce an allergic reaction.

Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Methylcyclohexane

Butanone

Ethyl acetate

Acetone

· Hazard statements

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 3)

□)

www.bostik.it 2/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 2)

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

Dangerous components:		
CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18- XXXX	Methylcyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
CAS: 25085-50-1 EC number: 607-533-3	p-tert-butylphenol formaldehyde resin Skin Sens. 1, H317	2.5-10%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32- XXXX	Rosin Skin Sens. 1, H317	≥0.1-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32- XXXX	Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25

Contd. on page 4

- EU

www.bostik.it 3/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 3)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

 \cdot 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

- EII

www.bostik.it 4/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 4)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

78-93-3 Butanone

Oral

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Consumer, oral, longterm exposition

Ingredien	ts with limit values that require monitori	ng at the workplace:
78-93-3 B	utanone	
	nort-term value: 900 mg/m³, 300 ppm ng-term value: 600 mg/m³, 200 ppm	
141-78-6	Ethyl acetate	
	nort-term value: 1468 mg/m³, 400 ppm ong-term value: 734 mg/m³, 200 ppm	
67-64-1 A	cetone	
IOELV Lo	ng-term value: 1210 mg/m³, 500 ppm	
DNELs		
108-87-2	Methylcyclohexane	
Oral	Consumer, oral, longterm exposition	0.4 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	1.7 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.8 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	1354.6 mg/m³
	Worker, inhalative, longterm exposition	64.3 mg/m³
	Consumer DNEL, acute inhalation	1016 mg/m³
	Consumer, inhalative, longterm exposition	16 mg/m³

(Contd. on page 6)

EU

www.bostik.it 5/14

31 mg/kg bw/day



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

Dem	s a l	Morkor dames al la	actorm ovnesities	1161 malka budan	(Contd. of pa
Dermal Inhalative		Worker, dermal, lor	•	1161 mg/kg bw/day	
		Consumer, dermal, longterm exposition		412 mg/kg bw/day	
			shortterm exposition	900 mg/m³	
			longterm exposition	600 mg/m³	
		Consumer DNEL, a		450 mg/m³	
444			ve, longterm exposition	106 mg/m³	
	78-6 I	Ethyl acetate		4.5 // /-	
Oral		Consumer, oral, lor	•	4.5 mg/kg bw/day	
Derm	ıaı	Worker, dermal, lor	•	63 mg/kg bw/day	
In the set			longterm exposition	37 mg/kg bw/day	
Inhala	ative		shortterm exposition	1468 mg/m³	
			longterm exposition	734 mg/m³	
		Consumer DNEL, a		734 mg/m³	
			ve, longterm exposition	367 mg/m³	
	4-1 A	cetone		00 // / /	
Oral		Consumer, oral, lor	•	62 mg/kg bw/day	
Derm	nal	Worker, dermal, lor	•	186 mg/kg bw/day	
			longterm exposition	62 mg/kg bw/day	
Inhala	atıve		shortterm exposition	2420 mg/m³	
			longterm exposition	1210 mg/m³	
	Consumer, inhalati		ve, longterm exposition	200 mg/m³	
· PNE					
108-8		Methylcyclohexane			
		h water	0.00134 mg/l		
		h water sediment	0.0362 mg/kg dry weig	ht	
		ne water	0.000134 mg/l 0.00362 mg/kg dry weight		
		ne sediment			
	Soil		0.0097 mg/kg		
	Sewage treatment plant		0.273 mg/l		
78-93	3-3 B	utanone			
Oral		ndary Poisoning	1000 mg/kg		
Fres		h water	55.8 mg/l		
		h water sediment	284.7 mg/kg dry weigh	t	
		ne water	9		
		ine sediment 284.7 mg/kg dry weigh		t	
Soil Sewage treatment plant			22.5 mg/kg		
		•	_		
		adic release	55.8 mg/l		
1/1		Ethyl acetate			
141-7		resh water 0.24 mg/l			
141-7	Fres	Water	1.15 mg/kg dry weight		

www.bostik.it 6/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

	(Contd. of page 6)
Marine water	0.024 mg/l
Marine sediment	0.115 mg/kg dry weight
Soil	0.148 mg/kg
Sewage treatment plan	t 650 mg/l
67-64-1 Acetone	•
Fresh water	10.6 mg/l
Fresh water sediment	30.4 mg/kg dry weight
Marine water	1.06 mg/l
Marine sediment	3.04 mg/kg dry weight
Soil	29.5 mg/kg
Sewage treatment plan	t 100 mg/l
Sporadic release	21 mg/l
1314-13-2 Zinc oxide	•
Fresh water	0.0144 mg/l
Fresh water sediment	146.9 mg/kg dry weight
Marine water	0.0072 mg/l
Marine sediment	162.2 mg/kg dry weight
Soil	83.1 mg/kg
Sewage treatment plan	t 0.1 mg/l

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)

EU.

www.bostik.it 7/14



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 7)

Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection:

Use protective suit.

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical stateColour:FluidYellow

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C
Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.8 Vol %
Upper: 11.5 Vol %
Flash point: -4 °C
Auto-ignition temperature: 260 °C

Decomposition temperature: Not determined.pH Not determined.

Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 2500 mPas

· Solubility · water:

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C:Vapour pressure at 50 °C:360 hPa

(Contd. on page 9)

– EU

www.bostik.it 8/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

	(Contd. of page 8	
Density and/or relative density Density at 20 °C: Relative density	0.933-~0.933 g/cm³ Not determined.	
Vapour density	Not determined.	
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.	
Appearance:		
Form:	Fluid	
Important information on protection of hea	alth	
and environment, and on safety.		
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of	
	explosive air/vapour mixtures are possible.	
Solvent content:		
Organic solvents:	77.5 %	
Water:	0.2 %	
VOC (EC)	77.45 %	
Solids content:	22.4 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes	w. w	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit	VOIG	
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
One of the second second	Volu	

SECTION 10: Stability and reactivity

· Organic peroxides

Corrosive to metals

Desensitised explosives

· 10.1 Reactivity No further relevant information available.

(Contd. on page 10)

www.bostik.it 9/14

Void

Void Void



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 9)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:				
108-87-2 I	108-87-2 Methylcyclohexane			
Oral	LD50	4000-4500 mg/kg (rabbit)		
Dermal	LD50	>2000 mg/kg (rabbit)		
78-93-3 B	utanone			
Oral	LD50	>2193 mg/kg (rat)		
Dermal	LD50	>8050 mg/kg (rat)		
141-78-6 I	Ethyl acet	ate		
Oral	LD50	4934 mg/kg (rabbit)		
Dermal	LD50	>20000 mg/kg (rabbit)		
Inhalative	LC50/4 h	29.3 mg/l (rat)		
67-64-1 A	67-64-1 Acetone			
Oral	LD50	5800 mg/kg (rat)		
Dermal	LD50	>15800 mg/kg (rat)		
Inhalative	LC50/4 h	76 mg/l (rat)		
25085-50-	1 p-tert-bu	utylphenol formaldehyde resin		
Oral	LD50	>2000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
8050-09-7	8050-09-7 Rosin			
Oral	LD50	2800 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
1314-13-2	1314-13-2 Zinc oxide			
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
. Drimon, i	Primary irritant offect:			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

(Contd. on page 11)

ΕU

www.bostik.it 10/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 10)

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrine disrupting properties		
78-93-3	Butanone	List II
98-54-4	4-tert-butylphenol	List I; II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 12)

ΕU

www.bostik.it 11/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

(Contd. of page 11)

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

44.4 UN	
14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids.
IMDG, IATA	
	6. E
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	- F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 n Maximum net quantity per outer packaging: 100



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

	(Contd. of page 1
	ml
· Transport category	3
Tunnel restriction code	E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100
	ml
Remarks:	For substances with class 3 according to IMDO Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· F	Regulat	ion (EC) No 273/2004 on drug precursors	
7	78-93-3	Butanone	3
6	67-64-1	Acetone	3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3	Butanone	3
67-64-1	Acetone	3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 14)

ΕU

www.bostik.it 13/14



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BTK SUPERCHIARO FB 50G*12 IT

		(Contd. of page 13)
H304	May be fatal if swallowed and enters airways.	, ,
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
· Classifi	cation according to Regulation (EC) No 1272/2008	

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 24.07.2024
Version number of previous version: 37

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Εl