

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

EU-EN

www.bostik.it 1/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 1)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements Void
- · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

Adhesive

· Dangerous components:		
EINECS: 231-072-3 Index number: 013-002-00-1	aluminium powder (stabilized) Tlam. Sol. 2, H228; Water-react. 2, H261	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Stantone Flam. Liq. 2, H225; Stantone Eye Irrit. 2, H319; STOT SE 3,	10-25%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4	4-methylpentan-2-one Flam. Liq. 2, H225;	10-25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

EU-EN

www.bostik.it 2/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

EU-EN -

(Contd. on page 4)

www.bostik.it 3/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with I	limit values that	t reauire ma	onitoring at th	ne workplace:

78-93-3 butanone

IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

108-10-1 4-methylpentan-2-one

IOELV Short-term value: 208 mg/m³, 50 ppm Long-term value: 83 mg/m³, 20 ppm

· DNELs

78-93-3 butanone

Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day
Inhalative	Consumer inhalation longterm exposition	106 mg/m³

· PNECs

78-93-3 butanone

Fresh water 55.8 mg/l Marine water 55.8 mg/l Soil 22.5 mg/kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

- EU-EN

www.bostik.it 4/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Recommended filter device for short term use:

Filter AX

Filter A

· Protection of hands:

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· Eye protection:



Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Fluid

Colour: According to product specification Characteristic

· Odour threshold:

· pH-value:

Not determined.

Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 78 °C

(Contd. on page 6)

EU-EN

www.bostik.it 5/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

	(Contd. of page
Flash point:	2 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	330 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	1.7 Vol % 11.5 Vol %
· Vapour pressure at 20 °C:	105 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	1.48 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents:	30.8 %
Solids content: · 9.2 Other information	68.5 % All relevant physical data were determined for th mixture. All non-determined data are not measurable on the relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

EU-EN

(Contd. on page 7)

www.bostik.it 6/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
78-93-3 b	78-93-3 butanone		
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	
108-10-1	108-10-1 4-methylpentan-2-one		
Oral	LD50	2080 mg/kg (rat)	
Dermal	LD50	16000 mg/kg (rab)	
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

www.bostik.it 7/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 7)

(Contd. on page 9)

EU-EN

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number	
ADR/ADN, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR/ADN	1263 PAINT RELATED MATERIAL, spe
ADIVADIN	provision 640D
IMDG, IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR/ADN	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR/ADN, IMDG, IATA	II
· · ·	п
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-E

www.bostik.it 8/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

· 14.7 Transport in bulk according to Anne of Marpol and the IBC Code	(Contd. of page ex II Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml 2 D/F
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2
· Remarks:	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml Under certain conditions substances in Class (flammable liquids) can be classified i packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIA PROVISION 640D, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

EU-EN -

(Contd. on page 10)

www.bostik.it 9/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.01.2021 Version number 14 Revision: 06.01.2021

Trade name: BOSTIK METALLO LIQUIDO FPB 55ML*12 IT

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H228 Flammable solid.

H261 In contact with water releases flammable gases.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
Serious eye damage/eye irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Department issuing SDS: Bison QESH

· Contact:

Marketing UHU BOSTIK

Reach coordinator

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Sol. 2: Flammable solids - Category 2

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* * Data compared to the previous version altered.

FU-FN

www.bostik.it 10/10