

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

H315 Causes skin irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

-EU

www.bostik.it 1/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 1)

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Isocyanic acid, polymethylenepolyphenylene ester, polymer with methyloxirane polymer with oxirane ether with 1,2,3-propanetriol

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and oxirane, block

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

(Contd. on page 3)

EU

www.bostik.it 2/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

	(C	contd. of page 2
Dangerous components:		
CAS: 58228-05-0 Polymer	Isocyanic acid, polymethylenepolyphenylene ester, polymer with methyloxirane polymer with oxirane ether with 1,2,3-propanetriol Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2,	25-50%
	H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9 Reg.nr.: 01-2119457014-47	Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	≥5-<10%
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	
CAS: 9016-87-9 Reg.nr.: 01-2119457024-46	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5% Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥5-<10%
CAS: 3470-98-2 EINECS: 222-437-8 Reg.nr.: 01-2120062728-48	1-butylpyrrolidin-2-one Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥2.5-<10%
CAS: 312597-92-5 Polymer Reg.nr.: exempt	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and oxirane, block Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

- FI

www.bostik.it 3/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 3)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

 During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

 $^{\cdot}$ 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

EU

(Contd. on page 5)

www.bostik.it 4/10



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber. NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- **General Information**
- Physical state Fluid

(Contd. on page 6)

EU

www.bostik.it 5/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 5)

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 190 °C

· Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >110 °C

Auto-ignition temperature: 400 °C

Decomposition temperature:pHNot determined.Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

 Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 54.2 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids

(Contd. on page 7)

- EU

www.bostik.it 6/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

,	Contd	۰f		_	6
(Conta	. 01	Dau	е	О

		(Oonta. or page o)
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
· Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with alcohols.

Reacts with water.

Reacts with alkali, amines and strong acids.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- · LD/LC50 values relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 8)

EU

www.bostik.it 7/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 35 (replaces version 34) Revision: 25.07.2024 Printing date 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 7)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Disposal must be made according to official regulations.

- **Uncleaned packaging:**
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA not regulated

· 14.2 UN proper shipping name

ADR/ADN, IMDG, IATA not regulated

(Contd. on page 9)

www.bostik.it 8/10



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Revision: 25.07.2024 Version number 35 (replaces version 34) Printing date 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
· 14.4 Packing group · ADR/ADN, IMDG, IATA	not regulated
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
· Transport/Additional information:	Not dangerous according to the abov specifications.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56a, 74
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

9/10 www.bostik.it



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.07.2024 Version number 35 (replaces version 34) Revision: 25.07.2024

Trade name: BTK PU CONSTRUCT EXPR BE CQ 390G*12 IT

(Contd. of page 9)

· Relevant phrases

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Acute toxicity - inhalation	The classification of the mixture is generally
Skin corrosion/irritation	based on the calculation method using
Serious eye damage/irritation	substance data according to Regulation (EC) No
Respiratory sensitisation	1272/2008.
Skin sensitisation	
Carcinogenicity	

· Department issuing SDS: PSRA

· Contact: PSRA

exposure)

Date of previous version: 02.06.2021
 Version number of previous version: 34

Specific target organ toxicity (repeated

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

Specific target organ toxicity (single exposure)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

www.bostik.it 10/10

FII