

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK 5242/C TI 1800ML*8 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

- FU

www.bostik.it 1/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 14 (replaces version 13) Revision: 11.03.2025 Printing date 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

Hazard pictograms







GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Methylcyclohexane

Acetone

Ethyl acetate

Butanone

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P261 Avoid breathing vapours.

P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-

extinguishing powder, Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH208 Contains Rosin. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

| · Determination of endocrine-disrupting properties | | |
|--|--------------------|------------|
| 78-93-3 | Butanone | List II |
| 98-54-4 | 4-tert-butylphenol | List I; II |

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

CAS: 108-87-2

· Description: Adhesive

| Dangerous compone | nts: |
|---------------------------------------|------|
|---------------------------------------|------|

EINECS: 203-624-3

Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18-

XXXX

Methylcyclohexane

🔞 Flam. Liq. 2, H225; 🚯 Asp. Tox. 1, H304; 💫 Aquatic Acute 1, H400; Aquatic Chronic 2,

H411; (1) Skin Irrit. 2, H315; STOT SE 3, H336

(Contd. on page 3)

25-50%

(Contd. of page 1)

www.bostik.it 2/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

| CAC: 67.64.4 | Acatomo | (Contd. of page 2 |
|---|---|-------------------|
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX | Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 25-50% |
| CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX | Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 10-25% |
| CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX | Butanone ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | ≥2.5-<10% |
| CAS: 59633-97-5 EC number: 812-475-9 | Formaldehyde, polymer with 1,3-benzenediol and 4-(1,1-dimethylethyl)phenol Skin Sens. 1, H317 | 2.5-10% |
| CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32- XXXX | Rosin Skin Sens. 1, H317 | ≥0.1-<1% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32- XXXX | Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | ≥0.025-<0.25% |
| CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 01-2119489419-21- XXXX | 4-tert-butylphenol Repr. 2, H361f; Eye Dam. 1, H318; Aquatic Chronic 1, H410; Skin Irrit. 2, H315 | ≥0.025-<0.25% |
| SVHC | | |
| 98-54-4 4-tert-butylphenol | | |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

EU

www.bostik.it 3/15



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 3)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

ÉU

www.bostik.it 4/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

| | ol parameters ts with limit values that require monitorii | ng at the workplace: |
|------------|---|----------------------|
| 67-64-1 A | - | O |
| IOELV Lo | ng-term value: 1210 mg/m³, 500 ppm | |
| 141-78-6 I | Ethyl acetate | |
| | nort-term value: 1468 mg/m³, 400 ppm ng-term value: 734 mg/m³, 200 ppm | |
| 78-93-3 B | 5 | |
| | nort-term value: 900 mg/m³, 300 ppm ng-term value: 600 mg/m³, 200 ppm | |
| DNELs | | |
| 108-87-2 I | Methylcyclohexane | |
| Oral | Consumer, oral, longterm exposition | 0.4 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 1.7 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 0.8 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 1354.6 mg/m³ |
| | Worker, inhalative, longterm exposition | 64.3 mg/m³ |
| | Consumer DNEL, acute inhalation | 1016 mg/m³ |
| | Consumer, inhalative, longterm exposition | 16 mg/m³ |
| 67-64-1 A | cetone | |
| Oral | Consumer, oral, longterm exposition | 62 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 186 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 62 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 2420 mg/m³ |
| | Worker, inhalative, longterm exposition | 1210 mg/m³ |
| | Consumer, inhalative, longterm exposition | 200 mg/m³ |
| 141-78-6 I | Ethyl acetate | |
| Oral | Consumer, oral, longterm exposition | 4.5 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 63 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 37 mg/kg bw/day |

www.bostik.it 5/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

| luda al - 45 | Mankan to both | ala authania armi e 101 c | 4.400 / 3 | (Contd. of pag |
|--------------|---------------------|---------------------------|-------------------|----------------|
| ınhalatıve | | shortterm exposition | 1468 mg/m³ | |
| | | longterm exposition | 734 mg/m³ | |
| | Consumer DNEL, a | | 734 mg/m³ | |
| | | ve, longterm exposition | 367 mg/m³ | |
| 78-93-3 B | | | | |
| Oral | Consumer, oral, lor | • | 31 mg/kg bw/day | |
| Dermal | Worker, dermal, lor | • | 1161 mg/kg bw/day | |
| | | longterm exposition | 412 mg/kg bw/day | |
| Inhalative | | shortterm exposition | 900 mg/m³ | |
| | | longterm exposition | 600 mg/m³ | |
| | Consumer DNEL, a | | 450 mg/m³ | |
| | Consumer, inhalati | ve, longterm exposition | 106 mg/m³ | |
| PNECs | | | | |
| | Methylcyclohexane | | | |
| | h water | 0.00134 mg/l | | |
| Fres | h water sediment | 0.0362 mg/kg dry weig | ht | |
| Mari | ne water | 0.000134 mg/l | | |
| Mari | ne sediment | 0.00362 mg/kg dry wei | ght | |
| Soil | | 0.0097 mg/kg | | |
| Sew | age treatment plant | 0.273 mg/l | | |
| 67-64-1 A | cetone | | | |
| Fres | h water | 10.6 mg/l | | |
| Fres | h water sediment | 30.4 mg/kg dry weight | | |
| Mari | ne water | 1.06 mg/l | | |
| | ne sediment | 3.04 mg/kg dry weight | | |
| Soil | | 29.5 mg/kg | | |
| | age treatment plant | = | | |
| | adic release | 21 mg/l | | |
| 141-78-6 | Ethyl acetate | | | |
| | h water | 0.24 mg/l | | |
| Fres | h water sediment | 1.15 mg/kg dry weight | | |
| | ne water | 0.024 mg/l | | |
| | ne sediment | 0.115 mg/kg dry weigh | t | |
| Soil | | 0.148 mg/kg | | |
| | age treatment plant | 650 mg/l | | |
| 78-93-3 B | | | | |
| | ondary Poisoning | 1000 mg/kg | | |
| | h water | 55.8 mg/l | | |
| | h water sediment | 284.7 mg/kg dry weigh | t | |
| | ne water | 55.8 mg/l | | |
| Mari | ne sediment | 284.7 mg/kg dry weigh | t | |

www.bostik.it 6/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

| | | (Contd. of page 6) |
|------|------------------------|------------------------|
| | Soil | 22.5 mg/kg |
| | Sewage treatment plant | 709 mg/l |
| | Sporadic release | 55.8 mg/l |
| 1314 | 1-13-2 Zinc oxide | |
| | Fresh water | 0.0144 mg/l |
| | Fresh water sediment | 146.9 mg/kg dry weight |
| | Marine water | 0.0072 mg/l |
| | Marine sediment | 162.2 mg/kg dry weight |
| | Soil | 83.1 mg/kg |
| | Sewage treatment plant | 0.1 mg/l |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

(Contd. on page 8)

- EU

www.bostik.it 7/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.03.2025 Version number 14 (replaces version 13) Printing date 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

· Eye/face protection

(Contd. of page 7)



Tightly sealed goggles

Goggles recommended during refilling

Body protection:

Use protective suit.

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: Dark orange colour · Odour: Characteristic · Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C · Flammability Highly flammable.

Lower and upper explosion limit

2.1 Vol % · Lower: · Upper: 13 Vol % -19 °C · Flash point: 260 °C **Auto-ignition temperature:**

· Decomposition temperature: Not determined. Not determined.

· Viscosity:

· Kinematic viscosity Not determined. Dynamic at 20 °C: 5000 mPas

· Solubility Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 233 hPa Vapour pressure at 50 °C: 800 hPa

Density and/or relative density

Density at 20 °C: 0.923 g/cm³ · Relative density Not determined. Not determined. · Vapour density

All relevant physical data were determined for the · 9.2 Other information

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

(Contd. on page 9)

8/15 www.bostik.it



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 8)

· Appearance:

· Form: Fluid

Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Change in condition

Organic solvents: 77.5 %
 Water: 0.2 %
 Solids content: 22.3 %

• Evaporation rate Not determined.

Information with regard to physical hazard

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit

Substances and mixtures, which emit flammable gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

(Contd. on page 10)

www.bostik.it 9/15

EII.



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 9)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| | • | evant for classification: | |
|------------|-------------------------|---------------------------|--|
| | Methylcyc | | |
| Oral | | | |
| - · - · · | LD50 | 4000-4500 mg/kg (rabbit) | |
| Dermal | LD50 | >2000 mg/kg (rabbit) | |
| 67-64-1 A | | | |
| Oral | LD50 | 5800 mg/kg (rat) | |
| Dermal | LD50 | >15800 mg/kg (rat) | |
| Inhalative | LC50/4 h | 76 mg/l (rat) | |
| 141-78-6 I | Ethyl acet | ate | |
| Oral | LD50 | 4934 mg/kg (rabbit) | |
| Dermal | LD50 | >20000 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | 29.3 mg/l (rat) | |
| 78-93-3 B | 78-93-3 Butanone | | |
| Oral | LD50 | >2193 mg/kg (rat) | |
| Dermal | LD50 | >8050 mg/kg (rat) | |
| 8050-09-7 | Rosin | | |
| Oral | LD50 | 2800 mg/kg (rat) | |
| Dermal | LD50 | >2000 mg/kg (rat) | |
| 1314-13-2 | Zinc oxid | le | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Dermal | LD50 | >2000 mg/kg (rat) | |
| 98-54-4 4- | tert-butyl _l | phenol | |
| Oral | LD50 | 2951 mg/kg (rat) | |
| Dermal | LD50 | 2288 mg/kg (rabbit) | |
| D.: | 4 - CC - | | |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.

(Contd. on page 11)

EU

www.bostik.it 10/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 10)

- · Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

| · Endocrine disrupting properties | | |
|-----------------------------------|--------------------|------------|
| 78-93-3 | Butanone | List II |
| 98-54-4 | 4-tert-butylphenol | List I; II |

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- PDI. Not applicable
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES

· IMDG ADHESIVES, MARINE POLLUTANT

(Contd. on page 12)

-EU

www.bostik.it 11/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

| | (Contd. of page 1 |
|--|---|
| ·IATA | ADHESIVES |
| · 14.3 Transport hazard class(es) | |
| · ADR/ADN | |
| 1 1 1 1 1 1 1 1 1 1 | |
| | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG | |
| | |
| | 3 Flammable liquids. |
| · Label | 3 |
| ·IATA | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| · 14.4 Packing group | |
| · ADR/ADN, IMDG, IATA | III |
| | Product contains environmentally hazardous ubstances: Methylcyclohexane |
| | Symbol (fish and tree) |
| · · · · · · · · · · · · · · · · · · · | Symbol (fish and tree) |
| | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): · EMS Number: | - F-E,S-D |
| Stowage Category | A |
| 14.7 Maritime transport in bulk according to | |
| | Not applicable. |
| · Transport/Additional information: | |
| Quantity limitations | On passenger aircraft/rail: 60 L |
| | On cargo aircraft only: 220 L |
| | |
| ADR/ADN | 5L |

www.bostik.it 12/15



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Version number 14 (replaces version 13)

Trade name: BTK 5242/C TI 1800ML*8 IT

Printing date 11.03.2025

| | (Contd. of page 12 |
|--|--|
| Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport category Tunnel restriction code | 3 E |
| ·IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| , | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml |
| Remarks: | For substances with class 3 according to IMDG Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s). |
| UN "Model Regulation": | UN 1133 ADHESIVES, 3, III ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

| · Regulation (EC) No 273/2004 on drug precursors | | |
|--|----------|---|
| 67-64-1 | Acetone | 3 |
| 78-93-3 | Butanone | 3 |

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

| | | 0. | |
|---------|----------|--------|-------|
| 67-64-1 | Acetone | | 3 |
| 78-93-3 | Butanone | | 3 |
| | | /O t-1 | 4 4 \ |

(Contd. on page 14)

Revision: 11.03.2025

www.bostik.it 13/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 13)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

98-54-4 4-tert-butylphenol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

| H225 | Highly | flammable | liquid | and | vapour |
|-------|----------|-------------|--------|-----|---------|
| 11220 | IIIMIIIV | Hallillabic | IIGGIG | ana | vaboui. |

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

| · Classification according to Regulation (EC) No 1272/2008 | | | | |
|---|--|--|--|--|
| Flammable liquids | Bridging principles | | | |
| Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. | | | |

Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 18.01.2022
Version number of previous version: 13

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 15)

- EII

www.bostik.it 14/15



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 14 (replaces version 13) Printing date 11.03.2025 Revision: 11.03.2025

Trade name: BTK 5242/C TI 1800ML*8 IT

(Contd. of page 14)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

www.bostik.it 15/15