

Printing date 11.03.2025 Version number 14 (replaces version 13)

Revision: 11.03.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: BTK 5242/C TI 3750ML*4 IT

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eve Irrit, 2	H319 Causes serious eve irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 11.03.2025 Version number 14 (replaces version 13) Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

· Hazard pictograms
∇ \vee \vee
GHS02 GHS07 GHS09
· Signal word Danger
· Hazard-determining components of labelling:
Methylcyclohexane
Acetone
Ethyl acetate
Butanone · Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire- extinguishing powder, Carbon dioxide.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with national regulations.
· Additional information:
EUH208 Contains Rosin. May produce an allergic reaction.
2.3 Other hazards
 Results of PBT and vPvB assessment PBT: Not applicable.
• vPvB: Not applicable.
Determination of endocrine-disrupting properties
78-93-3 Butanone List II
98-54-4 4-tert-butylphenol List I; II

• 3.2 Mixtures • Description: Adhesive		
Dangerous components:		
CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18- XXXX	Methylcyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%

EU



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

		(Contd. of page 2
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	Ethyl acetate Flam. Liq. 2, H225;	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone	≥2.5-<10%
CAS: 59633-97-5 EC number: 812-475-9	Formaldehyde, polymer with 1,3-benzenediol and 4-(1,1-dimethylethyl)phenol Skin Sens. 1, H317	2.5-10%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32- XXXX	Rosin	≥0.1-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32- XXXX	Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 01-2119489419-21- XXXX	4-tert-butylphenol	≥0.025-<0.25%
·SVHC		
98-54-4 4-tert-butylphenol		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)



Printing date 11.03.2025 Version num

Version number 14 (replaces version 13)

Revision: 11.03.2025

(Contd. of page 3)

Trade name: BTK 5242/C TI 3750ML*4 IT

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

Water haze Alcohol resistant foam

Fire-extinguishing powder Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

FU



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

(Contd. of page 4)

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1	Control	parameter	S	
				_

· Ingredi	ents with limit values that require monitoring	ng at the workplace:			
67-64-1	Acetone				
IOELV Long-term value: 1210 mg/m³, 500 ppm					
141-78-	6 Ethyl acetate				
	Short-term value: 1468 mg/m³, 400 ppm				
	Long-term value: 734 mg/m³, 200 ppm				
	Butanone				
	Short-term value: 900 mg/m³, 300 ppm				
	Long-term value: 600 mg/m³, 200 ppm				
DNELs					
	2 Methylcyclohexane				
Oral	Consumer, oral, longterm exposition	0.4 mg/kg bw/day			
Dermal	Worker, dermal, longterm exposition	1.7 mg/kg bw/day			
	Consumer, dermal, longterm exposition	0.8 mg/kg bw/day			
Inhalativ	<i>, , , , , , , , , ,</i>	1354.6 mg/m³			
	Worker, inhalative, longterm exposition	64.3 mg/m ³			
Consumer DNEL, acute inhalation 1016 mg/m ³					
Consumer, inhalative, longterm exposition 16 mg/m ³		16 mg/m³			
67-64-1	Acetone				
Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day			
Dermal	Worker, dermal, longterm exposition	186 mg/kg bw/day			
	Consumer, dermal, longterm exposition	62 mg/kg bw/day			
Inhalativ	Worker, inhalative, shortterm exposition	2420 mg/m³			
	Worker, inhalative, longterm exposition	1210 mg/m³			
Consumer, inhalative, longterm exposition 200 mg/m ³					
	6 Ethyl acetate				
Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day			
Dermal	Worker, dermal, longterm exposition	63 mg/kg bw/day			
	Consumer, dermal, longterm exposition	37 mg/kg bw/day			
		(Contd. on page			



Printing date 11.03.2025 Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

Inhalative	Worker inhalative	shortterm exposition	1468 mg/m ³	(Contd. of page
malauve		longterm exposition	734 mg/m ³	
	Consumer DNEL, a	•	734 mg/m ³	
		ve, longterm exposition	367 mg/m ³	
78-93-3 B			Sor night	
Oral	Consumer, oral, lor	naterm exposition	31 mg/kg bw/day	
Dermal	Worker, dermal, lor	•	1161 mg/kg bw/day	
Donnai		longterm exposition	412 mg/kg bw/day	
Inhalative		shortterm exposition	900 mg/m ³	
		longterm exposition	600 mg/m ³	
	Consumer DNEL, a	•	450 mg/m ³	
		ve, longterm exposition	-	
PNECs	Concurrent, initialiat		100 mg/m	
	Methylcyclohexane	•		
	n water	, 0.00134 mg/l		
	h water sediment	0.0362 mg/kg dry weig	ht	
	ne water	0.000134 mg/l		
Marin	ne sediment	0.00362 mg/kg dry wei	aht	
Soil		0.0097 mg/kg		
Sewa	age treatment plant			
67-64-1 A		0		
Fres	h water	10.6 mg/l		
Fres	n water sediment	30.4 mg/kg dry weight		
Marir	ne water	1.06 mg/l		
Marin	ne sediment	3.04 mg/kg dry weight		
Soil		29.5 mg/kg		
Sewa	age treatment plant	100 mg/l		
Spor	adic release	21 mg/l		
141-78-6 E	Ethyl acetate			
Fres	h water	0.24 mg/l		
Fres	n water sediment	1.15 mg/kg dry weight		
	ne water	0.024 mg/l		
	ne sediment	0.115 mg/kg dry weigh	t	
Soil	5 5			
	wage treatment plant 650 mg/l			
78-93-3 B		/		
	ndary Poisoning	1000 mg/kg		
	h water	55.8 mg/l		
	h water sediment	284.7 mg/kg dry weigh	t	
Marin	Marine water 55.8 mg/l			
	Marine sediment 284.7 mg/kg dry weig			



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

(Contd. of page 6)
22.5 mg/kg
709 mg/l
55.8 mg/l
·
0.0144 mg/l
146.9 mg/kg dry weight
0.0072 mg/l
162.2 mg/kg dry weight
83.1 mg/kg
0.1 mg/l

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.
- Avoid contact with the eyes a
- Respiratory protection:
- Use suitable respiratory protective device in case of insufficient ventilation.
- Recommended filter device for short term use:
- Filter AX
- Filter A
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR Nitrile rubber, NBR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

(Contd. on page 8)

FU



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

(Contd. of page 7)

Trade name: BTK 5242/C TI 3750ML*4 IT

· Eye/face protection



.

Tightly sealed goggles

Goggles recommended during refilling **Body protection:** Use protective suit. Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties		
General Information		
· Physical state	Fluid	
· Colour:	Dark orange colour	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and		
boiling range	55.8-56.6 °C	
· Flammability	Highly flammable.	
 Lower and upper explosion limit 	3 ,	
Lower:	2.1 Vol %	
· Upper:	13 Vol %	
Flash point:	-19 °C	
• Auto-ignition temperature:	260 °C	
Decomposition temperature:	Not determined.	
· pH	Not determined.	
· Viscosity:		
Kinematic viscosity	Not determined.	
· Dynamic at 20 °C:	5000 mPas	
Solubility		
· water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log		
value)	Not determined.	
· Vapour pressure at 20 °C:	233 hPa	
· Vapour pressure at 50 °C:	800 hPa	
· Density and/or relative density		
· Density at 20 °C:	0.923 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
•		
• 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not	
	mixture. All non-determined data are not measurable or not relevant for the	
	characterization of the mixture.	
	(Contd. on page 9)	



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

	(Contd. of page a
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	77.5 %
Water:	0.2 %
Solids content:	22.3 %
Change in condition	
Evaporation rate	Not determined.
Flammable gases Aerosols	Void Void
classes Explosives	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Corrosive to metais	VOID

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

(Contd. on page 10)

EU



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

(Contd. of page 9)

Acute tox	icity Base	hazard classes as defined in Regulation (EC) No 1272/2008 d on available data, the classification criteria are not met.
LD/LC50 \	alues rele	evant for classification:
108-87-2 N	Nethylcyc	lohexane
Oral	LD50	4000-4500 mg/kg (rabbit)
Dermal	LD50	>2000 mg/kg (rabbit)
67-64-1 A	cetone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rat)
Inhalative	LC50/4 h	76 mg/l (rat)
141-78-6 E	Ethyl aceta	ate
Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
		29.3 mg/l (rat)
78-93-3 B		
Oral	LD50	>2193 mg/kg (rat)
	LD50	>8050 mg/kg (rat)
8050-09-7	Rosin	
Oral	LD50	2800 mg/kg (rat)
	LD50	>2000 mg/kg (rat)
1314-13-2		
Oral	LD50	>5000 mg/kg (rat)
	LD50	>2000 mg/kg (rat)
98-54-4 4-		
Oral	LD50	2951 mg/kg (rat)
Dermal • Primary ir	LD50	2288 mg/kg (rabbit)
Causes se Respirato Germ cell Not applica Based on a Carcinoge Reproduc STOT-sing STOT-rep Aspiration Additiona	in irritation ye damag rious eye ry or skin mutageni able. available d enicity Bas tive toxic gle expos eated exp n hazard E I toxicolog	n. e/irritation irritation. sensitisation Based on available data, the classification criteria are not met



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

(Contd. of page 10)

List II

List I; II

Trade name: BTK 5242/C TI 3750ML*4 IT

· Repeated dose toxicity Not applicable.

11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Butanone

98-54-4 4-tert-butylphenol

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport informa	ation
 14.1 UN number or ID number ADR/ADN, IMDG, IATA 	UN1133
 14.2 UN proper shipping name ADR/ADN IMDG 	1133 ADHESIVES ADHESIVES, MARINE POLLUTANT
	(Contd. on page 12)



Printing date 11.03.2025 Version number 14 (replaces version 13) Revision

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

	(Contd. of page
	ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
Class	3 (F1) Flammable liquids.
Label	3
IMDG	
Class	3 Flammable liquids.
· Label	3
IATA	
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardou
	substances: Methylcyclohexane
 Marine pollutant: Special marking (ADR/ADN): 	Symbol (fish and tree) Symbol (fish and tree)
	• • •
 14.6 Special precautions for user Hazard identification number (Kemler code): 	Warning: Flammable liquids. -
• EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
· Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
· ADR/ADN	
· Limited quantities (LQ)	5L
	(Contd. on page



Printing date 11.03.2025 Ve

Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

	(Contd. of page 12)
 Excepted quantities (EQ) Transport category Tunnel restriction code 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Remarks:	For substances with class 3 according to IMDG- Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $200\ t$
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

	IVE 2011/65/EU on the restriction of the use of certain hazardous substances al and electronic equipment – Annex II	in
None of	the ingredients is listed.	
· REGUL	ATION (EU) 2019/1148	
· Regulat	ion (EC) No 273/2004 on drug precursors	
67-64-1	Acetone	3
78-93-3	Butanone	3
 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors 		
67-64-1	Acetone	3
78-93-3	Butanone	3

(Contd. on page 14)



Printing date 11.03.2025 Version number 14 (replaces version 13)

Revision: 11.03.2025

Trade name: BTK 5242/C TI 3750ML*4 IT

(Contd. of page 13)

• National regulations:

· Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57

98-54-4 4-tert-butylphenol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: PSRA

- Contact: PSRA
- Date of previous version: 18.01.2022
- · Version number of previous version: 13
- Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 15)



Printing date 11.03.2025

Version number 14 (replaces version 13)

Revision: 11.03.2025

(Contd. of page 14)

EU

Trade name: BTK 5242/C TI 3750ML*4 IT

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2