

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

| Aerosol 1 | H222-H229 | Extremely | flammable aerosol. | Pressurised | container: | May | burst if |
|-----------|-----------|-----------|--------------------|-------------|------------|-----|----------|
| | | heated | | | | | |



GHS08 health hazard

| Resp. Sens. 1 | H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
|---------------|------|--|
| Carc. 2 | H351 | Suspected of causing cancer. |
| STOT RE 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |



| Acute Tox. 4 | H332 | Harmful if inhaled. |
|---------------|------|--------------------------------------|
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| Skin Sens. 1 | H317 | May cause an allergic skin reaction. |
| STOT SE 3 | H335 | May cause respiratory irritation. |

(Contd. on page 2)

EU-EN

www.bostik.it 1/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 1)

Lact. H362 May cause harm to breast-fed children.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues alkanes, C14-17, chloro

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P263 Avoid contact during pregnancy and while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

EU-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 2)

· **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Sealant

| Description. Scalant | | |
|---|--|---------|
| · Dangerous components: | | |
| CAS: 9016-87-9 Reg.nr.: 01-2119457024-46 | diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | 25-50% |
| CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X | alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362 | 10-25% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-10% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-10% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 | n-Butan Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-10% |
| CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37 | dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-10% |
| CAS: 124-38-9 EINECS: 204-696-9 | carbon dioxide substance with a Community workplace exposure limit | 2.5-10% |

Additional information:

Propellant: CO2

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 4)

www.bostik.it 3/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 3)

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B

(Contd. on page 5)

EU-EN

www.bostik.it 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

124-38-9 carbon dioxide

IOELV Long-term value: 9000 mg/m³, 5000 ppm

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye protection:

Safety glasses



Tightly sealed goggles

(Contd. on page 6)

EU-EN

www.bostik.it 5/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 5)

· Body protection: Use protective suit.

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** -78.5 °C

· Flash point: -97 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

· Decomposition temperature: Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.8 Vol % Upper: 8.5 Vol %

· Vapour pressure at 25 °C: 0 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.009 g/cm³
 Not determined.
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 20.4 %

Solids content: 66.0 %

(Contd. on page 7)

EU-EN

www.bostik.it 6/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 6)

• 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

106-97-8 n-Butan

Inhalative LC50/4 h 658 mg/l (rat)

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 8)

EU-EN

www.bostik.it 7/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 7)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/ADN 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR/ADN



Class 2 5F Gases.

(Contd. on page 9)

EU-EN -

www.bostik.it 8/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

| | (Contd. of pa |
|---|---|
| Label | 2.1 |
| · IMDG, IATA | |
| | |
| · Class · Label | 2.1 2.1 |
| · 14.4 Packing group · ADR/ADN, IMDG, IATA | not regulated |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: | Warning: Gases F-D,S-U |
| Stowage Code | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capa of 1 litre: Category A. For AEROSOLS wit capacity above 1 litre: Category B. For WAS AEROSOLS: Category C, Clear of living quarte |
| · Segregation Code | SG69 For AEROSOLS with a maximum capa of 1 litre: Segregation as for class 9. Stow "separated froclass 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision class 2. |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: · Quantity limitations | On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg |
| · ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| · Transport category · Tunnel restriction code | 2 D |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| · Remarks: | Under certain conditions substances in Clas (flammable liquids) can be classified in |

www.bostik.it 9/11

(Contd. on page 10)

EU-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2021 Version number 21 Revision: 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 9)

| | (Some or page of |
|--------------------------|---|
| | packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2 |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 11)

EU-EN

www.bostik.it 10/11



Safety data sheet according to 1907/2006/EC, Article 31

Version number 21 Revision: 07.01.2021 Printing date 07.01.2021

Trade name: BOSTIK PU PRECISION GUN B3 LOW EXPANSION*12 IT

(Contd. of page 10)

| · Classification according to Regulation (EC) No 1272/2008 | | | |
|--|--|--|--|
| Aerosols | Bridging principles | | |
| Acute toxicity - inhalation Skin corrosion/irritation Serious eye damage/eye irritation Respiratory sensitisation Skin sensitisation Carcinogenicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. | | |

· Department issuing SDS: Bison QESH

· Contact:

Marketing UHU BOSTIK

Reach coordinator

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - inhalation – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

Lact.: Reproductive toxicity – effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

* Data compared to the previous version altered.

EU-EN

www.bostik.it 11/11