

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

ΕU

www.bostik.it 1/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

Ethyl acetate

Butanone

Acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Ethyl acetate

Butanone

Acetone

· Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 3)

EU

www.bostik.it 2/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 2)

Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

Description. Addresive		
· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	Ethyl acetate SE 3, H336, EUH066	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

(Contd. on page 4)

- FI

www.bostik.it 3/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 3)

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

=11-

(Contd. on page 5)

www.bostik.it 4/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 4)

· 8.1 Control parameters				
Ingredients with limit values that require monitoring at the workplace:				
141-78-6 Ethyl acetate				
IOELV Short-term value: 1468 mg/m³, 400 ppm				
Long-term value: 734 mg/m³, 200 ppm				
78-93-3 Butanone				
	ort-term value: 900			
	ng-term value: 600	mg/m³, 200 ppm		
67-64-1 A		0 mg/m³ E00 nnm		
	ng-term value: 121	o mg/m², soo ppm		
DNELs				
	Ethyl acetate			
Oral	Consumer, oral, lo	•	4.5 mg/kg bw/day	
Dermal	Worker, dermal, lo	•	63 mg/kg bw/day	
		, longterm exposition	37 mg/kg bw/day	
Inhalative	· ·	shortterm exposition	1468 mg/m³	
		longterm exposition	734 mg/m³	
	Consumer DNEL,		734 mg/m³	
		ive, longterm exposition	367 mg/m³	
78-93-3 B				
Oral	Consumer, oral, lo	•	31 mg/kg bw/day	
Dermal	Worker, dermal, lo	•	1161 mg/kg bw/day	
		, longterm exposition	412 mg/kg bw/day	
Inhalative	'	shortterm exposition	900 mg/m³	
		longterm exposition	600 mg/m³	
	Consumer DNEL,		450 mg/m³	
		ive, longterm exposition	106 mg/m³	
67-64-1 A				
Oral	Consumer, oral, lo	•	62 mg/kg bw/day	
Dermal	Worker, dermal, lo	•	186 mg/kg bw/day	
		, longterm exposition	62 mg/kg bw/day	
Inhalative	· ·	shortterm exposition	2420 mg/m³	
		longterm exposition	1210 mg/m³	
Consumer, inhalative, longterm expos		ive, longterm exposition	200 mg/m³	
PNECs				
141-78-6 E	Ethyl acetate			
Fres	h water	0.24 mg/l		
		1.15 mg/kg dry weight		

www.bostik.it 5/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

		(Contd. of page 5
	Marine sediment	0.115 mg/kg dry weight
	Soil	0.148 mg/kg
	Sewage treatment plant	650 mg/l
78-9	3-3 Butanone	
Oral	Secondary Poisoning	1000 mg/kg
	Fresh water	55.8 mg/l
	Fresh water sediment	284.7 mg/kg dry weight
	Marine water	55.8 mg/l
	Marine sediment	284.7 mg/kg dry weight
	Soil	22.5 mg/kg
	Sewage treatment plant	709 mg/l
	Sporadic release	55.8 mg/l
67-6	4-1 Acetone	
	Fresh water	10.6 mg/l
	Fresh water sediment	30.4 mg/kg dry weight
	Marine water	1.06 mg/l
	Marine sediment	3.04 mg/kg dry weight
	Soil	29.5 mg/kg
	Sewage treatment plant	100 mg/l
	Sporadic release	21 mg/l
. ۸ ۵۵	tional information: The	lists valid during the making were used as hasis

- · **Additional information:** The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

(Contd. on page 7)

ΕU

www.bostik.it 6/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 6)

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Ester-like
Not determined.

Undetermined.

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C
Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.8 Vol %
Upper: 13 Vol %
Flash point: -18 °C
Auto-ignition temperature: 460 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 600 mPas

Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value)
Vapour pressure at 20 °C:
Vapour pressure at 50 °C:
800 hPa

Density and/or relative density

Density at 20 °C: 0.94-0.941 g/cm³
Relative density Not determined.

(Contd. on page 8)

EU

www.bostik.it 7/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

	(Contd. of page 7)
· Vapour density	Not determined.
· 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· Appearance:	
· Form:	Fluid
 Important information on protection of hea and environment, and on safety. 	alth
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	·
· Organic solvents:	79.7 %
· Solids content:	20.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	\/a;d
Explosives	Void
· Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures Substances and mixtures, which emit	Void

Void

Void

Void

Void

Void

Void

SECTION 10: Stability and reactivity

flammable gases in contact with water

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

Oxidising liquids

· Oxidising solids

· Organic peroxides

Corrosive to metals

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 9)

- FI

www.bostik.it 8/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 8)

• 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
141-78-6 Ethyl acetate		
Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.3 mg/l (rat)
78-93-3 Butanone		
Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>8050 mg/kg (rat)
67-64-1 Acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rat)
Inhalative	LC50/4 h	76 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrin	e disrupting properties	
78-93-3	Butanone	List II
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 10)

FII

www.bostik.it 9/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 9)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

. 14 1	HIN	number	or ID	number
14.1	UIV	HUHHDEL	טו וט	Hullibel

· ADR/ADN, IMDG, IATA UN1133

14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES, special provision 640D

· IMDG, IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR/ADN



Class 3 (F1) Flammable liquids.

Label 3

· IMDG, IATA



Class 3 Flammable liquids.

(Contd. on page 11)

EU

www.bostik.it 10/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

	(Contd. of page 1
Label	3
14.4 Packing group ADR/ADN, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml
Transport category Tunnel restriction code	2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml
Remarks:	For substances with class 3 according to IMDG Code chapter 2.3.2.2 packing group is classifie in packing group III, as viscosity is in accordanc with requirements (flow time t > 100s).
	1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

(Contd. on page 12)

ΕU

www.bostik.it 11/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 43 (replaces version 42) Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 11)

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 Acetone

· Regulation (EC) No 273/2004 on drug precursors

78-93-3	Butanone	3
67-64-1	Acetone	3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 Butanone	J
67-64-1 Acetone	3

^{• 15.2} Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
	The classification of the mixture is generally based
	on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 31.07.2024
Version number of previous version: 42

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 13)

ΕU

www.bostik.it 12/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 43 (replaces version 42) Printing date 22.03.2025 Revision: 22.03.2025

Trade name: BTK HARD PLASTIC ADHESIVE BP 50G*6 IT

(Contd. of page 12)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

www.bostik.it 13/13