

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BTK PLAS FLE FPB 50G*6 IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: +49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

ΕU

www.bostik.it 1/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

Acetone

Ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Acetone

Ethyl acetate

· Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

EU

(Contd. on page 3)

www.bostik.it 2/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	Ethyl acetate The Flam. Liq. 2, H225; The Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40- XXXX	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

EU

www.bostik.it 3/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-64-1 Acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 5)

FI.

www.bostik.it 4/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

141-78-6 I	Ethyl acetate		(Contd. of pag
		: 1468 mg/m³, 400 ppm	
		: 734 mg/m³, 200 ppm	
DNELs		<u> </u>	
67-64-1 A	cetone		
Oral		al, longterm exposition	62 mg/kg bw/day
Dermal		al, longterm exposition	186 mg/kg bw/day
	· ·	ermal, longterm exposition	62 mg/kg bw/day
Inhalative	· ·	ative, shortterm exposition	2420 mg/m³
		ative, longterm exposition	1210 mg/m³
	Consumer, in	halative, longterm exposition	200 mg/m³
141-78-6 I	Ethyl acetate		-
Oral	Consumer, or	al, longterm exposition	4.5 mg/kg bw/day
Dermal	Worker, derm	al, longterm exposition	63 mg/kg bw/day
	Consumer, de	ermal, longterm exposition	37 mg/kg bw/day
Inhalative	Worker, inhal	ative, shortterm exposition	1468 mg/m³
	Worker, inhal	ative, longterm exposition	734 mg/m³
		NEL, acute inhalation	734 mg/m³
	Consumer, inhalative, longterm exposition		367 mg/m³
1065336-91-5 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			
Oral	Consumer, or	al, longterm exposition	0.18 mg/kg bw/day
Dermal	Worker, derm	al, longterm exposition	1.8 mg/kg bw/day
	Consumer, de	ermal, longterm exposition	0.9 mg/kg bw/day
Inhalative	Worker, inhal	ative, longterm exposition	1.27 mg/m³
	Consumer, in	halative, longterm exposition	0.31 mg/m³
· PNECs			
67-64-1 A	cetone		
Fresh wat	er	10.6 mg/l	
Fresh wat	er sediment	30.4 mg/kg dry weight	
Marine water 1.06 mg/l		1.06 mg/l	
Marine sediment 3.04 mg/kg dry weight		3.04 mg/kg dry weight	
Soil 29.5 mg/kg			
_	Sewage treatment plant 100 mg/l		
Sporadic release 21 mg/l		21 mg/l	
	Ethyl acetate		
Fresh water 0.24 mg/l		_	
Fresh water sediment 1.15 mg/kg dry weight			
Marine wa		0.024 mg/l	
Marine sediment 0.115 mg/kg dry weight		0.115 mg/kg dry weight	
Soil		0.148 mg/kg	

www.bostik.it 5/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 5)

	(Gonta: or page o)	
Sewage treatment plant	650 mg/l	
1065336-91-5 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Meth 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Fresh water	0.0022 mg/l	
Fresh water sediment	1.05 mg/kg dry weight	
Marine water	0.00022 mg/l	
Marine sediment	0.11 mg/kg dry weight	
Soil	0.21 mg/kg	
Sewage treatment plant	1 mg/l	
Sporadic release	0.009 mg/l	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

· Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR


Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



(Contd. on page 7)

EU

www.bostik.it 6/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 6)

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 55 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 2.1 Vol %
Upper: 13 Vol %
Flash point: -17 °C
Auto-ignition temperature: 460 °C

• Decomposition temperature: Not determined. pH Not determined.

· Viscosity:

Kinematic viscosityDynamic at 20 °C:Not determined.3000 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined. • Vapour pressure at 20 °C: 233 hPa

· Vapour pressure at 20 °C: 233 nPa · Vapour pressure at 50 °C: 800 hPa

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• **9.2 Other information** All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 78.4 %

(Contd. on page 8)

- , - FI

www.bostik.it 7/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 7)

· VOC (EC)	78.41 %
Solids content:	21.5 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

Void
Void

· Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-64-1 Acetone

Oral	LD50	5800 mg/kg (rat)
	LD50	>15800 mg/kg (rat)
Inhalative	LC50/4 h	76 mg/l (rat)

(Contd. on page 9)

ÉU



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 8)

141-78-6 I	Ethyl aceta	ate
Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.3 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- Additional ecological information:
- General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 10)

www.bostik.it 9/12

- EU



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2025 Version number 40 (replaces version 39) Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 9)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION	14: T	Fransport	inf	formation
---------	-------	------------------	-----	-----------

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR/ADN



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR/ADN, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): -

· EMS Number: F-E,S-D

(Contd. on page 11)

- EU

www.bostik.it 10/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 40 (replaces version 39) Printing date 19.03.2025 Revision: 17.12.2024

Trade name: BTK PLAS FLE FPB 50G*6 IT

	(Contd. of page 10
Stowage Category	Α
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
Tunnel restriction code	E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000
Remarks:	ml For substances with class 3 according to IMDG Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Regulation (EC) No 2/3/2004 on drug precursors
--

67-64-1 Acetone 3

www.bostik.it 11/12

(Contd. on page 12)



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 17.12.2024 Version number 40 (replaces version 39) Printing date 19.03.2025

Trade name: BTK PLAS FLE FPB 50G*6 IT

(Contd. of page 11)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 Acetone

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Suspected of damaging fertility. H361f

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 12.02.2024 · Version number of previous version: 39

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

12/12 www.bostik.it