

Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: BK PELLE FPB 50G*6 IT

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

• 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

• Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

	n of the substance or mixture cording to Regulation (EC) No 1272/2008 flame
Flam. Liq. 2	H225 Highly flammable liquid and vapour.
GHS07	
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatic Chronic 3	B H412 Harmful to aquatic life with long lasting effects.
 2.2 Label element Labelling accord 	nts ling to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 21.03.2025 Version number 38 (replaces version 37) Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:
- Methylcyclohexane
- Butanone
- Ethyl acetate
- Acetone
- Hazard statements
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fireextinguishing powder, Carbon dioxide.
- P501 Dispose of contents/container in accordance with national regulations.
- · Additional information:
- EUH208 Contains Rosin. May produce an allergic reaction.
- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labelling:
- Methylcyclohexane Butanone Ethyl acetate

Acetone

· Hazard statements

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

(Contd. on page 3)

(Contd. of page 1)



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

P261 Avoid breathing vapours.

(Contd. of page 2)

List II

P501 Dispose of contents/container in accordance with national regulations.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 Butanone

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

	· Dangerous	components:
--	-------------	-------------

Methylcyclohexane	> 10 - 0 5 0/
Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
Butanone	10-25%
Ethyl acetate Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
Acetone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
p-tert-butylphenol formaldehyde resin Skin Sens. 1, H317	2.5-10%
Rosin Skin Sens. 1, H317	≥0.1-<1%
Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
	 Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 Butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Acetone Stor SE 3, H336, EUH066 Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1,



Printing date 21.03.2025 Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 3)

Trade name: BK PELLE FPB 50G*6 IT

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Water haze Alcohol resistant foam Fire-extinguishing powder
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

EU



Printing date 21.03.2025 Version number 38 (replaces version 37) Revision

Revision: 11.03.2025

(Contd. of page 4)

Trade name: BK PELLE FPB 50G*6 IT

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 • Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

78-93-3 E	Butanone		
IOELV S	hort-term value: 900 mg/m³, 300 ppm		
	ong-term value: 600 mg/m³, 200 ppm		
141-78-6	Ethyl acetate		
IOELV S	hort-term value: 1468 mg/m³, 400 ppm		
L	ong-term value: 734 mg/m³, 200 ppm		
67-64-1 A	Acetone		
IOELV L	ong-term value: 1210 mg/m³, 500 ppm		
DNELs			
108-87-2	Methylcyclohexane		
Oral	Consumer, oral, longterm exposition	0.4 mg/kg bw/day	
Dermal	Worker, dermal, longterm exposition	1.7 mg/kg bw/day	
	Consumer, dermal, longterm exposition	0.8 mg/kg bw/day	
Inhalative	Worker, inhalative, shortterm exposition	1354.6 mg/m³	
	Worker, inhalative, longterm exposition	64.3 mg/m³	
	Consumer DNEL, acute inhalation	1016 mg/m³	
	Consumer, inhalative, longterm exposition	16 mg/m ³	
78-93-3 E	Butanone	1	
	Consumer, oral, longterm exposition	31 mg/kg bw/day	

www.bostik.it

ΕU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

Dermal	Worker, dermal, lor	ngterm exposition	1161 mg/kg bw/day	(Contd. of pa
		longterm exposition	412 mg/kg bw/day	
Inhalative		shortterm exposition	900 mg/m ³	
		longterm exposition	600 mg/m³	
	Consumer DNEL, a	•	450 mg/m³	
	Consumer, inhalative, longterm exposition		-	
141-78-6	Ethyl acetate		Ŭ	
Oral	Consumer, oral, lor	ngterm exposition	4.5 mg/kg bw/day	
Dermal	Worker, dermal, lor	ngterm exposition	63 mg/kg bw/day	
	Consumer, dermal,	longterm exposition	37 mg/kg bw/day	
Inhalative	Worker, inhalative,	shortterm exposition	1468 mg/m ³	
	Worker, inhalative,	longterm exposition	734 mg/m³	
	Consumer DNEL, a	•	734 mg/m³	
	Consumer, inhalati	ve, longterm exposition	367 mg/m ³	
67-64-1 A	Acetone		1	
Oral	Consumer, oral, lor	ngterm exposition	62 mg/kg bw/day	
Dermal	Worker, dermal, lor	ngterm exposition	186 mg/kg bw/day	
	Consumer, dermal,	longterm exposition	62 mg/kg bw/day	
Inhalative	Worker, inhalative,	shortterm exposition	2420 mg/m³	
	Worker, inhalative,	longterm exposition	1210 mg/m³	
	Consumer, inhalati	ve, longterm exposition	200 mg/m³	
PNECs				
108-87-2	Methylcyclohexane	•		
Free	sh water	0.00134 mg/l		
Free	sh water sediment	0.0362 mg/kg dry weig	ht	
Mar	ine water	0.000134 mg/l		
Mar	ine sediment	0.00362 mg/kg dry wei	ght	
Soil		0.0097 mg/kg		
Sev	age treatment plant	0.273 mg/l		
78-93-3 E	Butanone			
Oral Sec	ondary Poisoning	1000 mg/kg		
Free	sh water	55.8 mg/l		
Free	sh water sediment	284.7 mg/kg dry weigh	t	
Mar	ine water	55.8 mg/l		
Mar	ine sediment	284.7 mg/kg dry weigh	t	
Soil	22.5 mg/kg			
Sev	age treatment plant 709 mg/l			
	radic release	55.8 mg/l		
	Ethyl acetate			
	sh water	0.24 mg/l		
Free	sh water sediment	1.15 mg/kg dry weight		
				(Contd. on pa



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

Marine water	(Contd. of page 6
Marine sediment	0.024 mg/l
	0.115 mg/kg dry weight
Soil	0.148 mg/kg
Sewage treatment plant	
67-64-1 Acetone	
Fresh water	10.6 mg/l
Fresh water sediment	30.4 mg/kg dry weight
Marine water	1.06 mg/l
Marine sediment	3.04 mg/kg dry weight
Soil	29.5 mg/kg
Sewage treatment plant	-
Sporadic release	21 mg/l
1314-13-2 Zinc oxide	
Fresh water	0.0144 mg/l
Fresh water sediment	146.9 mg/kg dry weight
Marine water	0.0072 mg/l
Marine sediment	162.2 mg/kg dry weight
Soil	83.1 mg/kg
Sewage treatment plant	t 0.1 mg/l
 8.2 Exposure controls Appropriate engineering controls 	e lists valid during the making were used as basis. Introls No further data; see section 7. Ures, such as personal protective equipment
 8.2 Exposure controls Appropriate engineering controls Individual protection measure General protective and hyg The usual precautionary measure Keep away from foodstuffs, books and the second secon	ective device in case of insufficient ventilation.
 8.2 Exposure controls Appropriate engineering controls Individual protection measures General protective and hygen the usual precautionary measures and the usual precautionary measures and the usual precaution of the usual precaution	ective device in case of insufficient ventilation.



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 7)

Trade name: BK PELLE FPB 50G*6 IT

· Material of gloves

Recommended thickness of the material: > 0,12 mm Butyl rubber, BR Nitrile rubber, NBR Recommended thickness of the material: > 0,7 mm **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).
- · Eye/face protection



.

Tightly sealed goggles

Goggles recommended during refilling **Body protection:** Use protective suit. Solvent resistant protective clothing

SECTION 9: Physical and chemical properties		
· 9.1 Information on basic physical and che	mical properties	
General Information		
· Physical state	Fluid	
· Colour:	Yellow	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
 Boiling point or initial boiling point and 		
boiling range	55.8-56.6 °C	
· Flammability	Highly flammable.	
• Lower and upper explosion limit		
· Lower:	1.8 Vol %	
· Upper:	11.5 Vol %	
· Flash point:	-4 °C	
 Auto-ignition temperature: 	260 °C	
 Decomposition temperature: 	Not determined.	
∙рН	Not determined.	
· Viscosity:		
Kinematic viscosity	Not determined.	
· Dynamic at 20 °C:	2500 mPas	
· Solubility		
· water:	Not miscible or difficult to mix.	
 Partition coefficient n-octanol/water (log 		
value)	Not determined.	
 Vapour pressure at 20 °C: 	105 hPa	
 Vapour pressure at 50 °C: 	360 hPa	
		(Contd. on page 9)

EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

	(Contd. of page 8
Density and/or relative density	
Density at 20 °C:	0.933-~0.933 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of heal and environment, and on safety.	lth
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
.	explosive air/vapour mixtures are possible.
Solvent content:	^
Organic solvents:	77.5 %
Water:	0.2 %
VOC (EC)	77.45 %
Solids content:	22.4 %
Change in condition	Not determined.
Evaporation rate	Not determined.
Information with regard to physical haza	ırd
classes	No.54
Explosives	Void
Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
. Elammabla calida	
	Void
Self-reactive substances and mixtures	Void
• Self-reactive substances and mixtures • Pyrophoric liquids	Void Void
 Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures 	Void Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures 	Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit 	Void Void Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water 	Void Void Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids 	Void Void Void Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids 	Void Void Void Void Void Void
 Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids 	Void Void Void Void Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

(Contd. on page 10) EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 9)

Trade name: BK PELLE FPB 50G*6 IT

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

Oral Dermal	Methylcyc	
Dermal	LD50	
		4000-4500 mg/kg (rabbit)
	LD50	>2000 mg/kg (rabbit)
78-93-3 E	Butanone	
Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>8050 mg/kg (rat)
141-78-6	Ethyl acet	ate
Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.3 mg/l (rat)
67-64-1 A	cetone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rat)
Inhalative	LC50/4 h	76 mg/l (rat)
25085-50	-1 p-tert-b	utylphenol formaldehyde resin
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
8050-09-	7 Rosin	
Oral	LD50	2800 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
1314-13-	2 Zinc oxic	le
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Skin cor Causes s Serious Causes s	erious eye	ation n. e/irritation

(Contd. on page 11)

EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

(Contd. of page 10)

List II

List I: II

Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· Acute effects (acute toxicity, irritation and corrosivity) Not applicable.

- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Butanone

98-54-4 4-tert-butylphenol

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 12)

FU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

(Contd. of page 11)

Trade name: BK PELLE FPB 50G*6 IT

· Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR/ADN, IMDG, IATA	111
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	
EMS Number: Stowage Category	F-E,S-D A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 1000
	(Contd. on page 1



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

	(Contd. of page 12)
· · Transport category · Tunnel restriction code	ml 3 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) Remarks: 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml For substances with class 3 according to IMDG- Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance
· UN "Model Regulation":	With requirements (flow time t > 100s). UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors
- 78-93-3 Butanone
- 67-64-1 Acetone
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
- 78-93-3 Butanone

67-64-1 Acetone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 14)

3

3

3

3

EU



Printing date 21.03.2025

Version number 38 (replaces version 37)

Revision: 11.03.2025

Trade name: BK PELLE FPB 50G*6 IT

(Contd. of page 13) H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Flammable liquids Bridging principles Skin corrosion/irritation The classification of the mixture is generally Serious eye damage/irritation based on the calculation method using Specific target organ toxicity (single exposure) substance data according to Regulation (EC) No Hazardous to the aquatic environment - long-1272/2008. term (chronic) aquatic hazard · Department issuing SDS: PSRA Contact: PSRA Date of previous version: 24.07.2024 · Version number of previous version: 37 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 FII