

Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

• Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0
 E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

· Further information obtainable from: PSRA

1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https:// poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

(Contd. on page 2)



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

(Contd. of page 1) · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing vapours. P280 Wear protective gloves. P302+P352 IF ON SKIN: Wash with plenty of water. P501 Dispose of contents/container in accordance with national regulations. · Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:			
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; \$\stringlet Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 %	≥10-<25%	
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-2.5%	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: No special measures required.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

EU



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

(Contd. of page 2)

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required. • 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

FU



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

monitored	at the workplace.		
· DNELs			
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)			
Oral	Consumer, oral, long	gterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, long	gterm exposition	0.75 mg/kg bw/day (rat)
	Consumer, dermal, l	ongterm exposition	0.0893 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, lo	ongterm exposition	4.93 mg/m³ (rat)
	Consumer, inhalative	e, longterm exposition	0.87 mg/m³ (rat)
· Additiona	I information: The list	sts valid during the ma	king were used as basis.
• General p The usual Keep awa Immediate Wash han Do not inh Avoid cont	rotective and hygien precautionary measury from foodstuffs, bever ly remove all soiled and ds before breaks and ale gases / fumes / and tact with the eyes and ory protection: Not res	nic measures: ures are to be adhered verages and feed. and contaminated cloth I at the end of work. erosols. d skin.	protective equipment to when handling chemicals. ing
MIS-	Protective gloves		
preparatio	n.		esistant to the product/ the substance/ th
Selection degradatio	on	on consideration of th	e penetration times, rates of diffusion and th
Recomme	nded thickness of the ection Material	e material: > 0,12 mm :butyl-rubber (e.g. Bu : > 8 h	toject 898: material thickness 0,7 mm)
Material Break thro		:Ethyl Vinyl Alcohol L :>8 h	aminate (EVAL)
	erial for short-term us		TT <480 min): nitrile rubber, neoprene rubber
The select the stands	ted protective gloves ard EN 374 derived	from it. Gloves shoul	pecifications of EU Directive 89/686/EEC an d be discarded and replaced if there is an n. Take note of the information given by th

the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed (Contd. on page 5)



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

(Contd. of page 4)

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

with the producers of the protective gloves.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chen	nical properties
• General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	
boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
· Upper:	Not determined.
Flash point:	>100 °C
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	Not determined.
· Density at 20 °C:	1.9 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are not
	measurable or not relevant for the
	characterization of the mixture.
· Appearance:	
· Form:	Solid
	(Contd. on page 6



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

	(Contd. of page
· Important information on protection of hea	alth
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Solids content:	43.5 %
 Change in condition 	
· Evaporation rate	Not determined.
· Information with regard to physical haz	ard
classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
 Self-reactive substances and mixtures 	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
 Substances and mixtures, which emit 	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 7)

EU



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

(Contd. of page 6)

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

· Serious eye damage/irritation

- Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity
- Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 8)

FU



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

(Contd. of page 7)

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	not regulated	
ADN	- not regulated	
 14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA 	not regulated	
· 14.3 Transport hazard class(es)		
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated	
 14.4 Packing group ADR/ADN, IMDG, IATA 	not regulated	
· 14.5 Environmental hazards:	Not applicable.	
[·] 14.6 Special precautions for user	Not applicable.	
 14.7 Maritime transport in bulk accordi IMO instruments 	i ng to Not applicable.	
· Transport/Additional information:	Not dangerous according to the above specifications.	
· UN "Model Regulation":	not regulated	

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)



Printing date 26.01.2024

Version number 11 (replaces version 10)

Revision: 26.01.2024

Trade name: BTK EPOXY STICK AQUA BS 56G*12 IT

(Contd. of page 8)

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
 Department issuing SDS: UHU QESH Contact: UHU QESH Date of previous version: 04.07.2023 Version number of previous version: 10 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchand the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Lab EINECS: European Inventory of Existing Commercial Chemic ELINCS: European Ist of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American O DNEL: Derived No-Effect Level (REACH) PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Ic * Data compared to the previous version alter 	cal Substances Chemical Society) ong-term aquatic hazard – Category 2 ong-term aquatic hazard – Category 3
	EL