

Printing date 12.08.2024 Version number 17 (replaces version 16)

Revision: 12.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https://poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains trimethoxyvinylsilane. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

- 2.3 Other hazards During curing methanol (CAS 67-56-1) is produced.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

(Contd. on page 2)



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

Dangerous components:CAS: 1067-25-0EINECS: 213-926-7Reg.nr.: 01-2119972314-37-XXXX	1-2.5%
EINECS: 213-926-7 Reg.nr.: 01-2119972314-37- XXXX	1-2.5%
CAS: 2768-02-7 EINECS: 220-449-8 Index number: 014-049-00-0 Reg.nr.: 01-2119513215-52	n ≥0.1-<1%
CAS: 52829-07-9 EINECS: 258-207-9 Reg.nr.: 01-2119537297-32 bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate & Repr. 2, H361f; CAS: 52829-07-9 & Repr. 2, H361f; CAS: 52829-07-9	atic <0.25%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions. • 5.2 Special hazards arising from the substance or mixture

- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

EU



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

(Contd. of page 2)

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** No special precautions are necessary if used correctly. • **Information about fire - and explosion protection:** No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: 12
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Г

Oral	trimethoxypropylsilane Consumer, oral, shortterm exposition	4 mg/kg bw/day (rat)	
Ulai	•	4 mg/kg bw/day (rat)	
	Consumer, oral, longterm exposition		
Dermal	Worker, dermal, shortterm exposition	20 mg/kg bw/day (rat)	
	Worker, dermal, longterm exposition	20 mg/kg bw/day (rat)	
	Consumer, dermal, shortterm exposition	4 mg/kg bw/day (rat)	
	Consumer, dermal, longterm exposition	4 mg/kg bw/day (rat)	
Inhalative	Worker, inhalative, shortterm exposition	130 mg/m³ (rat)	
	Worker, inhalative, longterm exposition	130 mg/m³ (rat)	
	Consumer DNEL, acute inhalation	26400 mg/m³ (rat)	
	Consumer, inhalative, longterm exposition	26 mg/m³ (rat)	
		26 mg/m³ (rabbit)	
2768-02-7	trimethoxyvinylsilane		
Oral	Consumer, oral, longterm exposition	0.3 mg/kg bw/day (rat)	
Dermal	Worker, dermal, longterm exposition	3.9 mg/kg bw/day (rat)	
	Consumer, dermal, longterm exposition	7.8 mg/kg bw/day (rat)	
Inhalative	Worker, inhalative, longterm exposition	27.6 mg/m³ (rat)	
	Consumer, inhalative, longterm exposition	6.7 mg/m³ (rat)	
		18.9 mg/m³ (rabbit)	



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

	(Contd. of page		
PNECs 2768-02-7 trimethoxyvi	nylsilano		
Fresh water	0.4 mg/l (rat)		
Fresh water sediment	1.5 mg/kg dry weight (rat)		
Marine water 0.04 mg/l (rat)			
Marine sediment			
Soil			
Sewage treatment plant	6.6 mg/l (rat)		
Sporadic release	2.4 mg/l (rat)		
Additional information:	The lists valid during the making were used as basis.		
Wash hands before breat Respiratory protection Hand protection The glove material has preparation. Selection of the glove m degradation Material of gloves Recommended thickness	 hygienic measures: measures are to be adhered to when handling chemicals. aks and at the end of work. Not necessary if room is well-ventilated. s to be impermeable and resistant to the product/ the substance/ t taterial on consideration of the penetration times, rates of diffusion and t s of the material: > 0,12 mm 		
(Permeation according to	ove material nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). oggles recommended during refilling		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go	nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). ggles recommended during refilling		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic	nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). oggles recommended during refilling cal and chemical properties		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic	nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). ggles recommended during refilling		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basis General Information	nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). oggles recommended during refilling cal and chemical properties		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi	hicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). Arggles recommended during refilling al and chemical properties ic physical and chemical properties Fluid According to product specification		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour:	nicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). Aggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour: Odour threshold:	hicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). hyggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic Not determined.		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing	ic physical and chemical properties Fluid According to product specification Characteristic Not determined. Fluid Fluid Characteristic Not determined.		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing p Boiling point or initial b	hicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). ggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic Not determined. point: boiling point and		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing p Boiling point or initial b boiling range	hicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). Inggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic Not determined. Did tetermined. Did tetermi		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing p Boiling point or initial b boiling range Flammability	hicals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). oggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic Not determined. boiling point and 2230 °C Not applicable.		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour threshold: Melting point/freezing p Boiling point or initial b boiling range Flammability Lower and upper explored	ic physical and chemical properties Fluid According to product specification Characteristic Not determined. Undetermined. Undetermined. Soliting point and 2230 °C Not applicable. Solition limit		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basis General Information Physical state Colour: Odour threshold: Melting point/freezing p Boiling point or initial b boiling range Flammability Lower and upper explo	icals mentioned below the penetration time has to be at least 10 minut o EN 374 Part 3: Level 1). ggles recommended during refilling cal and chemical properties ic physical and chemical properties Fluid According to product specification Characteristic Not determined. Didetermined. Characteristic Not determined. Didetermine		
Penetration time of glo For the mixture of chem (Permeation according to Eye/face protection Go SECTION 9: Physic 9.1 Information on basi General Information Physical state Colour: Odour threshold: Melting point/freezing p Boiling point or initial b boiling range Flammability Lower and upper explored	ic physical and chemical properties Fluid According to product specification Characteristic Not determined. Undetermined. Undetermined. Soliting point and 2230 °C Not applicable. Solition limit		

EU -



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

	(Contd. of page
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for th
	mixture. All non-determined data are no
	measurable or not relevant for th
_	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	— • • • • • • • • • • • • • • • • • • •
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	94.4 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Explosives Flammable gases	Void
Explosives Flammable gases Aerosols	Void Void
Explosives Flammable gases Aerosols Oxidising gases	Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids	Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit	Void Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Void Void Void Void Void Void
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void Void Void Void



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

(Contd. of page 5)

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.
- · Additional information: During curing methanol (CAS 67-56-1) is produced.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification:			
ſ	1067-25-0	1067-25-0 trimethoxypropylsilane		
Γ	Oral	LD50	>5170 mg/kg (rat)	
			mg/kg (rabbit)	
	Inhalative	LC50/4 h	>22.2 mg/l (rat)	
	2768-02-7 trimethoxyvinylsilane			
_	<u> </u>			

6900 mg/kg (rot)

Orai	LD50	6899 mg/kg (rat)
	LD50	3158 mg/kg (rat)
Inhalative	LC50/4 h	16.8 mg/l (rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity
- Not applicable.
- Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.

(Contd. on page 7)

EU



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

(Contd. of page 6)

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number		
ADR/ADN, IMDG, IATA	not regulated	
	-	
ADN	not regulated	
14.2 UN proper shipping name		
ADR/ADN, ADN, IMDG, ĬATA	not regulated	
14.3 Transport hazard class(es)		
ADR/ADN, ADN, IMDG, IATA		
Class	not regulated	



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

(Contd. of page 7)
not regulated
Not applicable.
Not applicable.
g to Not applicable.
Not dangerous according to the above specifications.
not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

• Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.

(Contd. on page 9)



Printing date 12.08.2024

Version number 17 (replaces version 16)

Revision: 12.08.2024

Trade name: BTK WOOD MAX EXP POWER TP 100G*12 IT

(Contd. of page 8) H361f Suspected of damaging fertility. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. Department issuing SDS: PSRA · Contact: PSRA Date of previous version: 21.12.2021 · Version number of previous version: 16 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Repr. 2: Reproductive toxicity - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 ΕU