


36232 - UHU HART FB 125ML L347



- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

Fax: 0049-(0)7223-284-245

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

E-mail: sds@boltonadhesives.com

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labelling: methyl acetate
- n-butyl acetate
- Hazard statements H225 Highly flammable liquid and vapour.

(Contd. on page 2)



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition
- sources. No smoking.
- Avoid breathing vapours. P261

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501

- Dispose of contents/container in accordance with national regulations.
- · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:

[•] Dangerous components:		
CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX	methyl acetate Flam. Liq. 2, H225;	50-100%
CAS: 9004-70-0 EC number: 682-719-5	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29- XXXX	n-butyl acetate	2.5-10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

• After eye contact:

(Contd. of page 2)

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

(Contd. of page 3)

Trade name: UHU HART FB 125ML L347

· Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 79-20-9 methyl acetate OEL (Ireland) Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm 123-86-4 n-butyl acetate OEL (Ireland) Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm **IOELV** IOELV (EU) Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm 79-20-9 methyl acetate Oral Consumer, oral, longterm exposition 21.5 mg/kg bw/day Dermal Worker, dermal, longterm exposition 43 mg/kg bw/day Consumer, dermal, shortterm exposition 203 mg/kg bw/day Consumer, dermal, longterm exposition 21.5 mg/kg bw/day Inhalative Worker, inhalative, shortterm exposition 3777 mg/m³ Worker, inhalative, longterm exposition 300 mg/m³ Consumer DNEL, acute inhalation 3777 mg/m³ Consumer, inhalative, longterm exposition 64 mg/m³ 123-86-4 n-butyl acetate Oral Consumer, oral, longterm exposition 3.4 mg/kg bw/day Dermal Consumer, dermal, longterm exposition 3.4 mg/kg bw/day Inhalative Consumer, inhalative, longterm exposition 102.34 mg/m³ **PNECs** 79-20-9 methyl acetate Oral Secondary Poisoning 20.4 mg/kg Fresh water 0.12 mg/l Fresh water sediment 0.128 mg/kg dry weight Marine water 0.012 mg/l Marine sediment 0.013 mg/kg dry weight Soil 0.0416 mg/kg Sewage treatment plant 600 mg/l 123-86-4 n-butyl acetate Fresh water 0.18 mg/l Marine water 0.018 mg/l (Contd. on page 5)



Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

Soil	0.0903 mg/kg
	ion: The lists valid during the making were used as basis.
8.2 Exposure control	
	ering controls No further data; see section 7.
	n measures, such as personal protective equipment
	and hygienic measures:
	hary measures are to be adhered to when handling chemicals.
	dstuffs, beverages and feed.
	all soiled and contaminated clothing preaks and at the end of work.
Do not inhale gases	
Avoid contact with th	
Avoid contact with th	
Respiratory protect	
Hand protection	
	has to be impermeable and resistant to the product/ the substance/ t
preparation.	
	e material on consideration of the penetration times, rates of diffusion and t
degradation	
Material of gloves	
	ness of the material: > 0,12 mm
Nitrile rubber, NBR	
Penetration time of	
	nemicals mentioned below the penetration time has to be at least 10 minu
	ng to EN 374 Part 3: Level 1).
Eye/face protection	
Tightly sea	aled goggles
Tightly sea	aled goggles
Goggles recommend	
Goggles recommend	led during refilling
Goggles recommend	led during refilling rsical and chemical properties
Goggles recommend SECTION 9: Phy 9.1 Information on b	led during refilling rsical and chemical properties basic physical and chemical properties
Goggles recommend SECTION 9: Phy 9.1 Information on b General Information	led during refilling rsical and chemical properties basic physical and chemical properties
Goggles recommend SECTION 9: Phy 9.1 Information on b General Information Physical state	led during refilling rsical and chemical properties basic physical and chemical properties
Goggles recommend SECTION 9: Phy 9.1 Information on b General Information Physical state Colour:	led during refilling rsical and chemical properties basic physical and chemical properties T Fluid Colourless
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour:	led during refilling rsical and chemical properties basic physical and chemical properties n Fluid Colourless Ester-like
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour: Odour: Odour threshold:	led during refilling rsical and chemical properties basic physical and chemical properties T Fluid Colourless Ester-like Not determined.
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour: Odour: Odour threshold: Melting point/freezi	led during refilling rsical and chemical properties basic physical and chemical properties T Fluid Colourless Ester-like Not determined. Undetermined.
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour: Odour: Odour threshold: Melting point/freezi Boiling point or init	led during refilling rsical and chemical properties basic physical and chemical properties n Fluid Colourless Ester-like Not determined. In In In In In In In In In In
Goggles recommend SECTION 9: Phy 9.1 Information on b General Information Physical state Colour: Odour: Odour threshold: Melting point/freezi Boiling point or init boiling range	led during refilling rsical and chemical properties basic physical and chemical properties n Fluid Colourless Ester-like Not determined. undetermined. ial boiling point and 57 °C
Goggles recommend SECTION 9: Phy 9.1 Information on b General Information Physical state Colour: Odour threshold: Melting point/freezi Boiling point or init boiling range Flammability	led during refilling rsical and chemical properties pasic physical and chemical properties n Fluid Colourless Ester-like Not determined. Indetermined. ial boiling point and 57 °C Highly flammable.
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour: Odour threshold: Melting point/freezi Boiling point or init boiling range Flammability Lower and upper ex	led during refilling rsical and chemical properties basic physical and chemical properties n Fluid Colourless Ester-like Not determined. ial boiling point and 57 °C Highly flammable. kplosion limit
Goggles recommend SECTION 9: Phy 9.1 Information on to General Information Physical state Colour: Odour: Odour threshold: Melting point/freezi Boiling point or init boiling range Flammability Lower and upper ex Lower:	led during refilling rsical and chemical properties basic physical and chemical properties n Fluid Colourless Ester-like Not determined. Ing point: ial boiling point and 57 °C Highly flammable. splosion limit 3.1 Vol %
Goggles recommend SECTION 9: Phy 9.1 Information on the General Information Physical state Colour: Odour: Odour: Odour threshold: Melting point/freezin Boiling point or inithe boiling range Flammability Lower and upper experted.	led during refilling rsical and chemical properties basic physical and chemical properties h Fluid Colourless Ester-like Not determined. ial boiling point and 57 °C Highly flammable. kplosion limit



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

	(Contd. of page
Auto-ignition temperature:	180 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	9000 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	220 hPa
Vapour pressure at 50 °C:	800 hPa
Density and/or relative density	
Density at 20 °C:	1.115 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are no
	measurable or not relevant for the
	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of health	1
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	68.7 %
VOC (EC)	68.72 %
Solids content:	31.3 %
Change in condition	
Evaporation rate	Not determined.
•	1
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
	N / . ! . I
Self-reactive substances and mixtures	Void
Self-reactive substances and mixtures Pyrophoric liquids	Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit	Void Void Void



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

	(Contd. of page 6)
Void	
Void	
Void	
Void	
	Void Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification: 79-20-9 wethyl acetate Oral LD50 3705 mg/kg (rabbit) 123-86-4 n-butyl acetate Oral LD50 13100 mg/kg (rat) Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/4 h >21 mg/l (rat) · Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation	
Oral LD50 3705 mg/kg (rabbit) 123-86-4 n-butyl acetate Oral LD50 13100 mg/kg (rat) Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/4 h >21 mg/l (rat) · Skin corrosion/irritation Based on available data, the classification criteria are not met.	
123-86-4 n-butyl acetate Oral LD50 13100 mg/kg (rat) Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/4 h >21 mg/l (rat) • Skin corrosion/irritation Based on available data, the classification criteria are not met.	
Oral LD50 13100 mg/kg (rat) Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/4 h >21 mg/l (rat) Skin corrosion/irritation Based on available data, the classification criteria are not met.	
Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/4 h >21 mg/l (rat) • Skin corrosion/irritation Based on available data, the classification criteria are not met.	
Inhalative LC50/4 h >21 mg/l (rat) • Skin corrosion/irritation Based on available data, the classification criteria are not met.	
• Skin corrosion/irritation Based on available data, the classification criteria are not met.	
 Causes serious eye irritation. Respiratory or skin sensitisation Based on available data, the classification criteria are not Germ cell mutagenicity Not applicable. Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met. Additional toxicological information: Acute effects (acute toxicity, irritation and corrosivity) Not applicable. Sensitisation Not applicable. (Contd. on 	



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

(Contd. of page 7)

Trade name: UHU HART FB 125ML L347

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	ltion
· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	UN1133
 14.2 UN proper shipping name ADR/ADN 	1133 ADHESIVES, special provision 640D
· IMDG, IATA	ADHESIVES



Printing date 01.08.2024 Version number 13 (replaces version 12) Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

	(Contd. of page 8
 14.3 Transport hazard class(es) 	
· ADR/ADN	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	11
14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code) EMS Number: Stowage Category 	Warning: Flammable liquids. : 33 F-E,S-D E
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	(Contd. on page 1



Printing date 01.08.2024

· Remarks:

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

(Contd. of page 9)

For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).

· UN "Model Regulation":

UN 1133 ADHESIVES, 3, II

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $50000\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

• Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 11)



Printing date 01.08.2024

Version number 13 (replaces version 12)

Revision: 01.08.2024

Trade name: UHU HART FB 125ML L347

Flammable liquids	Bridging principles
Serious eye damage/irritation Specific target organ toxicity (single exposure)	The classification of the mixture is generally base on the calculation method using substance da according to Regulation (EC) No 1272/2008.
Department issuing SDS: PSRA Contact: PSRA Date of previous version: 25.10.2022 Version number of previous version: 12 Abbreviations and acronyms: ADR: Accord relatif au transport international des marcha the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and La EINECS: European Inventory of Existing Commercial Cher ELINCS: European Inventory of Existing Commercial Cher ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the Americar VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal dose, 50 percent D50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure	mical Substances n Chemical Society)