

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com
- **Further information obtainable from:** PSRA
- **1.4 Emergency telephone number:**
National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)
Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

(Contd. on page 2)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 1)

· **Hazard statements**

H226 Flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



GHS02 GHS05

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe dust.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P501 Dispose of contents/container in accordance with national regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

· **Determination of endocrine-disrupting properties**

78-93-3 Butanone

List II

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Cleansing agent

· **Dangerous components:**

EC number: 918-167-1 Reg.nr.: 01-2119472146-39-XXXX	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	50-100%
CAS: 85536-14-7 EINECS: 287-494-3 Reg.nr.: 01-2119490234-40-XXXX	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives ⚠ Skin Corr. 1A, H314; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; ⚠ Aquatic Chronic 3, H412	≥10-<25%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<1%
EC number: 939-290-7 Reg.nr.: 01-2119970169-28	Quaternary ammonium compounds, benzyl-C16-18 (even numbered)-alkyldimethyl, chlorides ⚠ Skin Corr. 1B, H314; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); ⚠ Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302	≥0.25-<1%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-XXXX	Butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<1%

· **Regulation (EC) No 648/2004 on detergents / Labelling for contents**

aliphatic hydrocarbons	≥30%
ISOPROPYL ALCOHOL	<5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Call a doctor immediately.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - Water haze
 - Alcohol resistant foam
 - Fire-extinguishing powder
 - Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Mount respiratory protective device.
 - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Send for recovery or disposal in suitable receptacles.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Use neutralising agent.
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 5)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 4)

- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol

OEL (Ireland)	Short-term value: 400 ppm Long-term value: 200 ppm Skin
---------------	---

78-93-3 Butanone

OEL (Ireland)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Skin, IOELV
IOELV (EU)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm

· **DNELs**

85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

Oral	Consumer, oral, longterm exposition	0.425 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	85 mg/kg bw/day
	Consumer, dermal, longterm exposition	42.5 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	6 mg/m ³
	Consumer, inhalative, longterm exposition	1.5 mg/m ³

67-63-0 propan-2-ol

Oral	Consumer, oral, longterm exposition	26 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	888 mg/kg bw/day
	Consumer, dermal, longterm exposition	319 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	500 mg/m ³
	Consumer, inhalative, longterm exposition	89 mg/m ³

78-93-3 Butanone

Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	1161 mg/kg bw/day
	Consumer, dermal, longterm exposition	412 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	900 mg/m ³
	Worker, inhalative, longterm exposition	600 mg/m ³
	Consumer DNEL, acute inhalation	450 mg/m ³
	Consumer, inhalative, longterm exposition	106 mg/m ³

· **PNECs**

85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

Fresh water	0.268 mg/l
-------------	------------

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 5)

Fresh water sediment	8.1 mg/kg dry weight
Marine water	0.027 mg/l
Marine sediment	6.8 mg/kg dry weight
Soil	35 mg/kg
Sewage treatment plant	3.43 mg/l
Sporadic release	0.017 mg/l

67-63-0 propan-2-ol

Oral	Secondary Poisoning	160 mg/kg
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg dry weight
	Marine water	140.9 mg/l
	Marine sediment	552 mg/kg dry weight
	Soil	28 mg/kg
	Sewage treatment plant	2251 mg/l
	Sporadic release	140.9 mg/l

78-93-3 Butanone

Oral	Secondary Poisoning	1000 mg/kg
	Fresh water	55.8 mg/l
	Fresh water sediment	284.7 mg/kg dry weight
	Marine water	55.8 mg/l
	Marine sediment	284.7 mg/kg dry weight
	Soil	22.5 mg/kg
	Sewage treatment plant	709 mg/l
	Sporadic release	55.8 mg/l

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

· **Recommended filter device for short term use:** Filter A

· **Hand protection**

Solvent resistant gloves

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 6)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

- **Body protection:** Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

· Physical state	Fluid
· Colour:	Brown
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	-25 °C
· Boiling point or initial boiling point and boiling range	36 °C
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	0.7 Vol %
· Upper:	6.5 Vol %
· Flash point:	≤60 °C
· Auto-ignition temperature:	~310 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	140000 mPas
· Solubility	
· water at 20 °C:	0.04 g/l
· Partition coefficient n-octanol/water (log value)	Not determined.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 7)

· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	~0.81 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information** All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	0.9 %
· VOC (EC)	80.61 %
· Solids content:	5.7 %
· Change in condition	
· Evaporation rate	Not determined.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 8)

- **10.3 Possibility of hazardous reactions** Corrosive action on metals.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)
Inhalative	LC50/4 h	>5000 mg/l (rat)

85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

Oral	LD50	>300-2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

78-93-3 Butanone

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>8050 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**
Not applicable.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 9)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3 Butanone

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packaging:**

· **Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR/ADN, IMDG, IATA**

UN2924

· **14.2 UN proper shipping name**

· **ADR/ADN**

2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL))

· **IMDG, IATA**

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives, ISOPROPANOL (ISOPROPYL ALCOHOL))

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 10)

· **14.3 Transport hazard class(es)**

· **ADR/ADN**



· **Class** 3 (FC) Flammable liquids.
 · **Label** 3+8

· **IMDG**



· **Class** 3 Flammable liquids.
 · **Label** 3/8

· **IATA**



· **Class** 3 Flammable liquids.
 · **Label** 3 (8)

· **14.4 Packing group**

· **ADR/ADN, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.
 · **Hazard identification number (Kemler code):** 38
 · **EMS Number:** F-E,S-C
 · **Segregation groups** (SGG1) Acids
 · **Stowage Category** A
 · **Stowage Code** SW2 Clear of living quarters.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **ADR/ADN**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 11)

<ul style="list-style-type: none"> · Transport category · Tunnel restriction code <hr style="border-top: 1px dashed black;"/> <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) <ul style="list-style-type: none"> · Remarks: 	<p style="text-align: center;">3</p> <p style="text-align: center;">D/E</p> <p style="text-align: center;">5L</p> <p style="text-align: center;">Code: E1</p> <p style="text-align: center;">Maximum net quantity per inner packaging: 30 ml</p> <p style="text-align: center;">Maximum net quantity per outer packaging: 1000 ml</p> <p>For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL)), 3 (8), III</p>

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

78-93-3	Butanone	3
7664-93-9	sulphuric acid	3

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

78-93-3	Butanone	3
7664-93-9	sulphuric acid	3

(Contd. on page 13)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 12)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** PSRA

- **Contact:** PSRA

- **Date of previous version:** 24.01.2022

- **Version number of previous version:** 36

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1A: Skin corrosion/irritation – Category 1A
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 14)

IE



Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025

Version number 37 (replaces version 36)

Revision: 22.03.2025

Trade name: GRF SEALANT REMOVER BO 250ML*6 L221

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 13)

IE