

62266 - UHU AP POWER TR FB 45ML*10 L584

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

Trade name: UHU AP POWER TR FB 45ML*10 L584

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7

D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number: Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labelling: acetone
- ethyl acetate
- Hazard statements
- H225 Highly flammable liquid and vapour.

(Contd. on page 2)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

Trade name: UHU AP POWER TR FB 45ML*10 L584

(Contd. of page 1) H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. P261 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with national regulations. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9. · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone	50-100%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: No special measures required.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

(Contd. of page 2)

Trade name: UHU AP POWER TR FB 45ML*10 L584

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

(Contd. on page 4)

IE-EN



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

(Contd. of page 3)

Trade name: UHU AP POWER TR FB 45ML*10 L584

• 7.3 Specific end use(s) No further relevant information available.

67-64-1 ace	-					
	Ingredients with limit values that require monitoring at the workplace: 67-64-1 acetone					
,	OEL (Ireland) Long-term value: 1210 mg/m ³ , 500 ppm					
	IOELV					
. ,	IOELV (EU) Long-term value: 1210 mg/m ³ , 500 ppm					
141-78-6 et	-					
OEL (Irelan	d) Short-term value: 1468 mg/m³, 400 ppn Long-term value: 734 mg/m³, 200 ppm	n				
	IOELV					
IOELV (EU)	Short-term value: 1468 mg/m³, 400 ppn Long-term value: 734 mg/m³, 200 ppm	n				
· DNELs						
67-64-1 ace						
	Consumer, oral, longterm exposition	62 mg/kg bw/day				
	Consumer, dermal, longterm exposition	62 mg/kg bw/day				
	Consumer, inhalation, longterm exposition	200 mg/m³				
141-78-6 et	-					
	Consumer, oral, longterm exposition	4.5 mg/kg bw/day				
	Consumer, dermal, longterm exposition	37 mg/kg bw/day				
	Consumer DNEL, acute inhalation	734 mg/m ³				
	Consumer, inhalation, longterm exposition	367 mg/m³				
PNECs	-					
67-64-1 ace						
Fresh water	0					
	er 1.06 mg/l					
Soil 29.5 mg/kg						
141-78-6 ethyl acetate Fresh water 0.26 mg/l						
Marine wate						
Soil	0.22 mg/kg					
	information: The lists valid during the mal	king were used as basis				
• 8.2 Exposu • Appropriat • Individual • General pro The usual p	-	ee item 7. protective equipment				

(Contd. on page 5)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

Trade name: UHU AP POWER TR FB 45ML*10 L584

(Contd. of page 4) Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes. Avoid contact with the eyes and skin. · Respiratory protection: Not required. Hand protection The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR · Penetration time of glove material For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1). Eye/face protection Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chem General Information 	ical properties
· Physical state	Fluid
· Colour:	According to product specification
	Characteristic
Odour threshold:	
	Not determined.
Melting point/freezing point:	Undetermined.
 Boiling point or initial boiling point and 	
boiling range	55.8-56.6 °C
· Flammability	Highly flammable.
• Lower and upper explosion limit	
· Lower:	2.1 Vol %
· Upper:	13 Vol %
Flash point:	-19 °C
Ignition temperature:	460 °C
Decomposition temperature:	Not determined.
·pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	8000 mPas
Solubility	
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	Not misciple of amount to mix.
value)	Not determined.
valuej	
	(Contd. on page 6)
	IE-EN -



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

Trade name: UHU AP POWER TR FB 45ML*10 L584

	(Contd. of page
Vapour pressure at 20 °C:	233 hPa
Density and/or relative density	
Density at 20 °C:	0.897 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are n measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	llth
and environment, and on safety.	Due durat is wat a slfi waitin w
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
Colvert content:	explosive air/vapour mixtures are possible.
Solvent content:	70.0.0/
Organic solvents:	78.8 %
VOC (EC)	78.77 %
Solids content:	21.2 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

(Contd. on page 7)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

(Contd. of page 6)

Trade name: UHU AP POWER TR FB 45ML*10 L584

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

141-78-6 ethyl acetate

Oral LD50 5620 mg/kg (rabbit)

Inhalative LC50/4 h 1600 mg/l (rat)

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

- Additional toxicological information:
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- \cdot 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

(Contd. of page 7)

Trade name: UHU AP POWER TR FB 45ML*10 L584

· 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

 14.1 UN number or ID number ADR/ADN, IMDG, IATA 	UN1133	
· 14.2 UN proper shipping name · ADR/ADN · IMDG, IATA	1133 ADHESIVES ADHESIVES	
14.3 Transport hazard class(es)		
ADR/ADN		
Class	3 (F1) Flammable liquids.	
Label IMDG, IATA	3	
Class	3 Flammable liquids.	
Label	3	



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

Trade name: UHU AP POWER TR FB 45ML*10 L584

	(Contd. of page 8
 14.4 Packing group ADR/ADN, IMDG, IATA 	Ш
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler con EMS Number: Stowage Category 	Warning: Flammable liquids. de): - F-E,S-D A
 14.7 Maritime transport in bulk according IMO instruments 	y to Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
 Transport category Tunnel restriction code 	S E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 10)



Printing date 22.11.2023

Version number 9 (replaces version 8)

Revision: 06.05.2023

(Contd. of page 9)

3

3

Trade name: UHU AP POWER TR FB 45ML*10 L584

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

•	Bridging principles
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data
	according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: UHU QESH
- · Contact: UHU QESH
- Date of previous version: 27.10.2022
- · Version number of previous version: 8
- Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent
- LC50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- ** Data compared to the previous version altered.