

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BIS CONTACT KIT TI 4.5L*2 L161
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

· IF

www.bison.net 1/16



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02 GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Acetone

Butanone

- · Hazard statements
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361d Suspected of damaging the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

· Additional information:

EUH208 Contains Rosin. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

· IF

www.bison.net 2/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

· vPvB: Not applicable.

(Contd. of page 2)

Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

Description: Adnesive		
· Dangerous components:		
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 Reg.nr.: 01-2119471310-51- XXXX	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33- XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone Flam. Liq. 2, H225; Lye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 25085-50-1 EC number: 607-533-3	p-tert-butylphenol formaldehyde resin Skin Sens. 1, H317	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0 Reg.nr.: Exempt	Magnesium oxide substance with a Community workplace exposure limit	1-2.5%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32- XXXX	Rosin Skin Sens. 1, H317	≥0.1-<1%

(Contd. on page 4)

10

www.bison.net 3/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

		(Contd. of page 3)
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41- XXXX	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32- XXXX	Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 5)

www.bison.net 4/16

IE -



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 4)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

OEL (Ireland) Short-term value: 384 mg/m³, 100 ppm

Long-term value: 192 mg/m³, 50 ppm

Skin, IOELV

(Contd. on page 6)

- IF

www.bison.net 5/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

IOELV//EI	1) Chart tarm value: 204 mg/m³ 400 nnm		(Contd. of pa
IOELV (EU) Short-term value: 384 mg/m³, 100 ppm Long-term value: 192 mg/m³, 50 ppm			
Skin			
67-64-1 A	cetone		
OEL (Irela	nd) Long-term value: 1210 mg/m³, 500 ppn IOELV	1	
IOELV (EU	J) Long-term value: 1210 mg/m³, 500 ppn	1	
78-93-3 B	utanone		
·	nd) Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Skin, IOELV		
IOELV (EU	 Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm 		
	Magnesium oxide		
OEL (Irela	nd) Short-term value: 10** mg/m³ Long-term value: 4* 5** 10*** mg/m³ *respirable dust **fume ***total inhalab	e dust	
	cyclohexane		
OEL (Irela	nd) Long-term value: 700 mg/m³, 200 ppm IOELV		
IOELV (EU	J) Long-term value: 700 mg/m³, 200 ppm		
DNELs			
108-88-3 t	oluene		
Oral	Consumer, oral, longterm exposition	8.13 mg/kg bw/day	
Dermal	Worker, dermal, longterm exposition	384 mg/kg bw/day	
	Consumer, dermal, longterm exposition	226 mg/kg bw/day	
Inhalative	Worker, inhalative, shortterm exposition	384 mg/m³	
	Worker, inhalative, longterm exposition	192 mg/m³	
	Consumer DNEL, acute inhalation	226 mg/m³	
	Consumer, inhalative, longterm exposition	56.5 mg/m³	
Hydrocarl	oons, C7, n-alkanes, isoalkanes, cyclics		
Oral	Consumer, oral, longterm exposition	149 mg/kg bw/day (rat)	
Dermal	Worker, dermal, longterm exposition	300 mg/kg bw/day (rat)	
	Consumer, dermal, longterm exposition	149 mg/kg bw/day (rat)	
Inhalative	Worker, inhalative, longterm exposition	2085 mg/m³ (rat)	
	Consumer, inhalative, longterm exposition	477 mg/m³ (rat)	
67-64-1 A	cetone		
Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day	
Dermal	Worker, dermal, longterm exposition	186 mg/kg bw/day	
	Consumer, dermal, longterm exposition	62 mg/kg bw/day	
Inhalative	Worker, inhalative, shortterm exposition	2420 mg/m³	
IIIIIalalive	· · · · · · · · · · · · · · · · · · ·		

www.bison.net 6/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

	Concumer inheleti	us langtorm sympaities	200 mg/m³	(Contd. of pa	
70.00		ve, longterm exposition	ZUU mg/m³		
	Butanone				
Oral	Consumer, oral, lor	•	31 mg/kg bw/day		
Dermal	, ,	•	1161 mg/kg bw/day		
		longterm exposition	412 mg/kg bw/day		
Inhalati	ve Worker, inhalative,	•	600 mg/m³		
		ve, longterm exposition	106 mg/m³		
	-7 cyclohexane				
Oral	Consumer, oral, lor	•	59.4 mg/kg bw/day (rat)		
Dermal		•	2016 mg/kg bw/day (rat)		
	Consumer, dermal,	longterm exposition	1186 mg/kg bw/day (rat)		
Inhalati	ve Worker, inhalative,	shortterm exposition	700 mg/m³ (rat)		
	Worker, inhalative,	longterm exposition	700 mg/m³ (rat)		
	Consumer DNEL, a	acute inhalation	412 mg/m³ (rat)		
	Consumer, inhalati	ve, longterm exposition	206 mg/m³ (rat)		
PNECs	·				
108-88	-3 toluene				
Fı	esh water	0.68 mg/l			
Fı	esh water sediment	16.39 mg/kg dry weight			
М	arine water	0.68 mg/l			
Marine sediment Soil Sewage treatment plant Sporadic release		16.39 mg/kg dry weigh	16.39 mg/kg dry weight		
		2.89 mg/kg			
		0.68 mg/l			
67-64-1	Acetone	J			
Fı	esh water	10.6 mg/l			
Fı	esh water sediment	30.4 mg/kg dry weight			
М	arine water	1.06 mg/l			
М	arine sediment	3.04 mg/kg dry weight			
S	oil	29.5 mg/kg			
	ewage treatment plant				
	poradic release	21 mg/l			
	Butanone	<u> </u>			
Oral S	econdary Poisoning	1000 mg/kg			
Fı	esh water	55.8 mg/l			
Fı	esh water sediment	284.7 mg/kg dry weigh	t		
М	arine water	55.8 mg/l			
	arine sediment	284.7 mg/kg dry weigh	t		
	oil	22.5 mg/kg			
	ewage treatment plant	5			
	poradic release	55.8 mg/l			

www.bison.net 7/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

	(Contd. of page 7				
110-82-7 cyclohexane	110-82-7 cyclohexane				
Fresh water	0.207 mg/l (rat)				
Fresh water sediment	3.627 mg/kg dry weight (rat)				
Marine water	0.207 mg/l (rat)				
Marine sediment	3.627 mg/kg dry weight (rat)				
Soil	2.99 mg/kg (rat)				
Sewage treatment plant	3.24 mg/l (rat)				
1314-13-2 Zinc oxide					
Fresh water	0.0144 mg/l				
Fresh water sediment	146.9 mg/kg dry weight				
Marine water	0.0072 mg/l				
Marine sediment	162.2 mg/kg dry weight				
Soil	83.1 mg/kg				
Sewage treatment plant	0.1 mg/l				

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0.7 mm

(Contd. on page 9)

- IE

www.bison.net 8/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 24.07.2024 Version number 42 (replaces version 41) Printing date 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 8)

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection:

Use protective suit.

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification · Odour: Characteristic

Not determined. · Odour threshold: Undetermined.

• Melting point/freezing point:

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C Highly flammable. **Flammability**

· Lower and upper explosion limit

0.7 Vol % · Lower: 13 Vol % · Upper: -1 °C · Flash point:

450 °C · Auto-ignition temperature:

 Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

Kinematic viscosity Not determined. · Dynamic at 20 °C: 2500 mPas

Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure at 20 °C: 233 hPa Vapour pressure at 50 °C: 800 hPa

Density and/or relative density

Density at 20 °C: 0.952 g/cm³ Not determined. Relative density

(Contd. on page 10)

9/16 www.bison.net



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

	(Contd. of page
· Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature: Explosive properties:	Product is not selfigniting. Product is not explosive. However, formation explosive air/vapour mixtures are possible.
Solvent content:	·
· Organic solvents:	78.8 %
· Water:	0.2 %
· VOC (EC)	78.78 %
Solids content:	20.8 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
Explosives	Void
Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 11)

'/

www.bison.net 10/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 10)

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

	LD/LC50 values relevant for classification:					
	108-88-3 toluene					
	Oral	LD50	5580 mg/kg (rat)			
	Dermal LD50		>5000 mg/kg (rabbit)			
	Inhalative	LC50/4 h	25.7 mg/l (rat)			
	Hydrocarl	oons, C7,	n-alkanes, isoalkanes, cyclics			
	Oral	LD50	>5840 mg/kg (rat)			
	Dermal	LD50	>2920 mg/kg (rat)			
	Inhalative	LC50/4 h	>23.3 mg/l (rat)			
	67-64-1 A	cetone				
	Oral	LD50	5800 mg/kg (rat)			
	Dermal	LD50	>15800 mg/kg (rat)			
	Inhalative	LC50/4 h	76 mg/l (rat)			
	25085-50-1 p-tert-butylphenol formaldehyde resin					
	Oral	LD50	>2000 mg/kg (rat)			
	Dermal	LD50	>2000 mg/kg (rat)			
	78-93-3 Butanone					
	Oral	LD50	>2193 mg/kg (rat)			
	Dermal	LD50	>8050 mg/kg (rat)			
	1309-48-4	Magnesi				
	Oral	LD50	3870 mg/kg			
	8050-09-7	Rosin				
	Oral	LD50	2800 mg/kg (rat)			
	Dermal	LD50	>2000 mg/kg (rat)			
	110-82-7 cyclohexane					
	Oral	LD50	12705 mg/kg (rat)			
	1314-13-2					
	Oral	LD50	>5000 mg/kg (rat)			
L	Dermal	LD50	>2000 mg/kg (rat)			
	. Skin corre		(*			

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

(Contd. on page 12)

IE ·

www.bison.net 11/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 11)

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Suspected of damaging the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrine disrupting properties		
78-93-3	Butanone	List II
98-54-4	4-tert-butylphenol	List I; II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 13)

- IE

www.bison.net 12/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 12)

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids. 3
IMDG	3
	0.51
Class Label	3 Flammable liquids. 3
IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code EMS Number: Stowage Category	e): - F-E,S-D A

www.bison.net 13/16



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

. 44.7 Mouttime transport in bull, according	(Contd. of page
14.7 Maritime transport in bulk according IMO instruments	Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100
· Transport category · Tunnel restriction code	ml 3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml For substances with class 3 according to IMD0 Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance.
· UN "Model Regulation":	with requirements (flow time t > 100s). U N

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48, 57
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene 3

(Contd. on page 15)

www.bison.net 14/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

		f page 14)
67-64-1	Acetone	3
78-93-3	Butanone	3
	on (EC) No 111/2005 laying down rules for the monitoring of trade betw iity and third countries in drug precursors	een the
108-88-3	toluene	3
67-64-1	Acetone	3
78-93-3	Butanone	3
· 15.2 Che	mical safety assessment: A Chemical Safety Assessment has not been carried	out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225	Highly	flammable	liquid	and	vapour.
------	--------	-----------	--------	-----	---------

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

٠.		
	Flammable liquids	Bridging principles
•	Skin corrosion/irritation Serious eye damage/irritation Reproductive toxicity Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
	Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - longterm (chronic) aquatic hazard	

· Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 31.05.2021
Version number of previous version: 41

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 16)

-) -IF

www.bison.net 15/16



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.07.2024 Version number 42 (replaces version 41) Revision: 24.07.2024

Trade name: BIS CONTACT KIT TI 4.5L*2 L161

(Contd. of page 15)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 1: Hazardous to the approximate environment – acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

16/16 www.bison.net