

Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

• Trade name: BIS CONTACT KIT TI 650ML*12 L162

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9

NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:


National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

👏 💙 GHS02 flame



H225 Highly flammable liquid and vapour.

GHS08 health hazard

Repr. 2

H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07			
Skin Irrit. 2	H315	Causes skin irritation.	
Eye Irrit. 2	H319	Causes serious eye irritation.	
STOT SE 3	H336	May cause drowsiness or dizziness.	
			(Contd. on page 2)



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

(Contd. of page 1) · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: toluene Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics acetone butanone Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H361d Suspected of damaging the unborn child. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. **Precautionary statements** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash hands thoroughly after handling. P264 Use only outdoors or in a well-ventilated area. P271 P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. Specific treatment (see on this label). P321 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. P362+P364 P332+P313 If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. P337+P313 P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH208 Contains Rosin. May produce an allergic reaction. · 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable.



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

(Contd. of page 2)

List II

Trade name: BIS CONTACT KIT TI 650ML*12 L162

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 butanone

3.2 Mixtures Description: Adhesive		
Dangerous components:		
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 Reg.nr.: 01-2119471310-51	toluene	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ↑ Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225;	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225;	≥2.5-<10%
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0 Reg.nr.: Exempt	magnesium oxide substance with a Community workplace exposure limit	1-2.5%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32	Rosin	≥0.1-<1%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41	cyclohexane	≥0.25-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

(Contd. on page 4)

IE



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

(Contd. of page 3)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- **Protective equipment:** Mouth respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. (Contd. on page 5)

IF



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

(Contd. of page 4)

Trade name: BIS CONTACT KIT TI 650ML*12 L162

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
108-88-3 tolu	108-88-3 toluene		
OEL (Ireland)	Short-term value: 384 mg/m³, 100 ppm Long-term value: 192 mg/m³, 50 ppm Sk, IOELV		
IOELV (EU)	Short-term value: 384 mg/m³, 100 ppm Long-term value: 192 mg/m³, 50 ppm Skin		
67-64-1 aceto	67-64-1 acetone		
OEL (Ireland)	Long-term value: 1210 mg/m³, 500 ppm IOELV		
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm		
78-93-3 butar	78-93-3 butanone		
OEL (Ireland)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, IOELV		
<u> </u>		(Contd. on page 6)	



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

			(Contd. of page 5)	
IOELV (El	J)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm		
1309-48-4	ma	gnesium oxide		
		Short-term value: 10** mg/m ³		
• == (•.•.	,	Long-term value: 4* 5** 10*** mg/m ³		
*respirable dust **fume ***total inhalable dust			le dust	
110-82-7 (cycl	ohexane		
OEL (Irela	ınd)	Long-term value: 700 mg/m³, 200 ppm IOELV		
IOELV (El	J)	Long-term value: 700 mg/m³, 200 ppm		
· DNELs				
67-64-1 ad	ceto	ne		
Oral	Cor	nsumer, oral, longterm exposition	62 mg/kg bw/day	
Dermal	Cor	nsumer, dermal, longterm exposition	62 mg/kg bw/day	
Inhalative	Cor	nsumer, inhalative, longterm exposition	200 mg/m³	
78-93-3 bi	utan	one	-	
Oral	Cor	nsumer, oral, longterm exposition	31 mg/kg bw/day	
Dermal	Cor	nsumer, dermal, longterm exposition	412 mg/kg bw/day	
Inhalative	Cor	nsumer, inhalative, longterm exposition	106 mg/m ³	
· PNECs	<u> </u>			
67-64-1 ad	ceto	ne		
Fresh wate	er	10.6 mg/l		
Marine wa	ater	1.06 mg/l		
Soil		29.5 mg/kg		
78-93-3 bi	utan	one		
Fresh wate	er	55.8 mg/l		
Marine wa	ater	55.8 mg/l		
Soil		22.5 mg/kg		
Individual General p The usual Keep awa Immediate Wash han	ate e l pro prote prec y fro ely re ds b ectiv	engineering controls No further data; so tection measures, such as personal ective and hygienic measures: cautionary measures are to be adhered m foodstuffs, beverages and feed. emove all soiled and contaminated cloth efore breaks and at the end of work. re clothing separately. with the eyes and skin.	protective equipment to when handling chemicals.	
Avoid cont Respirato In case of exposure of	b ry p brie use	f exposure or low pollution use respirat self-contained respiratory protective de		
Avoid cont Respirato In case of exposure of Use suitab	brie brie use ble re	f exposure or low pollution use respirat	vice.	



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

(Contd. of page 6)

Filter A
• Hand protection
Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Recommended thickness of the material: > 0,12 mm

- Butyl rubber, BR
- Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

- Body protection:
- Use protective suit.

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

General Information Physical state	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	t de la constant de la const
boiling range	55.8-56.6 °C
Flammability	Highly flammable.
Lower and upper explosion limit	
Lower:	0.7 Vol %
Upper:	13 Vol %
Flash point:	-1 °C
Auto-ignition temperature:	450 °C

(Contd. on page 8)



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

	(Contd. of page
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	2500 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	233 hPa
Vapour pressure at 50 °C:	800 hPa
Density and/or relative density	
Density at 20 °C:	0.952 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
• •	
9.2 Other information	All relevant physical data were determined for th
	mixture. All non-determined data are no
	measurable or not relevant for th
A	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	
and environment, and on safety.	Dreduct is not colfigniting
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
Solvent content:	explosive air/vapour mixtures are possible.
	79.0 %
Organic solvents: Water:	0.2 %
	20.8 %
Solids content:	20.0 %
Change in condition	Not determined.
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void

IE



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

		(Contd. of page 8)
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

	· Acute toxicity based on available data, the classification criteria are not met.		
· LD/LC50	· LD/LC50 values relevant for classification:		
108-88-3 t	108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	
67-64-1 ad	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	20000 mg/kg (rabbit)	
78-93-3 bi	78-93-3 butanone		
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	
110-82-7 (cyclohexa	ne	
Oral	Oral LD50 12705 mg/kg (rat)		
1314-13-2	1314-13-2 zinc oxide		
Oral	Oral LD50 >5000 mg/kg (rat)		
	Skin corrosion/irritation		
•	Causes skin irritation.		
	· Serious eye damage/irritation		
	Causes serious eye irritation. • Respiratory or skin sensitisation Based on available data, the classification criteria are not met.		
	· Germ cell mutagenicity		
	Not and high h		

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Suspected of damaging the unborn child.

(Contd. on page 10)



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

(Contd. of page 9)

List II

- STOT-single exposure May cause drowsiness or dizziness.
- \cdot STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 butanone

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 11)



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

(Contd. of page 10)

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
· Class · Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code) EMS Number:	: - F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml
Transport category Tunnel restriction code	3 E

IE



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

Trade name: BIS CONTACT KIT TI 650ML*12 L162

	(Contd. of page 11)
·IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000
	ml
Remarks:	Under certain conditions substances in Class 3
	(flammable liquids) can be classified in
	packinggroup III.
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III,
	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48, 57

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene

67-64-1 acetone

78-93-3 butanone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene

67-64-1 acetone

78-93-3 butanone

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. (Contd. on page 13)

ontd. on page 13)

3

3

3

3 3

3



Printing date 25.01.2024

Version number 41 (replaces version 40)

Revision: 25.01.2024

(Contd. of page 12)

Trade name: BIS CONTACT KIT TI 650ML*12 L162

· Relevant phrases

H225 Highly flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids Bridging principles Skin corrosion/irritation The classification of the mixture is generally Serious eye damage/irritation based on the calculation method using Reproductive toxicity substance data according to Regulation (EC) No Specific target organ toxicity (single exposure) 1272/2008. Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - longterm (chronic) aquatic hazard Department issuing SDS: Bison QESH **Contact:** Reach coordinator Date of previous version: 31.05.2021 · Version number of previous version: 40 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 ** Data compared to the previous version altered.