

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BIS SILICONE REMOVER BD 100ML*6 L192
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Hazard-determining components of labelling: Benzenesulfonic acid, 4-C10-13-sec-alkylderivs.

(Contd. on page 2)

ΪΕ •

www.bison.net 1/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS02 GHS05

· Signal word Danger

· Hazard-determining components of labelling:

Benzenesulfonic acid, 4-C10-13-sec-alkylderivs.

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Determination of endocrine-disrupting properties

78-93-3 butanone List II

(Contd. on page 3)

www.bison.net 2/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Cleansing agent

· Dangerous components:			
EC number: 918-167-1	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	50-100%	
Reg.nr.: 01-2119472146-39	🚸 Flam. Liq. 3, H226; 🕸 Asp. Tox. 1, H304, EUH066		
CAS: 85536-14-7 EINECS: 287-494-3 Reg.nr.: 01-2119490234-40	Benzenesulfonic acid, 4-C10-13-sec-alkylderivs. Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Aquatic Chronic 3, H412	≥10-<25%	
CAS: 61789-72-8 EINECS: 263-081-3 Reg.nr.: 01-2119970169-28	Quaternary ammonium compounds, benzyl-C14-18-alkyldimethyl, chlorides Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302	≥0.25-<1%	
CAS: 78-93-3	butanone	<1%	
EINECS: 201-159-0	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE		
Index number: 606-002-00-3	3, H336, EUH066		
Reg.nr.: 01-2119457290-43			
Regulation (EC) No 648/2004 on detergents / Labelling for contents			

· Regulation (EC) No 648/2004 on detergents / Labelling for contents		
aliphatic hydrocarbons	≥30%	
anionic surfactants	≥5 - <15%	
cationic surfactants, ISOPROPYL ALCOHOL	<5%	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Call a doctor immediately.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- \cdot After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

(Contd. on page 4)

IE -

www.bison.net 3/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 3)

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

 During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

www.bison.net 4/12

IE -



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-93-3 butanone

OEL (Ireland) Short-term value: 900 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, IOELV

IOELV (EU) Short-term value: 900 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

· DNELs

78-93-3 butanone

Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day
Inhalative	Consumer inhalative longterm exposition	106 mg/m³

- PNECs

78-93-3 butanone

Fresh water	55.8 mg/l
Marine water	55.8 mg/l
Soil	22.5 mg/kg

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter A
- · Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

(Contd. on page 6)

www.bison.net 5/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 5)

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Brown

Odour: CharacteristicOdour threshold: Not determined.

· Melting point/freezing point: -25 °C

· Boiling point or initial boiling point and

boiling range 36 °C Flammability Flammable.

· Lower and upper explosion limit

 Lower:
 0.7 Vol %

 Upper:
 6.5 Vol %

 Flash point:
 ≤60 °C

 Auto-ignition temperature:
 ~310 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic at 20 °C:Not determined.140000 mPas

Solubility

• water at 20 °C: 0.04 g/l

· Partition coefficient n-octanol/water (log

value) Not determined.
Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: ~0.81 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

(Contd. on page 7)

ΙE

www.bison.net 6/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 6)

· Appearance:

· Form: Fluid

Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 0.9 % · Water: 0.0 % · Solids content: 5.7 %

· Change in condition

Flammable solids

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Void

· Organic peroxides Void
· Corrosive to metals Void
· Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Corrosive action on metals.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

(Contd. on page 8)

www.bison.net 7/12

IF.



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 7)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkylderivs.			
Oral	LD50	1350 mg/kg (rat)	
	78-93-3 butanone		
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 9)

IE -

www.bison.net 8/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 8)

Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14:	Transport	information
--------------------	------------------	-------------

	444	LINI	numbar	~" ID	numbar
٠	14.1	UN	number	or ID	number

· ADR/ADN, IMDG, IATA UN2924

· 14.2 UN proper shipping name

· ADR/ADN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S.

(Benzenesulfonic acid, 4-C10-13-sec-alkylderivs., ISOPROPANOL (ISOPROPYL ALCOHOL))

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Benzenesulfonic acid, 4-C10-13-sec-alkylderivs., ISOPROPANOL (ISOPROPYL ALCOHOL))

· 14.3 Transport hazard class(es)

· ADR/ADN

· IMDG, IATA





· Class 3 (FC) Flammable liquids. · Label 3+8

· IMDG





Class 3 Flammable liquids.

(Contd. on page 10)

· /-

www.bison.net 9/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

	(Contd. of page
· Label	3/8
· IATA	
· Class · Label	3 Flammable liquids. 3 (8)
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Stowage Code 	Warning: Flammable liquids. 38 F-E,S-C (SGG1) Acids A SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml 3
· Transport category · Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100
· Remarks:	ml Under certain conditions substances in Class (flammable liquids) can be classified i packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.
	(Contd. on page

www.bison.net 10/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 10)

UN "Model Regulation":

UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYLDERIVS., ISOPROPANOL (ISOPROPYL ALCOHOL)), 3 (8), III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 12)

-, - IF

www.bison.net 11/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.03.2024 Version number 35 (replaces version 34) Revision: 26.03.2024

Trade name: BIS SILICONE REMOVER BD 100ML*6 L192

(Contd. of page 11)

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: PSRA

Contact: PSRA

Date of previous version: 24.01.2022Version number of previous version: 34

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

ΙE

www.bison.net 12/12