

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

(Contd. on page 2)

Fax: 0049-(0)7223-284-245

·IF

www.uhu.com 1/20



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 34 (replaces version 33) Revision: 26.01.2024 Printing date 29.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P261 Avoid breathing vapours. P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Adhesive

Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5

Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-

XXXX

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205

Specific concentration limits:

Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 %

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

2/20 www.uhu.com



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

www.uhu.com 3/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 3)

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs			
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)			
Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)	
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)	
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)	
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m³ (rat)	
	Consumer, inhalative, longterm exposition	0.87 mg/m³ (rat)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions

(Contd. on page 5)

\_ <u>'</u>

www.uhu.com 4/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 4)

(mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Amine-like
Not determined.

Undetermined.

Boiling point or initial boiling point and

boiling range Undetermined.
• Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >150 °C

• **Decomposition temperature:** Not determined.

pH at 20 °C

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 40000 mPas

Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

• Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• **9.2 Other information** All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

(Contd. on page 6)

·IE

www.uhu.com 5/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 5)

· Appearance:

· Form: Fluid

Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

Solids content: 100.0 %Molecular weight 700 g/mol

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives

Flammable gases

Void

Aerosols

Oxidising gases

Void

Gases under pressure

Flammable liquids

Flammable solids

Solf-reactive substances and mixtures

Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

\_ IE

www.uhu.com 6/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 6)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

E -

(Contd. on page 8)

www.uhu.com 7/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 7)

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN3082 -
14.2 UN proper shipping name ADR/ADN	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), MARIN POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
14.3 Transport hazard class(es)	
ADR/ADN	
Class	<ol><li>9 (M6) Miscellaneous dangerous substances ar articles.</li></ol>
Label	9
IMDG, IATA	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Class	9 Miscellaneous dangerous substances ar articles.

www.uhu.com 8/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

	(Contd. of page
Label	9
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substance and articles.
Hazard identification number (Kemler code): EMS Number: Stowage Category	90 F-A,S-F A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category Tunnel restriction code	3 (-)
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A (EPICHLORHYDRIN); EPOXY RESIN (NUMBEN AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 10)

· IF

www.uhu.com 9/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 34 (replaces version 33) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 9)

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### · Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation

Skin sensitisation

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

Date of previous version: 17.05.2022
Version number of previous version: 33

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

IE -

www.uhu.com 10/20



# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 26.01.2024 Printing date 29.01.2024 Version number 34 (replaces version 33)

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.

11/20 www.uhu.com



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 23 (replaces version 22)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

mercaptan polymer

· Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

(Contd. on page 2)

Revision: 26.01.2024

Fax: 0049-(0)7223-284-245

-*)* - IF -

www.uhu.com 12/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 1)

P501 Dispose of contents/container in accordance with national regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · **Description**: Adhesive

Dangerous components:		
CAS: 72244-98-5 EC number: 615-735-8 Reg.nr.: 01-2120118957-46- XXXX	mercaptan polymer  Skin Sens. 1, H317; Aquatic Chronic 3, H412	50-100%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol  Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥2.5-<10%
CAS: 280-57-9 EINECS: 205-999-9 Reg.nr.: 01-2119980944-22	triethylenediamine      Acute Tox. 4, H302; Skin Irrit. 2, H315	1-2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

· IF

www.uhu.com 13/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Recommended filter device for short term use: Combination filter A-P1

(Contd. on page 4)

- IE

www.uhu.com 14/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 3)

#### · Hand protection



## Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Recommended thickness of the material: > 0,12 mm

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber Nitrile rubber, NBR

### · Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Goggles recommended during refilling

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Characteristic
Not determined.

Undetermined.

Boiling point or initial boiling point and

boiling range 156 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >100 °C

· Decomposition temperature: Not determined.

· pH at 20 °C 11

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 17500 mPas

Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined.

• Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C:
 Relative density
 1.138 g/cm³
 Not determined.

(Contd. on page 5)

- IE

www.uhu.com 15/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

<b>^</b>		•		
Cor	nta.	ot	page	4

	(Contd. of page
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for th mixture. All non-determined data are no measurable or not relevant for th characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Solids content:	1.8 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza classes	arα Void
Explosives	Void
Flammable gases Aerosols	Void
	Void
Oxidising gases Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	VOIG
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Corrosive to metals	

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

· IF

www.uhu.com 16/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

#### 280-57-9 triethylenediamine

Oral LD50 1700 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

. *)* 

www.uhu.com 17/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 6)

Harmful to aquatic organisms

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	not regulated -
· 14.2 UN proper shipping name · ADR/ADN, IMDG, IATA	not regulated
· 14.3 Transport hazard class(es)	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
· 14.4 Packing group · ADR/ADN, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk accordi	ng to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	not regulated

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 8)

') IF

www.uhu.com 18/20



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024 Version number 23 (replaces version 22) Revision: 26.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 7)

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

### · Classification according to Regulation (EC) No 1272/2008

Skin sensitisation

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

Date of previous version: 27.10.2022
Version number of previous version: 22

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 9)

\_ ÍE

www.uhu.com 19/20



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 23 (replaces version 22) Revision: 26.01.2024 Printing date 29.01.2024

Trade name: UHU QUICKSET EPOXY ADH BS 2X15ML\*10 AREN

(Contd. of page 8)

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

20/20 www.uhu.com