

Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

• Trade name: BIS EPOXY METAL BD 24ML*12 L642

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

Fax: 0049-(0)7223-284-245

· Further information obtainable from: PSRA

E-mail: sds@boltonadhesives.com

 1.4 Emergency telephone number: Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

táirge imoibriúcháin: roisín eapocsa bisphenol-F- (epichlorhydrin) (meánmheáchan móilíneach ≤ 700)

(Contd. on page 2)



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

reaction produ	(Contd. of page 1) suct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤		
700)	ici. Displienoi-A-(epicilioinyunin) epoxy resin (number average molecular weight \leq		
	[(C12-14-alkyloxy)methyl] derivates		
· Hazard statem			
H315 Causes s			
	serious eye irritation.		
	se an allergic skin reaction.		
	aquatic life with long lasting effects.		
· Precautionary			
P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
P261	Avoid breathing vapours.		
P280			
P302+P352			
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P501	Dispose of contents/container in accordance with national regulations.		
· Additional info	· Additional information:		
EUH205 Conta	EUH205 Contains epoxy constituents. May produce an allergic reaction.		
[.] 2.3 Other haza	· 2.3 Other hazards		
· Results of PB	· Results of PBT and vPvB assessment		
	· PBT: Not applicable.		
· vPvB: Not app	· vPvB: Not applicable.		

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:		
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- xxxx	táirge imoibriúcháin: roisín eapocsa bisphenol-F- (epichlorhydrin) (meánmheáchan móilíneach ≤ 700) � Aquatic Chronic 2, H411; � Skin Irrit. 2, H315; Skin Sens. 1, H317	50-100%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 % 	25-50%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivates Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

(Contd. on page 3)



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **SECTION 6: Accidental release measures**
- 6.1 Personal precautions, protective equipment and emergency procedures Not required. 6.2 Environmental precautions:
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 3)
7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
Storage class: 10
7.3 Specific end use(s) No further relevant information available.
SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) Oral 0.5 mg/kg bw/day (rat) Consumer, oral, longterm exposition Dermal Worker, dermal, longterm exposition 0.75 mg/kg bw/day (rat) 0.0893 mg/kg bw/day (rat) Consumer, dermal, longterm exposition Inhalative Worker, inhalative, longterm exposition 4.93 mg/m³ (rat) Consumer, inhalative, longterm exposition 0.87 mg/m³ (rat) · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Appropriate engineering controls No further data; see section 7. · Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required. Recommended filter device for short term use: Combination filter A-P1 Hand protection Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Recommended thickness of the material: > 0,12 mm

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm) Break through time : > 8 h

(Contd. on page 5)



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 4)

Material Break through time : Ethyl Vinyl Alcohol Laminate (EVAL)

: > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical and chen	nical properties		
General Information	• •		
Physical state	Fluid		
Colour:	According to product specification		
Odour:	Characteristic		
Odour threshold:	Not determined.		
Melting point/freezing point:	Undetermined.		
Boiling point or initial boiling point and			
boiling range	Undetermined.		
Flammability	Not applicable.		
Lower and upper explosion limit			
Lower:	Not determined.		
Upper:	Not determined.		
Flash point:	>150 °C		
Decomposition temperature:	Not determined.		
pH at 20 °C	6		
Viscosity:			
Kinematic viscosity	Not determined.		
Dynamic at 20 °C:	720000 mPas		
Solubility			
water:	Not miscible or difficult to mix.		
Partition coefficient n-octanol/water (log			
value)	Not determined.		
Vapour pressure:	Not determined.		
Density and/or relative density			
Density at 20 °C:	1.45 g/cm³		

IF .



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

	(Contd. of page s
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are no
	measurable or not relevant for the
	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	22.0.0/
Solids content:	33.0 %
Change in condition	Not data wain a d
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void Void
Desensitised explosives	

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

(Contd. of page 6)

Trade name: BIS EPOXY METAL BD 24ML*12 L642

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity
- Not applicable.
- Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

(Contd. on page 8)

IF



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

(Contd. of page 7)

Trade name: BIS EPOXY METAL BD 24ML*12 L642

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR/ADN, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR/ADN	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (táirg imoibriúcháin: roisín eapocsa bisphenol-F (epichlorhydrin) (meánmheáchan móilíneach 700), reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700))
IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
14.3 Transport hazard class(es) ADR/ADN	
Class	9 (M6) Miscellaneous dangerous substances an articles.



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

	(Contd. of page
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles. 9
	9
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code): EMS Number: Stowage Category	90 F-A,S-F A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 (-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 1



Printing date 29.01.2024

· UN "Model Regulation":

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 9)

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TÁIRGE IMOIBRIÚCHÁIN: ROISÍN EAPOCSA BISPHENOL-F- (EPICHLORHYDRIN) (MEÁNMHEÁCHAN MÓILÍNEACH ≤ 700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

IE -



Printing date 29.01.2024

Version number 19 (replaces version 18)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

· Classification according to Regulation (EC)	No 1272/2008
Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generall based on the calculation method usin substance data according to Regulation (EC) N 1272/2008.
 Department issuing SDS: UHU QESH Contact: UHU QESH Date of previous version: 27.10.2022 Version number of previous version: 18 Abbreviations and acronyms: Abbreviations and acronyms: ADR: Accord relatif au transport international des marchat the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and La EINECS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American DNEL: Derived No-Effect Level (REACH) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - 	nical Šubstances Chemical Society) long-term aquatic hazard – Category 2



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

• Trade name: BIS EPOXY METAL BD 24ML*12 L642

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7

D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 E-mail: sds@boltonadhesives.com


Fax: 0049-(0)7223-284-245

· Further information obtainable from: PSRA

 • 1.4 Emergency telephone number: Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

2,4,6-tris(dimethylaminomethyl)phenol

Amines, polyethylenepoly-, triethylenetetramine fraction

- Hazard statements
- H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

· Precautionary statements

(Contd. of page 1)

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing vapours. Wear protective gloves / eye protection. P280 P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501

Dispose of contents/container in accordance with national regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

EINECS: 202-859-9	
EINECS: 202-013-9 Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Index number: 603-069-00-0 Tox. 4, H302 Reg.nr.: 01-2119560597-27 Amines, polyethylenepoly-, triethylenetetramine fraction	10-25%
	:5-≤10%
EINECS: 292-588-2 Reg.nr.: 01-2119487919-13 Aquatic Chronic 3, H412	≥3-<5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

IF



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

(Contd. of page 2)

Trade name: BIS EPOXY METAL BD 24ML*12 L642

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

aegraaaten	
Material of gloves	
Recommended thickness of th	e material: > 0,12 mm
Hand protection Material	: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)
Break through time	:>8h
0	

Material	: Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time	: > 8 h
glove material for short-term	use / splash: (10 min <btt <480="" min):="" neoprene="" nitrile="" rubber,="" rubber<="" td=""></btt>

Nitrile rubber. NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

(Contd. of page 4)

Trade name: BIS EPOXY METAL BD 24ML*12 L642

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties		
• 9.1 Information on basic physical and chemical properties		
General Information		
Physical state	Fluid	
· Colour:	Beige	
· Odour:	Amine-like	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
· Boiling point or initial boiling point and		
boiling range	205.4 °C	
· Flammability	Not applicable.	
 Lower and upper explosion limit 		
· Lower:	1.3 Vol %	
· Upper:	13 Vol %	
· Flash point:	101 °C	
Auto-ignition temperature:	435 °C	
· Decomposition temperature:	Not determined.	
· Ha	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
· Dynamic at 20 °C:	200000 mPas	
Solubility		
· water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log		
value)	Not determined.	
· Vapour pressure at 20 °C:	0.1 hPa	
· Vapour pressure at 50 °C:	0.7 hPa	
Density and/or relative density		
· Density at 20 °C:	1.013 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
9.2 Other information	All relevant physical data ware datarmined for the	
9.2 Other mormation	All relevant physical data were determined for the mixture. All non-determined data are not	
	measurable or not relevant for the	
	characterization of the mixture.	
· Appearance:		
· Form:	Fluid	
Important information on protection of hea	1011	
and environment, and on safety.	Droduct is not colfigniting	
· Ignition temperature:	Product is not selfigniting.	
	(Contd. on page 6)	

IF



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

	(Contd. of page 5
· Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
· Organic solvents:	12.5 %
· Solids content:	81.5 %
Change in condition	
Evaporation rate	Not determined.
· Information with regard to physical haz	ard
classes	
· Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
Self-reactive substances and mixtures	Void
 Pyrophoric liquids 	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
• Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
Organic peroxides	Void
· Corrosive to metals	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1230 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

(Contd. on page 7)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 6) · Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Causes serious eye damage. · Respiratory or skin sensitisation May cause an allergic skin reaction. · Germ cell mutagenicity Not applicable. Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • Reproductive toxicity Based on available data, the classification criteria are not met. • STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. • Additional toxicological information: · Acute effects (acute toxicity, irritation and corrosivity) Not applicable. · Sensitisation Not applicable. · Repeated dose toxicity Not applicable. 11.2 Information on other hazards · Endocrine disrupting properties None of the ingredients is listed. SECTION 12: Ecological information 12.1 Toxicity · Aquatic toxicity: No further relevant information available. 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. vPvB: Not applicable. 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

(Contd. of page 7)

Trade name: BIS EPOXY METAL BD 24ML*12 L642

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
 · 14.1 UN number or ID number · ADR/ADN, IMDG, IATA 	not regulated -
 14.2 UN proper shipping name ADR/ADN, IMDG, IATA 	not regulated
 14.3 Transport hazard class(es) 	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
 14.4 Packing group ADR/ADN, IMDG, IATA 	not regulated
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user 	Not applicable.
 14.7 Maritime transport in bulk according IMO instruments 	g to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
 None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)



Printing date 29.01.2024

Version number 20 (replaces version 19)

Revision: 26.01.2024

Trade name: BIS EPOXY METAL BD 24ML*12 L642

(Contd. of page 8)

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Serious eye damage/irritation The classification of the mixture is generally based on the Skin sensitisation calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: UHU QESH

Contact: UHU QESH

Date of previous version: 27.10.2022

· Version number of previous version: 19

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3