

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: BIS GREASE SPRAY AE 400ML*12 L255
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160

NL-4460 AD Goes tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

GB-EN

www.bison.net 1/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 1)

Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Lubricant

Dangerous components:				
EC number: 927-241-2	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	25-50%		
	n-Butan Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-2.5%		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

www.bison.net 2/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

- GB-EN

www.bison.net 3/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

106-97-8 n-Butan

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection: Not required.

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Not required.

GB-EN

(Contd. on page 5)

www.bison.net 4/10



Safety data sheet according to 1907/2006/EC, Article 31

Version number 25 (replaces version 24) Revision: 18.08.2022 Printing date 11.02.2023

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Characteristic · Odour: · Odour threshold: Not determined. Undetermined.

· Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 180 °C

· Flammability Not applicable.

Lower and upper explosion limit

0.6 Vol % · Lower: · Upper: 10.9 Vol % -97 °C · Flash point: 240 °C · Ignition temperature:

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

Solubility

Not miscible or difficult to mix. Partition coefficient n-octanol/water (log

Not determined.

value)

· Vapour pressure at 20 °C: 8300 hPa

Density and/or relative density

Density at 20 °C: 0.68 g/cm³ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 39.5 % · Solids content: 0.0 %

Change in condition

· Evaporation rate Not applicable.

(Contd. on page 6)

5/10 www.bison.net



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 5)

	(Contd. or page 5)
Information with regard to physical haza	ard
classes	
· Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised
	container: May burst if heated.
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

106-97-8 n-Butan

Inhalative LC50/4 h 658 mg/l (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 7)

www.bison.net 6/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 6)

· Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 8)

www.bison.net 7/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 7)

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

· ADR/ADN 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR/ADN



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· 14.4 Packing group

· ADR/ADN, IMDG, IATA not regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

• **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

• Segregation Code SG69 For AEROSOLS with a maximum capacity

of 1 litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of

(Contd. on page 9)

- GB-EN

www.bison.net 8/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

	(Contd. of page
	class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk accord	ing to Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Remarks:	Not permitted as Excepted Quantity Under certain conditions substances in Class (flammable liquids) can be classified i packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 10)

GB-EN

www.bison.net 9/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 25 (replaces version 24) Revision: 18.08.2022

Trade name: BIS GREASE SPRAY AE 400ML*12 L255

(Contd. of page 9)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008			
Aerosols, Section 2.3.1	Bridging principles		
Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.		
Aspiration hazard	Expert judgement		

· Department issuing SDS: Bison QESH

· Contact: Reach coordinator

Date of previous version: 22.04.2022
 Version number of previous version: 24

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB-EN

www.bison.net 10/10