

Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: PSRA

· 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS02 flame

 $\overline{}$

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatia Chronia 2	H412 Hermful to aquatic life with long leating effects

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

[•] Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



(Contd. on page 2)

IE



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

(Contd. of page 1) Signal word Danger · Hazard-determining components of labelling: butanone methylcyclohexane ethyl acetate acetone Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapours. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with national regulations. · Additional information: EUH208 Contains Rosin. May produce an allergic reaction. · Labelling of packages where the contents do not exceed 125 ml · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: butanone methylcyclohexane ethyl acetate acetone Hazard statements H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. P261 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with national regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment PBT: Not applicable. (Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

(Contd. of page 2)

List II

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 butanone

3.2 Mixtures		
Description: Adhesive Dangerous components:		
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18	methylcyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
CAS: 25085-50-1 ELINCS: 472-160-3 Reg.nr.: Exempt	Butylphenolformaldehyde resin Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32	Rosin Skin Sens. 1, H317	≥0.1-<1%
CAS: 123-26-2 EINECS: 204-613-6 Reg.nr.: 01-2119978265-26	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1- amide) Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

(Contd. on page 4)

IE



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

(Contd. of page 3)

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Water haze

Alcohol resistant foam Fire-extinguishing powder

- Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

(Contd. on page 5)



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

(Contd. of page 4)

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1	Control	parameters
-----	---------	------------

· Ingredients	with limit values that require monitoring at the workplace:				
78-93-3 butanone					
OEL (Ireland) Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, IOELV					
IOELV (EU)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm				
141-78-6 et	hyl acetate				
OEL (Irelan	d) Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm IOELV				
IOELV (EU) Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm					
108-87-2 m	ethylcyclohexane				
OEL (Irelan	d) Long-term value: 1600 mg/m³, 400 ppm				
67-64-1 ace	tone				
OEL (Irelan	d) Long-term value: 1210 mg/m³, 500 ppm IOELV				
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm				
· DNELs					
78-93-3 butanone					
Oral (Consumer, oral, longterm exposition 31 mg/kg bw/day				
Dermal (Consumer, dermal, longterm exposition 412 mg/kg bw/day				
Inhalative (Consumer, inhalative, longterm exposition 106 mg/m³				
141-78-6 et	hyl acetate				
Oral (Consumer, oral, longterm exposition 4.5 mg/kg bw/day				
	(Contd. on p	age			



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

							(0,0) marked of r	
Dermal	Cor	sumer, dermal, longterm exposition	ו ו	37 mg/kg b	w/day		(Contd. of p	age (
Inhalative	Cor	sumer DNEL, acute inhalation		734 mg/m³				
	Cor	sumer, inhalative, longterm exposit	ion	367 mg/m³				
67-64-1 a	ceto	ne						
Oral C		sumer, oral, longterm exposition		62 mg/kg b	w/day			
Dermal	Cor	sumer, dermal, longterm exposition		62 mg/kg b	•			
Inhalative	Cor	nsumer, inhalative, longterm exposit	ion	200 mg/m³				
· PNECs	<u>.</u>		· ·					
78-93-3 b	utan	one						
Fresh wat	er	55.8 mg/l						
Marine wa	ater	55.8 mg/l						
Soil		22.5 mg/kg						
141-78-6	ethy	acetate						
Fresh wat	er	0.26 mg/l						
Marine wa	ater	0.026 mg/l						
Soil		0.22 mg/kg						
67-64-1 a	ceto	ne						
Fresh wat	er	10.6 mg/l						
Marine we								
Manile Wa	ater	1.06 mg/l						
Soil Additiona 8.2 Expos	al inf sure	29.5 mg/kg ormation: The lists valid during the controls		-		sis.		
Soil • Additiona • 8.2 Expos • Appropria • Individua • General p The usual Keep awa Immediate Wash han Do not inh Avoid com • Respirato Use suitat	I inf sure ate e prote prote y fro y fro ds b aale (ory p ole re ende	29.5 mg/kg ormation: The lists valid during the controls ngineering controls No further dat tection measures, such as perso ctive and hygienic measures: cautionary measures are to be adhe m foodstuffs, beverages and feed. move all soiled and contaminated c efore breaks and at the end of work gases / fumes / aerosols. with the eyes and skin. rotection: espiratory protective device in case of d filter device for short term use:	ta; so nal j ered t clothi	ee section f protective of to when had ng	7. equipme i ndling che	nt		



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

(Contd. of page 6) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Recommended thickness of the material: > 0,12 mm Butyl rubber, BR Nitrile rubber, NBR Recommended thickness of the material: > 0,7 mm • Penetration time of glove material
- For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
- For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).
- · Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling Body protection: Use protective suit. Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· General Information · Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	
boiling range	55.8-56.6 °C
· Flammability	Highly flammable.
· Lower and upper explosion limit	·
Lower:	1.8 Vol %
· Upper:	11.5 Vol %
· Flash point:	-4 °C
• Auto-ignition temperature:	260 °C
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	1000 mPas
Solubility	
· water:	Not miscible or difficult to mix.
 Partition coefficient n-octanol/water (log 	
value)	Not determined.
Vapour pressure at 20 °C:	105 hPa
	(Contd. on page 8



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

	(Contd. of page
Vapour pressure at 50 °C:	360 hPa
Density and/or relative density	
Density at 20 °C:	0.87 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea and environment, and on safety.	lth
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
h h . h	explosive air/vapour mixtures are possible.
Solvent content:	1 1 1
Organic solvents:	80.4 %
Water:	0.1 %
Solids content:	19.5 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
	Void
Uxidising solids	
Oxidising solids Organic peroxides	Void
Organic peroxides Corrosive to metals	Void Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

(Contd. on page 9)



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

(Contd. of page 8)

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:						
78-93-3 b	78-93-3 butanone					
Oral	LD50	3300 mg/kg (rat)				
Dermal	LD50	5000 mg/kg (rabbit)				
141-78-6	ethyl aceta	ate				
Oral	LD50	5620 mg/kg (rabbit)				
Inhalative	LC50/4 h	1600 mg/l (rat)				
108-87-2	methylcyc	lohexane				
Oral	LD50	2250 mg/kg (mouse)				
67-64-1 a	cetone					
Oral	LD50	5800 mg/kg (rat)				
Dermal	LD50	20000 mg/kg (rabbit)				
1314-13-2 zinc oxide						
Oral	LD50	>5000 mg/kg (rat)				
Skin corr						
	kin irritatior	n. e/irritation				

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.

(Contd. on page 10)



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

(Contd. of page 9)

List II

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

· 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 butanone

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information				
· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	UN1133			
 14.2 UN proper shipping name ADR/ADN IMDG, IATA 	1133 ADHESIVES ADHESIVES			
		(Contd. on page 1		



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

ADR/ADN Class 3 (F1) Flammable liquids. Label 3 IMDG, IATA Concentration of the second se	. 14.2 Transport barard alass(as)	(Contd. of page
Class 3 (F1) Flammable liquids. Label 3 IMDG, IATA Class 3 IMDG, IATA Class 3 Label 3 14.4 Packing group ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantitie	· 14.3 Transport hazard class(es)	
Label 3 IMDG, IATA IMDG, IATA IMDG, IATA Immable liquids. Label 3 14.4 Packing group 3 ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: Marine pollutant: No 14.6 Special precautions for user Hazard identification number (Kemler code): - Hazard identification number (Kemler code): - F.E.S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (EQ) SL		
Label 3 IMDG, IATA IMDG, IATA IMDG, IATA Immable liquids. Label 3 14.4 Packing group 3 ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: Marine pollutant: No 14.6 Special precautions for user Hazard identification number (Kemler code): - Hazard identification number (Kemler code): - F.E.S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (EQ) SL		
Label 3 IMDG, IATA IMDG, IATA IMDG, IATA Immable liquids. Label 3 14.4 Packing group 3 ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: Marine pollutant: No 14.6 Special precautions for user Hazard identification number (Kemler code): - Hazard identification number (Kemler code): - F.E.S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (EQ) SL	3	
Label 3 IMDG, IATA IMDG, IATA IMDG, IATA Immable liquids. Label 3 14.4 Packing group 3 ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: Marine pollutant: No 14.6 Special precautions for user Hazard identification number (Kemler code): - Hazard identification number (Kemler code): - F.E.S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (EQ) SL		2 (E1) Elemmoble liquide
IMDG, IATA Class 3 Flammable liquids. Label 3 14.4 Packing group ADR/ADN, IMDG, IATA ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: No Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) SL Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		
Class 3 Flammable liquids. Label 3 14.4 Packing group 3 ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) SL Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Limited quantities (LQ) SL Excepted quantities (EQ) <		
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m	····· • • • • • • • • • • • • • • • • •	
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m		
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m	3	
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m	Class	3 Flammable liquids.
ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Limited quantities (LQ) 5L Excepted quantities (EQ) SL Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m	·Label	
14.5 Environmental hazards: No 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN SL Limited quantities (LQ) SL Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net	· 14.4 Packing group	
Marine pollutant:No14.6 Special precautions for user Hazard identification number (Kemler code): - EMS Number:Warning: Flammable liquids. - F-E,S-D A14.7 Maritime transport in bulk according to IMO instrumentsF-E,S-D A14.7 Maritime transport in bulk according to IMO instrumentsNot applicable.Transport/Additional information: Quantity limitationsOn passenger aircraft/rail: 60 L On cargo aircraft only: 220 LADR/ADN Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlTransport category Tunnel restriction code5L E Code: E1 Maximum net quantity per outer packaging: 100 mlIMDG Limited quantities (LQ)5L E Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified	ADR/ADN, IMDG, IATA	III
14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN SL Limited quantities (LQ) SL Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG SL Limited quantities (LQ) SL Excepted quantities (LQ) SL Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	14.5 Environmental hazards:	
Hazard identification number (Kemler code): - F-E,S-D EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On passenger aircraft only: 220 L ADR/ADN SL Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG SL Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· · · · · · · · · · · · · · · · · · ·	
EMS Number:F-E,S-DStowage CategoryA14.7 Maritime transport in bulk according to IMO instrumentsNot applicable.Transport/Additional information: Quantity limitationsOn passenger aircraft/rail: 60 L On cargo aircraft only: 220 LADR/ADNSL Excepted quantities (LQ)Limited quantities (LQ)SL Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlTransport category3 ETunnel restriction codeSL EIMDG Limited quantities (LQ)SL EImited quantities (LQ)SL ETunnel restriction codeSL EIMDG Limited quantities (EQ)SL Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified	• 14.6 Special precautions for user	
Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN SL Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG SL Limited quantities (EQ) SL Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· Hazard identification number (Kemier code) · EMS Number:	
IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On cargo aircraft only: 220 L ADR/ADN SL Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) SL Code: E1 Maximum net quantity per outer packaging: 100 ml Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		
Transport/Additional information: On passenger aircraft/rail: 60 L Quantity limitations On cargo aircraft only: 220 L ADR/ADN 5L Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG 5L Limited quantities (LQ) 5L Excepted quantities (EQ) SL Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· 14.7 Maritime transport in bulk according to	
Quantity limitationsOn passenger aircraft/rail: 60 L On cargo aircraft only: 220 LADR/ADNSLLimited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlTransport category3 ETunnel restriction codeEIMDG Excepted quantities (LQ)5L ELimited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified	IMO instruments	Not applicable.
ADR/ADN SL Limited quantities (LQ) SL Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) SL Excepted quantities (LQ) SL Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		
ADR/ADN 5L Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Transport category 3 Tunnel restriction code E IMDG Excepted quantities (LQ) Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· Quantity limitations	
Limited quantities (LQ)5LExcepted quantities (EQ)Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlTransport category3 ETunnel restriction codeEIMDG Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified		
Excepted quantities (EQ)Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlTransport category3Tunnel restriction codeEIMDG Limited quantities (LQ)5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified		5L
Transport category 3 Tunnel restriction code E IMDG E Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per outer packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	Excepted quantities (EQ)	Code: E1
Transport category 3 Tunnel restriction code E IMDG E Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		
Transport category 3 Tunnel restriction code E IMDG E Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		
IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· Transport category	3
Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· Tunnel restriction code	
Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml Remarks: Under certain conditions substances in Class (flammable liquids) can be classified	· IMDG	-
Maximum net quantity per inner packaging: 30 mMaximum net quantity per outer packaging: 100Maximum net q		
Maximum net quantity per outer packaging: 100 mlRemarks:Under certain conditions substances in Class (flammable liquids) can be classified	LAUPIEN quantities (LQ)	Maximum net quantity per inner packaging: 30 m
Remarks: Under certain conditions substances in Class (flammable liquids) can be classified		Maximum net quantity per outer packaging: 100
(flammable liquids) can be classified	· Romarks	



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

(Contd. of page 11)

3

3

3

3

· UN "Model Regulation":

UN 1133 ADHESIVES, 3, III

See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

67-64-1 acetone

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

67-64-1 acetone

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 13)

IE



Printing date 25.01.2024

Version number 37 (replaces version 36)

Revision: 25.01.2024

Trade name: GRF BISON/CONTACT TIX TI 10L*1 L221

· Classification according to Regulation (EC) N	(Contd. of page 12)
	ed on the calculation method using substance data
Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
 Department issuing SDS: Bison QESH Contact: Reach coordinator Date of previous version: 31.05.2021 Version number of previous version: 36 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchand the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Lab EINECS: European Inventory of Existing Commercial Chemi ELINCS: European Inventory of Existing Commercial Chemi ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American O DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Asp. Tox. 1: Aspiration hazard – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - lot Aquatic Chronic 2: Hazardous to the aquatic environment - lot Aquatic Chronic 3: Hazardous to the aquatic environment - lot Aquatic Chronic 3: Hazardous to the aquatic environment - lot Aquatic Chronic 3: Hazardous to the aquatic environment - lot 	- Category 3 ute aquatic hazard – Category 1 ong-term aquatic hazard – Category 1 ong-term aquatic hazard – Category 2 ong-term aquatic hazard – Category 3