

Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

· Trade name: GRF B-21 BO 500ML\*12 L222

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

# 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

#### · Further information obtainable from: Bison QESH

· 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: butanone

(Contd. on page 2)

IF



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

#### Trade name: GRF B-21 BO 500ML\*12 L222

(Contd. of page 1) · Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. P261 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with national regulations. · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. · Labelling of packages where the contents do not exceed 125 ml Hazard pictograms GHS02 GHS07 Signal word Danger · Hazard-determining components of labelling: butanone · Hazard statements H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing vapours. P501 Dispose of contents/container in accordance with national regulations. · 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. **Determination of endocrine-disrupting properties** 78-93-3 butanone List II **SECTION 3: Composition/information on ingredients** 

#### · 3.2 Mixtures

#### · Description: Adhesive

# <sup>·</sup> Dangerous components:

. <b>J</b>		
CAS: 78-93-3	butanone	50-100%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3,	
Index number: 606-002-00-3		
Reg.nr.: 01-2119457290-43		

(Contd. on page 3)



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

(Contd. of page 2)

#### Trade name: GRF B-21 BO 500ML\*12 L222

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Water haze
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide
- $\cdot$  For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# **SECTION 6:** Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

(Contd. of page 3)

#### Trade name: GRF B-21 BO 500ML\*12 L222

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

#### • **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

78-93-3 bı			
OEL (Ireland) Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, IOELV			
IOELV (EU) Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm			
·DNELs			
78-93-3 bı	tanone		
Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition 412 mg/kg bw/day		
Inhalative	nhalative Consumer, inhalation, longterm exposition 106 mg/m³		
PNECs			
78-93-3 bı	tanone		
Fresh wate	er 55.8 mg/l		
Marine wat	ter 55.8 mg/l		
Soil 22.5 mg/kg			
· Additiona	information: The lists valid during the maki	ing were used as basis.	
	u <b>re controls</b> <b>te engineering controls</b> No further data; se	ee section 7.	
		(Contd. on page	




Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

#### Trade name: GRF B-21 BO 500ML\*12 L222



· Odour:

- Odour threshold:
- · Melting point/freezing point:
- Boiling point or initial boiling point and boiling range
- · Flammability

Colourless Like ketone Not determined. Undetermined.

79-80.5 °C Highly flammable.

(Contd. on page 6)



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

# Trade name: GRF B-21 BO 500ML\*12 L222

	(Contd. of page
Lower and upper explosion limit	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Flash point:	-9 °C
Auto-ignition temperature:	514 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	375 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	105 hPa
Density and/or relative density	
Density at 20 °C:	0.883 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data ware datarmined for th
9.2 Other Information	All relevant physical data were determined for th
	mixture. All non-determined data are no
	measurable or not relevant for th
	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of health	1
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	80.4 %
Solids content:	19.6 %
	19.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	ł
classes	
Explosives	Void
Flammable gases	Void
U U	Void
Aerosols Oxidicing gasos	
Oxidising gases	Void
Oxidising gases Gases under pressure	Void Void
Oxidising gases Gases under pressure Flammable liquids	Void Void Highly flammable liquid and vapour.
Oxidising gases Gases under pressure Flammable liquids Flammable solids	Void Void Highly flammable liquid and vapour. Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Highly flammable liquid and vapour. Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Highly flammable liquid and vapour. Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void Highly flammable liquid and vapour. Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Highly flammable liquid and vapour. Void Void Void



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

#### Trade name: GRF B-21 BO 500ML\*12 L222

		(Contd. of page 6)
• Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

# · LD/LC50 values relevant for classification:

#### 78-93-3 butanone

Oral LD50 3300 mg/kg (rat)

Dermal LD50 5000 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity
- Not applicable.
- Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.

(Contd. on page 8)



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

(Contd. of page 7)

List II

#### Trade name: GRF B-21 BO 500ML\*12 L222

#### · 11.2 Information on other hazards

# · Endocrine disrupting properties

78-93-3 butanone

#### **SECTION 12: Ecological information**

#### · 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

#### · Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information		
<ul> <li>14.1 UN number or ID number</li> <li>ADR/ADN, IMDG, IATA</li> </ul>	UN1133	
<ul> <li>• 14.2 UN proper shipping name</li> <li>• ADR/ADN</li> <li>• IMDG, IATA</li> <li>1133 ADHESIVES, special provision 640D</li> <li>• ADHESIVES</li> </ul>		
	(Contd. on page S	



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

Trade name: GRF B-21 BO 500ML\*12 L222

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class	3 Flammable liquids.
	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	II
• 14.5 Environmental hazards: • Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-D
Stowage Category	B
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 r
	Maximum net quantity per outer packaging: 50 Maximum net quantity per outer packaging: 5
Transport category	ml 2
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	Z D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 r
	Maximum net quantity per inner packaging: 50 Maximum net quantity per outer packaging: 5
Demontos	ml
Remarks:	Under certain conditions substances in Class (flammable liquids) can be classified packinggroup III.
	(Contd. on page

IE



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

#### Trade name: GRF B-21 BO 500ML\*12 L222

(Contd. of page 9)

3

3

UN "Model Regulation":

UN 1133 ADHESIVES, 3, II

See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- $^{\circ}$  Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Classification according to Regulation (EC) No 1272/2008

<b>č</b> č č ( ,	
Flammable liquids	Bridging principles
Serious eye damage/irritation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Department issuing SDS: Bison QESH

· Contact: Reach coordinator

· Date of previous version: 19.06.2021

· Version number of previous version: 17

(Contd. on page 11)



Printing date 11.01.2024

Version number 18 (replaces version 17)

Revision: 04.01.2024

(Contd. of page 10)

#### Trade name: GRF B-21 BO 500ML\*12 L222

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

vPvB: very Persistent and very Bioaccumulative

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.