

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 35 (replaces version 34)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BIS SHOE GLUE FB 55ML\*12 L327
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

**Bison International** 

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling: acetone

(Contd. on page 2)

Revision: 25.01.2024

- IE

www.bison.net 1/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 1)

ethyl acetate

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms





GHS02 GHS07

## · Signal word Danger

### · Hazard-determining components of labelling:

acetone

ethyl acetate

#### · Hazard statements

H336 May cause drowsiness or dizziness.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

## 2.3 Other hazards

## · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Adhesive

(Contd. on page 3)

www.bison.net 2/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

		(Contd. of page 2)			
· Dangerous components:					
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone      Flam. Liq. 2, H225;    Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%			
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate  Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%			
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (CAS no. 41556-26-7) and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (CAS no. 82919-37-7)  Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.025-<0.1%			

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

T)

www.bison.net 3/12



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 3)

#### · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

## 67-64-1 acetone

OEL (Ireland) Long-term value: 1210 mg/m³, 500 ppm

**IOELV** 

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 5)

ίΕ·

www.bison.net 4/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

			(Contd. of page 4		
141-78-6	141-78-6 ethyl acetate				
OEL (Ireland)		Short-term value: 1468 mg/m³, 400 ppm			
		Long-term value: 734 mg/m³, 200 ppm			
IOELV (EU)		Short-term value: 1468 mg/m³, 400 ppm			
IOELV (EU)		Long-term value: 734 mg/m³, 200 ppm			
DNELs					
67-64-1 ad	ceto	one			
Oral	Со	nsumer, oral, longterm exposition	62 mg/kg bw/day		
Dermal Consumer, dermal, long		nsumer, dermal, longterm exposition	62 mg/kg bw/day		
Inhalative	Со	nsumer, inhalative, longterm exposition	200 mg/m³		
141-78-6 ethyl acetate					
Oral	Со	nsumer, oral, longterm exposition	4.5 mg/kg bw/day		
Dermal Consu		nsumer, dermal, longterm exposition	37 mg/kg bw/day		
Inhalative C		onsumer DNEL, acute inhalation 734 mg/m³			
	Consumer, inhalative, longterm exposition		367 mg/m³		
·PNECs					
67-64-1 ad	ceto	one			
Fresh water		10.6 mg/l			
Marine water		1.06 mg/l			
Soil		29.5 mg/kg			
141-78-6 ethyl acetate					
Fresh water		0.26 mg/l			
Marine water					
Soil		0.22 mg/kg			

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

· Recommended filter device for short term use:

Filter AX

Filter A

· Hand protection

Solvent resistant gloves

(Contd. on page 6)

- IF

www.bison.net 5/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection: Solvent resistant protective clothing

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 55 °C

· **Flammability** Highly flammable.

Lower and upper explosion limit

Lower: 2.1 Vol %
Upper: 13 Vol %
Flash point: <0 °C</li>
Auto-ignition temperature: 460 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic at 20 °C:Not determined.3000 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 233 hPa

(Contd. on page 7)

-IE

www.bison.net 6/12



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 6) · Vapour pressure at 50 °C: 800 hPa · Density and/or relative density Density at 20 °C: 0.898 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: Organic solvents: 78.4 % · VOC (EC) 78.41 % · Solids content: 21.5 % · Change in condition Not determined. Evaporation rate · Information with regard to physical hazard classes Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Highly flammable liquid and vapour. Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

(Contd. on page 8)

· IE

www.bison.net 7/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 7)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
67-64-1 ad				
Oral	LD50	5800 mg/kg (rat)		
Dermal LD50 20000 mg/kg (rabbit)		20000 mg/kg (rabbit)		
141-78-6 ethyl acetate				
Oral	LD50	5620 mg/kg (rabbit)		
Inhalative	LC50/4 h	1600 mg/l (rat)		

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)

- IF

www.bison.net 8/12



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR/ADN, IMDG, IATA UN1133
- · 14.2 UN proper shipping name
- · ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES
  - MIDO, IATA ADTILOT
- · 14.3 Transport hazard class(es)
- · ADR/ADN



Class 3 (F1) Flammable liquids.

(Contd. on page 10)

www.bison.net 9/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

	(Contd. of page 9
Label	3
IMDG, IATA	
Class Label	3 Flammable liquids.
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. - F-E,S-D A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

(Contd. on page 11)

www.bison.net 10/12



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 10)

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone 3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

- · Department issuing SDS: Bison QESH
- · Contact: Reach coordinator
- Date of previous version: 31.05.2021
   Version number of previous version: 34
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)

\_ IF

www.bison.net 11/12



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2024 Version number 35 (replaces version 34) Revision: 25.01.2024

Trade name: BIS SHOE GLUE FB 55ML\*12 L327

(Contd. of page 11)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1A: Skin sensitisation – Category 1A Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

\* Data compared to the previous version altered.

12/12 www.bison.net