

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF WDF-05 BO 250ML*12 L242
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International B.V.

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

www.griffon.eu 1/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 1)

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Tetrahydrofuran

Butanone

· Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Tetrahydrofuran

Butanone

· Hazard statements

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with national regulations.

(Contd. on page 3)

- GB

www.griffon.eu 2/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

Description. Adhesive			
· Dangerous components:			
CAS: 109-99-9 EINECS: 203-726-8 Index number: 603-025-00-0 Reg.nr.: 01-2119444314-46- XXXX	Tetrahydrofuran		
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone Flam. Liq. 2, H225;	25-50%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

(Contd. on page 4)

- GB

www.griffon.eu 3/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 3)

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

зв -

(Contd. on page 5)

www.griffon.eu 4/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 35 (replaces version 34) Printing date 11.11.2024 Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

-GB

					(Contd. of p
SEC	TIOI	N 8: Exposure o	controls/personal p	protection	
8.1 Control parameters					
		-	that require monitori	ng at the workplace:	
109-9	9-9 T	etrahydrofuran	<u> </u>		
WEL		t-term value: 300 m			
	Long Sk	g-term value: 150 m	g/m³, 50 ppm		
79 02		utanone			
		t-term value: 899 m	ng/m³ 300 nnm		
***	Long	g-term value: 600 m			
	Sk, Ē	BMGV			
DNEL	.s				
109-9	9-9 T	etrahydrofuran			
Oral		Consumer, oral, lor	•	1.5 mg/kg bw/day	
Derm		Worker, dermal, lor	•	12.6 mg/kg bw/day	
			longterm exposition	1.5 mg/kg bw/day	
Inhala	ative		shortterm exposition	96 mg/m³	
			longterm exposition	72.4 mg/m³	
		Consumer DNEL, a		52 mg/m³	
70.00	2.0		ve, longterm exposition	13 mg/m³	
7 8-93 Oral	-3 BI	utanone	atorm evacaition	21 malka bulday	
Derm.	al	Consumer, oral, lor Worker, dermal, lor	•	31 mg/kg bw/day 1161 mg/kg bw/day	
Denn	aı		longterm exposition	412 mg/kg bw/day	
Inhala	ative		shortterm exposition	900 mg/m³	
ii ii idic			longterm exposition	600 mg/m³	
		Consumer DNEL, acute inhalation		450 mg/m³	
		Consumer, inhalative, longterm exposition		_	
PNEC	cs.			-	
		etrahydrofuran			
		ndary Poisoning	67 mg/kg		
Fresh water Fresh water sediment Marine water Marine sediment Soil Sewage treatment plant Sporadic release		n water	4.32 mg/l		
		n water sediment	23.3 mg/kg dry weight		
		ne water	0.432 mg/l		
		ne sediment	2.33 mg/kg dry weight		
			2.13 mg/kg		
		•	_		
			21.6 mg/l		
		utanone	4000		
		ndary Poisoning	1000 mg/kg		
	riesi	n water	55.8 mg/l		(Contd. on p

www.griffon.eu 5/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 5)

Fresh water sediment	284.7 mg/kg dry weight	
Marine water	55.8 mg/l	
Marine sediment	284.7 mg/kg dry weight	
Soil	22.5 mg/kg	
Sewage treatment plant	709 mg/l	

Ingredients with biological limit values:

78-93-3 Butanone

BMGV 70 µmol/L

Medium: urine

Sporadic release

Sampling time: post shift Parameter: butan-2-one

· Additional information: The lists valid during the making were used as basis.

55.8 mg/l

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter A
- Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

(Contd. on page 7)

GB

www.griffon.eu 6/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 6)

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 65.5 °C

Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.5 Vol %
 Upper: 12 Vol %
 Flash point: -21 °C

· Auto-ignition temperature: 230 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 675 mPas

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure at 20 °C: 200 hPa

• Vapour pressure at 20 °C: 200 hra

Density and/or relative density

Density at 20 °C: 0.965-0.966 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

(Contd. on page 8)

- GB

www.griffon.eu 7/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 35 (replaces version 34) Printing date 11.11.2024 Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 7)

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

82.9 % Organic solvents: 0.0 % · Water: · VOC (EC) 82.92 % Solids content: 16.9 %

Change in condition

Not determined. · Evaporation rate

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Void · Aerosols Oxidising gases Void · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 9)

8/13 www.griffon.eu



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 8)

• 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		3	,	
	· LD/LC50 values relevant for classification:			
	109-99-9 Tetrahydrofuran			
	Oral	LD50	500 mg/kg (rat)	
	Dermal	LD50	>2000 mg/kg (rat)	
	Inhalative	LC50/4 h	>5000 mg/l (rat)	
78-93-3 Butanone				
	Oral		>2193 mg/kg (rat)	
	Dermal	LD50	>8050 mg/kg (rat)	

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrin	e disrupting properties	
78-93-3	Butanone	List II
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 10)

GB

www.griffon.eu 9/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 9)

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION	14: Trans	port in	formation
---------	-----------	---------	-----------

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR/ADN



· Class 3 (F1) Flammable liquids.

Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

ADR/ADN, IMDG, IATA

(Contd. on page 11)

- GE

www.griffon.eu 10/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler co	Warning: Flammable liquids.
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according	y to Not applicable.
	ногаррисаріе.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	Ē
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml
Remarks:	For substances with class 3 according to IMD0 Code chapter 2.3.2.2 packing group is classified in packing group. III, as viscosity is in accordance with requirements (flow time t > 100s).
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 12)

GΒ

www.griffon.eu 11/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 35 (replaces version 34) Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 11)

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 Butanone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 Butanone

3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Serious eye damage/irritation	The classification of the mixture is generally based
Carcinogenicity	on the calculation method using substance data
Specific target organ toxicity (single exposure)	according to Regulation (EC) No 1272/2008.

· Department issuing SDS: PSRA

Contact: PSRA

Date of previous version: 21.06.2024
 Version number of previous version: 34

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)

GB

www.griffon.eu 12/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 35 (replaces version 34) Printing date 11.11.2024 Revision: 11.11.2024

Trade name: GRF WDF-05 BO 250ML*12 L242

(Contd. of page 12)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

13/13 www.griffon.eu