

Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

## · 1.1 Product identifier

- · Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

### · Further information obtainable from: Bison QESH

· 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

# **SECTION 2: Hazards identification**

### · 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:
- EUH208 Contains trimethoxyvinylsilane. May produce an allergic reaction.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

### · Description: Adhesive

# · Dangerous components: CAS: 2768-02-7 trimethoxyvinylsilane 2.5-10% EINECS: 220-449-8 Image: Case of the state o

(Contd. on page 2)



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

	CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide � Carc. 2, H351, EUH212	ntd. of page 1) ≥0.1-<1%	
	CAS: 2768-02-7 EINECS: 220-449-8 Index number: 014-049-00-0 Reg.nr.: 01-2119513215-52	trimethoxyvinylsilane � Flam. Liq. 2, H225; � Skin Sens. 1B, H317	≥0.1-<1%	
	CAS: 52829-07-9 EINECS: 258-207-9 Reg.nr.: 01-2119537297-32	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	<0.25%	
_	• Additional information: For the wording of the listed hazard phrases refer to section 16.			

# **SECTION 4: First aid measures**

### · 4.1 Description of first aid measures

- General information: No special measures required.
- · After inhalation:
- Supply fresh air; consult doctor in case of complaints. No special measures required.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

# **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures Not required.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

IE-EN



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

(Contd. of page 2)

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly. · Information about fire - and explosion protection: No special measures required.

### • 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Wash hands before breaks and at the end of work. · Respiratory protection: Not required.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Goggles recommended during refilling

(Contd. on page 4)

IE-EN



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

(Contd. of page 3)

9.1 Information on basic physical and o	chemical properties
General Information Physical state	Fluid
Colour:	Beige
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	Undetermined.
Flammability	
Lower and upper explosion limit	Not applicable.
Lower:	Not determined.
	Not determined.
Upper: Elash point:	98 °C
Flash point:	
Decomposition temperature:	Not determined. Not determined.
pH Viscosity:	
Viscosity:	Not determined.
Kinematic viscosity Dynamic at 20 °C:	100000 mPas
Solubility	100000 1115 45
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (lo	9 Not determined.
value) Vapour prossuro:	Not determined.
Vapour pressure:	
Density and/or relative density	Not determined
Density:	Not determined. Not determined.
Relative density Vapour density	
	Not determined.
9.2 Other information	All relevant physical data were determined for t
	mixture. All non-determined data are n
	measurable or not relevant for th
	characterization of the mixture.
Appearance:	
Form:	Pasty
Important information on protection of	health
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	75.4 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical h	nazard
classes	
Explosives	Void
	Void

page ∪, IE-EN -



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

		(Contd. of page 4)
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

# **SECTION 10: Stability and reactivity**

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• **10.5 Incompatible materials:** No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

		evant for classi	fication:				
13463-67-7 titanium dioxide							
Oral LD50 >20000 mg/kg (rat)							
Dermal	LD50	>10000 mg/kg (rabbit)					
Inhalative LC50/4 h >6.82 mg/l (rat)							
· Skin corrosion/irritation							
Componer		CAS No.	Method	Species	Conclusion		
Vinyltrimet			OECD No. 429	mouse, dermal	no sensitisation		
		e/irritation					
Componer	nt	CAS No.	Method	Species	Conclusion		
3-Aminopr		13822-56-5	BCOP OECD 437	cattle, eye	no ocular irritation		
trimethoxy	silane						



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

(Contd. of page 5)

Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· Acute effects (acute toxicity, irritation and corrosivity) Not applicable.

- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

### · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods

• Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

IE-EN



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

(Contd. of page 6)

<ul> <li>14.1 UN number or ID number</li> <li>ADR/ADN, IMDG, IATA</li> </ul>	not regulated -
<ul> <li>14.2 UN proper shipping name</li> <li>ADR/ADN, IMDG, IATA</li> </ul>	not regulated
· 14.3 Transport hazard class(es)	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
· 14.4 Packing group · ADR/ADN, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
<ul> <li>14.7 Maritime transport in bulk according IMO instruments</li> </ul>	<b>ng to</b> Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· IMDG · Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified ir packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	not regulated

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II REPORTABLE EXPLOSIVES PRECURSORS
  - None of the ingredients is listed.

(Contd. on page 8)



Printing date 08.02.2023

Version number 5 (replaces version 4)

Revision: 08.02.2023

#### Trade name: GRF PM FIX&SEAL EXP BE CQ 425G\*12 L221

(Contd. of page 7)

### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H351 Suspected of causing cancer.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

- · Department issuing SDS: Bison QESH
- · Contact: Reach coordinator
- Date of previous version: 30.07.2021
- · Version number of previous version: 4

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Carc. 2: Carcinogenicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 \* Data compared to the previous version altered. IE-EN