

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** Adhesive

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

· **Further information obtainable from:** PSRA

· **1.4 Emergency telephone number:**

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2    H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

STOT SE 3      H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02



GHS07



GHS09

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
ethyl acetate  
heptane
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501 Dispose of contents/container in accordance with national regulations.
- **Additional information:**  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains Rosin. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Adhesive

· **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-005	heptane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0 Reg.nr.: Exempt	magnesium oxide substance with a Community workplace exposure limit	1-2.5%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32	Rosin ⚠ Skin Sens. 1, H317	≥0.1-<1%

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 2)

CAS: 68610-51-5

EINECS: 271-867-2

Reg.nr.: 01-2119496062-39-0000

phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

<1%

⚠ Repr. 2, H361d; Aquatic Chronic 4, H413

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** No special measures required.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

IE

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**141-78-6 ethyl acetate**

OEL (Ireland)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm IOELV
---------------	---

IOELV (EU)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
------------	--

**1309-48-4 magnesium oxide**

OEL (Ireland)	Short-term value: 10** mg/m <sup>3</sup> Long-term value: 4* 5** 10*** mg/m <sup>3</sup> *respirable dust **fume ***total inhalable dust
---------------	--

· **DNELs**

**141-78-6 ethyl acetate**

Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	37 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	734 mg/m <sup>3</sup>
	Consumer, inhalative, longterm exposition	367 mg/m <sup>3</sup>

· **PNECs**

**141-78-6 ethyl acetate**

Fresh water	0.26 mg/l
Marine water	0.026 mg/l

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 4)

Soil	0.22 mg/kg
------	------------

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

77-78 °C

· **Flammability**

Highly flammable.

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· <b>Lower and upper explosion limit</b></li> <li>· <b>Lower:</b> 2.1 Vol %</li> <li>· <b>Upper:</b> 11.5 Vol %</li> <li>· <b>Flash point:</b> -4 °C</li> <li>· <b>Auto-ignition temperature:</b> 460 °C</li> <li>· <b>Decomposition temperature:</b> Not determined.</li> <li>· <b>pH</b> Not determined.</li> <li>· <b>Viscosity:</b></li> <li>· <b>Kinematic viscosity</b> Not determined.</li> <li>· <b>Dynamic at 20 °C:</b> 3750 mPas</li> <li>· <b>Solubility</b></li> <li>· <b>water:</b> Not miscible or difficult to mix.</li> <li>· <b>Partition coefficient n-octanol/water (log value)</b> Not determined.</li> <li>· <b>Vapour pressure at 20 °C:</b> 97 hPa</li> <li>· <b>Vapour pressure at 50 °C:</b> 360 hPa</li> <li>· <b>Density and/or relative density</b></li> <li>· <b>Density:</b> Not determined.</li> <li>· <b>Relative density</b> Not determined.</li> <li>· <b>Vapour density</b> Not determined.</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b> All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.</li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b> Fluid</li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b> Product is not selfigniting.</li> <li>· <b>Explosive properties:</b> Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</li> <li>· <b>Solvent content:</b></li> <li>· <b>Organic solvents:</b> 73.9 %</li> <li>· <b>Water:</b> 0.1 %</li> <li>· <b>VOC (EC)</b> 73.86 %</li> <li>· <b>Solids content:</b> 26.0 %</li> <li>· <b>Change in condition</b></li> <li>· <b>Evaporation rate</b> Not determined.</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b> Void</li> <li>· <b>Flammable gases</b> Void</li> <li>· <b>Aerosols</b> Void</li> <li>· <b>Oxidising gases</b> Void</li> <li>· <b>Gases under pressure</b> Void</li> <li>· <b>Flammable liquids</b> Highly flammable liquid and vapour.</li> <li>· <b>Flammable solids</b> Void</li> <li>· <b>Self-reactive substances and mixtures</b> Void</li> <li>· <b>Pyrophoric liquids</b> Void</li> </ul>	

(Contd. on page 7)

IE

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 6)

· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · **LD/LC50 values relevant for classification:**

##### 141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**  
Not applicable.  
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.

(Contd. on page 8)

IE

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 7)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR/ADN, IMDG, IATA**

UN1133

· **14.2 UN proper shipping name**

· **ADR/ADN**

1133 ADHESIVES

· **IMDG**

ADHESIVES, MARINE POLLUTANT

· **IATA**

ADHESIVES

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

Trade name: UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 8)

· **14.3 Transport hazard class(es)**

· **ADR/ADN**



· **Class** 3 (F1) Flammable liquids.  
 · **Label** 3

· **IMDG**



· **Class** 3 Flammable liquids.  
 · **Label** 3

· **IATA**



· **Class** 3 Flammable liquids.  
 · **Label** 3

· **14.4 Packing group**

· **ADR/ADN, IMDG, IATA** III

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances: heptane  
 · **Marine pollutant:** Symbol (fish and tree)  
 · **Special marking (ADR/ADN):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Flammable liquids.  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-E,S-D  
 · **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**  
 · **Quantity limitations** On passenger aircraft/rail: 60 L  
 On cargo aircraft only: 220 L

· **ADR/ADN**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 9)

· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 17 (replaces version 16)

Revision: 30.01.2024

**Trade name:** UHU POWER CONTACT FB 50ML\*10 L037

(Contd. of page 10)

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** UHU QESH

· **Contact:** UHU QESH

· **Date of previous version:** 28.10.2022

· **Version number of previous version:** 16

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· **\* Data compared to the previous version altered.**

IE