

Printing date 01.08.2024 Version number 18 (replaces version 17)

Revision: 01.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

Fax: 0049-(0)7223-284-245

· Further information obtainable from: PSRA

E-mail: sds@boltonadhesives.com

· 1.4 Emergency telephone number: Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labelling: methyl acetate
- Acetone
- Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

IE



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 1)

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

• Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

 Dangerous components: 		
CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX	methyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	Acetone Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

IF



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 2)

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

(Contd. on page 4)



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 3)

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

• 7.3 Specific end use(s) No further relevant information available.

SECTIO	N 8: Exposure controls/personal p	protection
	ol parameters	
	ts with limit values that require monitoring	ng at the workplace:
-	ethyl acetate	<u>.</u>
OEL (Irela	nd) Short-term value: 760 mg/m³, 250 ppm	
, ,	Long-term value: 610 mg/m ³ , 200 ppm	
64-17-5 et	hanol	
	nd) Short-term value: 1000 ppm	
67-64-1 A	cetone	
OEL (Irela	nd) Long-term value: 1210 mg/m³, 500 ppr IOELV	n
IOELV (El	J) Long-term value: 1210 mg/m³, 500 ppr	n
·DNELs		
79-20-9 m	ethyl acetate	
Oral	Consumer, oral, longterm exposition	21.5 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	43 mg/kg bw/day
	Consumer, dermal, shortterm exposition	203 mg/kg bw/day
	Consumer, dermal, longterm exposition	21.5 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	3777 mg/m ³
	Worker, inhalative, longterm exposition	300 mg/m ³
	Consumer DNEL, acute inhalation	3777 mg/m ³
	Consumer, inhalative, longterm exposition	0
64-17-5 et	hanol	
Oral	Consumer, oral, longterm exposition	87 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	343 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	206 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	1900 mg/m³ (rat)
	Worker, inhalative, longterm exposition	950 mg/m³ (rat)
	Consumer DNEL, acute inhalation	950 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	114 mg/m ³
67-64-1 A	cetone	1
Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	186 mg/kg bw/day
	Consumer, dermal, longterm exposition	62 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	2420 mg/m³
	Worker, inhalative, longterm exposition	1210 mg/m ³
	Consumer, inhalative, longterm exposition	200 mg/m ³
		(Contd. on page 5)



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

	(Contd. of page 4)
· PNECs	
79-20-9 methyl acetate	
Oral Secondary Poisoning	20.4 mg/kg
Fresh water	0.12 mg/l
Fresh water sediment	0.128 mg/kg dry weight
Marine water	0.012 mg/l
Marine sediment	0.013 mg/kg dry weight
Soil	0.0416 mg/kg
Sewage treatment plant	600 mg/l
64-17-5 ethanol	
Fresh water	0.96 mg/l
Fresh water sediment	3.6 mg/kg dry weight (rat)
Marine water	0.79 mg/l
Marine sediment	2.9 mg/kg dry weight (rat)
Soil	0.63 mg/kg
Sewage treatment plant	
Sporadic release	2.75 mg/l (rat)
67-64-1 Acetone	
Fresh water	10.6 mg/l
Fresh water sediment	30.4 mg/kg dry weight
Marine water	1.06 mg/l
Marine sediment	3.04 mg/kg dry weight
Soil	29.5 mg/kg
Sewage treatment plant	
Sporadic release	21 mg/l
•	lists valid during the making were used as basis.
Individual protection measure General protective and hygic The usual precautionary mease Wash hands before breaks an Do not inhale gases / fumes / a Respiratory protection: Not re Hand protection The glove material has to b preparation.	sures are to be adhered to when handling chemicals. d at the end of work. aerosols.
Recommended thickness of th	ne material: > 0,12 mm
Nitrile rubber, NBR	

(Contd. on page 6)



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 5)

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

	-
· 9.1 Information on basic physical and chem	ical properties
· General Information	
· Physical state	Fluid
· Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	•••••••
boiling range	55.8-56.6 °C
Flammability	Highly flammable.
· Lower and upper explosion limit	
· Lower:	3.1 Vol %
· Upper:	16 Vol %
· Flash point:	-13 °C
· Auto-ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	4400 mPas
	4400 IIIFas
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	Not determined
value) Vancur processo at 20 °C:	Not determined.
Vapour pressure at 20 °C:	220 hPa
Vapour pressure at 50 °C:	800 hPa
· Density and/or relative density	$0.087 a/am^3$
· Density at 20 °C:	0.987 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
	(Contd. on page 7



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

	(Contd. of page
· Appearance:	
· Form:	Fluid
 Important information on protection of heat 	alth
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o
	explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	65.8 %
· Water:	0.4 %
· VOC (EC)	65.79 %
· Solids content:	33.8 %
· Change in condition	
· Evaporation rate	Not determined.
Flammable gases	Void
· Explosives	Void
· Aerosols	Void
• Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
• Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 8)

IF



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

(Contd. of page 7)

)N 11: I 0	oxicological information	
		h hazard classes as defined in Regulation (EC) No 1272/20 ad on available data, the classification criteria are not met.	008
· LD/LC50	values rel	evant for classification:	
79-20-9 n	nethyl acei	tate	
Oral	LD50	3705 mg/kg (rabbit)	
64-17-5 e	thanol		
Oral	LD50	10470 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	៖ LC50/4 h	120 mg/l (rat)	
67-64-1 A			
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rat)	
		76 mg/l (rat) ation Based on available data, the classification criteria are n	
STOT-sir STOT-rep Aspiratio Addition Acute eff Sensitisa Repeated	ngle expos peated exp on hazard E al toxicolo fects (acute ation Not a d dose toxi rmation on	icity Not applicable. A other hazards	not met.
Endocrin	•	ng properties	
Endocrin	•	ng properties nts is listed.	
• Endocrin None of the	he ingredie		
 Endocrin None of the SECTIC 12.1 Toxi Aquatic to 12.2 Pers 12.3 Bioa 12.4 Mob 12.5 Rest PBT: Not vPvB: Not 12.6 End 	he ingredie DN 12: Ec icity toxicity: No sistence ar accumulati pility in soil ults of PBI t applicable ot applicable ocrine disi	of urther relevant information available. of degradability No further relevant information available. ve potential No further relevant information available. I No further relevant information available. I No further relevant information available. I and vPvB assessment	



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 8)

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

12.7 Other adverse effects

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.


Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.





Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

	(Contd. of page 9
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. -
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 60 L
Quantity minitations	On cargo aircraft only: 220 L
ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
Transport category	3
Tunnel restriction code	E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100 ml
Remarks:	For substances with class 3 according to IMDG
ולכווומו הס.	Code chapter 2.3.2.2 packing group is classifie
	in packing group III, as viscosity is in accordance
	with requirements (flow time $t > 100s$).
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III
on mousi Regulation .	

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 11)



Printing date 01.08.2024

Version number 18 (replaces version 17)

Revision: 01.08.2024

(Contd. of page 10)

3

3

Trade name: UHU all purpose FB 20ml EN/ID/PRC/TW/TH

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 Acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 Acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 Acetone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

 Classification according to Regulation (EC) 	No 1272/2008	
Flammable liquids	Bridging principles	
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS: PSRA

- · Contact: PSRA
- · Date of previous version: 15.01.2022
- · Version number of previous version: 17
- · Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3