

Safety data sheet according to 1907/2006/EC, Article 31

Version number 11 (replaces version 10) Printing date 21.11.2023

Revision: 06.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: UHU HART FB 35G/33ML*10 ENES
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: methyl acetate

n-butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

IE-EN

1/11 www.uhu.com



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing vapours.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

Dangerous components:		
CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX	methyl acetate The Flam. Liq. 2, H225; The Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%
CAS: 9004-70-0 EC number: 682-719-5	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Triangle Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	2.5-10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

IE-EN

www.uhu.com 2/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 2)

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

(Contd. on page 4)

IE-EN

www.uhu.com 3/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· ingredients with limit values that require monitoring at the workplace:			
	79-20-9 methyl acetate		
OEL (Ireland)	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm		
	123-86-4 n-butyl acetate		
OEL (Ireland)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm IOELV		
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm		

· DNELs

79-20-9 methyl acetate

Oral	Consumer, oral, longterm exposition	44 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	44 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	mg/m³ (rat)
		mg/m³ (rabbit)
	Consumer, inhalation, longterm exposition	131 mg/m³

123-86-4 n-butyl acetate

Oral	Consumer, oral, longterm exposition	3.4 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	3.4 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	102.34 mg/m ³

· PNECs

79-20-9 methyl acetate

Fresh water	
Marine water	
Soil	0.0416 mg/kg

123-86-4 n-butyl acetate

	•
Fresh water	0.18 mg/l
Marine water	
Soil	0.0903 mg/kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

IF-FN

www.uhu.com 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Ester-like
Not determined.

Undetermined.

Boiling point or initial boiling point and

boiling range 57 °C

• Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 3.1 Vol %
Upper: 16 Vol %
Flash point: -10 °C
Ignition temperature: 180 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 9000 mPas

·Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

(Contd. on page 6)

IE-EN

www.uhu.com 5/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 5)

· Vapour pressure at 20 °C: 220 hPa · Density and/or relative density Density at 20 °C: 1.115 g/cm³ · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: Organic solvents: 68.7 % · VOC (EC) 68.72 % 31.3 % Solids content: · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Highly flammable liquid and vapour. Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void

Void

Void

Void

SECTION 10: Stability and reactivity

· Organic peroxides

· Corrosive to metals

Desensitised explosives

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)

IE-EN

www.uhu.com 6/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 6)

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
79-20-9 m	79-20-9 methyl acetate		
Oral	LD50	3705 mg/kg (rabbit)	
123-86-4 ו	123-86-4 n-butyl acetate		
Oral	LD50	13100 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/l (rat)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

- IF-FN

www.uhu.com 7/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- **Uncleaned packaging:**
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number	or ID number
------------------	--------------

· ADR/ADN, IMDG, IATA UN1133

14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES, special provision 640D

· IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR/ADN



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG, IATA



Class 3 Flammable liquids.

· Label 3

(Contd. on page 9)

IE-EN

www.uhu.com 8/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

	(Contd. of page
14.4 Packing group ADR/ADN, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D E
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 50 ml
· UN "Model Regulation":	ml UN 1133 ADHESIVES, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

IE-EN

www.uhu.com 9/11



Safety data sheet according to 1907/2006/EC, Article 31

Version number 11 (replaces version 10) Revision: 06.05.2023 Printing date 21.11.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 9) · REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

ſ	· Classification according to Regulation (EC) No 1272/2008	
ı	Flammable liquids	Bridging principles
	Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

Date of previous version: 25.10.2022 · Version number of previous version: 10

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 11)

IE-EN

10/11 www.uhu.com



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2023 Version number 11 (replaces version 10) Revision: 06.05.2023

Trade name: UHU HART FB 35G/33ML*10 ENES

(Contd. of page 10)

Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

IE-EN

11/11 www.uhu.com