

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** UHU POR FB 40G/50ML*10 L065
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
UHU GmbH
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.: 0049-(0)7223-284-0
E-mail: sds@boltonadhesives.com
Fax: 0049-(0)7223-284-245
- **Further information obtainable from:** PSRA
- **1.4 Emergency telephone number:**
Emergency medical information: 8am-10pm (seven days) contact
National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Classification needs to be in accordance with the NZ Hazardous Substances (Hazard Classification) Notice 2020**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

IE

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 1)

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P302+P352 IF ON SKIN: Wash with plenty of water.
P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

EUH208 Contains zinc bis(dibutyldithiocarbamate). May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable

· **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

EC number: 927-510-4 Reg.nr.: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41-XXXX	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≥1-<2.5%
CAS: 136-23-2 EINECS: 205-232-8 Index number: 006-081-00-9 Reg.nr.: 01-2119956966-16-XXXX	zinc bis(dibutyldithiocarbamate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** No special measures required.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3

(Contd. on page 4)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

110-82-7 cyclohexane

OEL (Ireland)	Long-term value: 700 mg/m ³ , 200 ppm
IOELV	
IOELV (EU)	Long-term value: 700 mg/m ³ , 200 ppm

· **DNELs**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	Consumer, oral, longterm exposition	149 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	300 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	149 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	2085 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	477 mg/m ³ (rat)

110-82-7 cyclohexane

Oral	Consumer, oral, longterm exposition	59.4 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	2016 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	1186 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, shortterm exposition	700 mg/m ³ (rat)
	Worker, inhalative, longterm exposition	700 mg/m ³ (rat)
	Consumer DNEL, acute inhalation	412 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	206 mg/m ³ (rat)

· **PNECs**

110-82-7 cyclohexane

Fresh water	0.207 mg/l (rat)
Fresh water sediment	3.627 mg/kg dry weight (rat)
Marine water	0.207 mg/l (rat)
Marine sediment	3.627 mg/kg dry weight (rat)
Soil	2.99 mg/kg (rat)
Sewage treatment plant	3.24 mg/l (rat)
Sporadic release	0.207 mg/l

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

IE

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Physical state**

Liquid

· **Colour:**

Yellowish

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined

· **Melting point/freezing point:**

Undetermined

· **Boiling point or initial boiling point and boiling range**

83-105 °C

· **Flammability**

Highly flammable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined

· **Upper:**

Not determined

· **Flash point:**

-4 °C

· **Decomposition temperature:**

Not determined

· **pH**

Not determined

· **Viscosity:**

· **Kinematic viscosity**

Not determined

(Contd. on page 6)

IE

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 5)

· Dynamic at 20 °C:	8000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure:	Not determined
· Density and/or relative density	
· Density at 20 °C:	0.805 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	69.2 %
· VOC (EC)	69.19 %
· Solids content:	30.8 %
· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

(Contd. on page 7)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 6)

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)

110-82-7 cyclohexane

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	32.88 mg/l (rat)

136-23-2 zinc bis(dibutyldithiocarbamate)

Oral	LD50	>5000 mg/kg (rabbit)
Dermal	LD50	>2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable

(Contd. on page 8)

IE

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 7)

- **Sensitisation** Not applicable
- **Repeated dose toxicity** Not applicable
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR/ADN, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**
- **ADR/ADN** 1133 ADHESIVES
- **IMDG** ADHESIVES, MARINE POLLUTANT

(Contd. on page 9)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 8)

· IATA		ADHESIVES
· 14.3 Transport hazard class(es)		
· ADR/ADN		
 		
· Class		3 (F1) Flammable liquids.
· Label		3
· IMDG		
 		
· Class		3 Flammable liquids.
· Label		3
· IATA		
		
· Class		3 Flammable liquids.
· Label		3
· 14.4 Packing group		
· ADR/ADN, IMDG, IATA		III
· 14.5 Environmental hazards:		Product contains environmentally hazardous substances: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
· Marine pollutant:		Symbol (fish and tree)
· Special marking (ADR/ADN):		Symbol (fish and tree)
· 14.6 Special precautions for user		Warning: Flammable liquids.
· Hazard identification number (Kemler code): -		
· EMS Number:		F-E, S-D
· Stowage Category		A
· 14.7 Maritime transport in bulk according to IMO instruments		Not applicable
· Transport/Additional information:		
· Quantity limitations		On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN		
· Limited quantities (LQ)		5L
· Excepted quantities (EQ)		Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

(Contd. on page 10)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 9)

·	ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time $t > 100s$).
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026

Version number 19 (replaces version 18)

Revision: 18.07.2026

Trade name: UHU POR FB 40G/50ML*10 L065

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** PSRA

· **Contact:** PSRA

· **Date of previous version:** 27.10.2022

· **Version number of previous version:** 18

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

IE